

# D-Link 4G LTE M2M VPN Router

Gamintojas: **D-LINK** · Modelis: **DWM-314-T** · EAN: **790069476686** · Prekės kodas: **876006**



## 212,90 €

Kaina su PVM

Be PVM: **175,95 €**

**Sandėlyje**



**Prekė internetu**

Nuskenaukite kodą arba apsilankykite [www.shopro.lt](http://www.shopro.lt)

## Pagrindinės savybės

- ✓ 4G with one SIM slots for cellular WAN
- ✓ 4 Fast Ethernet LAN ports ensure reliable connectivity and reduce extra switch cost
- ✓ Plug & Play design for quick and easy integration
- ✓ Durable zinc-plated steel case is corrosion-resistant to ensure device longevity
- ✓ -30 to 70°C operating temperature to resist harsh environments
- ✓ Wall or DIN-rail mounting allow for optimal device placement



## Aprašymas

### Plug and Play

Simple plug and play installation with auto-MDI/MDIX crossover on all ports

### Multi-Port FE Connectivity

Four Fast Ethernet LAN ports to connect multiple devices for general M2M applications.

### SMS Event Management

Facilitate remote management via SMS, minimizing staff exposure to hazardous environments.

## Industrial-Grade Durability

Corrosion-resistant zinc-plated steel casing and robust design ensure reliable operation in harsh environments.

## Secure VPN Protection

Protect sensitive data transmission via secure VPN tunnels to prevent unauthorized network access.

## Centralized Management

Conveniently manage devices from anywhere via the D-ECS management platform.

## Optimize Smart Parking with 4G LTE Connectivity

The DWM-314-T 4G Multi-Connect Modem enhances smart parking solutions with uninterrupted 4G LTE connectivity, facilitating real-time data transmission to alleviate traffic congestion and increase parking efficiency. This modem features a built-in 4-port Gigabit switch, minimizing the extra power supply wires and the need for additional equipment, reducing extra switch cost and installation complexity. Secure VPN technology protects vehicle information and parking fee transactions, ensuring robust security for both drivers and parking management.

## Plug & Play for Easy Installation

Simply insert a Nano-SIM card (4FF) and power up; the DWM-314-T instantly connects your M2M devices to the robust 4G LTE cellular network. This modem's rugged, compact design is perfect for any setting, including harsh environments, offering flexible wall and DIN-rail mounting options. Designed for effortless, real-time remote access, it provides reliable long-distance connectivity ideal for various applications.

## Robust Build Quality

The industrial-grade casing provides reliable high-speed connectivity in extreme conditions. The corrosion-resistant zinc-plated steel case with wide operating temperature range and humidity tolerance mean that the DWM-314-T is ready for the most demanding M2M applications in virtually any environment.

## Techninė specifikacija

| Design                      |                         |
|-----------------------------|-------------------------|
| Device type                 | Cellular network router |
| Product colour              | Black                   |
| Mounting                    | DIN-rail                |
| Reset button                | Yes                     |
| LED indicators              | Yes                     |
| Ethernet LAN features       |                         |
| Ethernet LAN                | Yes                     |
| Ethernet LAN interface type | Fast Ethernet           |
| Ethernet LAN data rates     | 10,100 Mbit/s           |
| DHCP server                 | Yes                     |
| Wireless LAN features       |                         |

|                                   |             |
|-----------------------------------|-------------|
| Wi-Fi                             | No          |
| <b>Mobile network</b>             |             |
| Data network                      | 4G          |
| 4G standard                       | LTE         |
| Number of SIM cards               | 1           |
| <b>Ports &amp; interfaces</b>     |             |
| Ethernet LAN (RJ-45) ports        | 4           |
| <b>Security</b>                   |             |
| Security algorithms               | SSH         |
| Network address translation (NAT) | Yes         |
| Firewall                          | Yes         |
| Port forwarding                   | Yes         |
| <b>Certificates</b>               |             |
| Certification                     | CE; UKCA    |
| <b>Performance</b>                |             |
| Web-based management              | Yes         |
| Antenna type                      | External    |
| Antenna connector type            | SMA         |
| Antennas quantity                 | 2           |
| <b>Power</b>                      |             |
| Power source type                 | DC          |
| Input voltage                     | 9 - 36 V    |
| <b>Operational conditions</b>     |             |
| Operating temperature (T-T)       | -30 - 70 °C |
| Storage temperature (T-T)         | -40 - 85 °C |
| Operating relative humidity (H-H) | 10 - 95%    |
| Storage relative humidity (H-H)   | 0 - 95%     |
| <b>Weight &amp; dimensions</b>    |             |
| Width                             | 115 mm      |
| Depth                             | 99 mm       |
| Height                            | 31 mm       |
| <b>Matmenys ir svoris</b>         |             |
| Svoris                            | 1,05kg      |

## Dokumentai ir vaizdo įrašai

> [Gaminio lankstinukas](#)

## Gamintojo ir saugos informacija

GAMINTOJAS

**D-Link**

ATSAKINGAS ASMUO ES

**D-Link Benelux**

Postbus 48, 5480 AA Schijndel, NL

[dlink.com](https://dlink.com)

PLATINTOJAS

**MB KOMPIUTERIŲ GURU**

V. Nagevičiaus g. 3, LT-08237 Vilnius

[info@shopro.lt](mailto:info@shopro.lt)