

Viewsonic LS741HD duomenų projektorius 5000 ANSI lumens DMD 1080p (1920x1080) Juoda, Balta

Gamintojas: **VIEWSONIC** · Modelis: **LS741HD** · EAN: **766907026092** · Prekės kodas: **880251**



1 683,90 €

Kaina su PVM

Be PVM: **1 391,65 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Juoda, Balta
- ✓ DMD 5000 ANSI lumens
- ✓ Lazeris 20000 h
- ✓ 1080p (1920x1080) 3000000:1
- ✓ Ekranų dydžio suderinamumas: 762 - 7620 mm (30 - 300") Spalvų skaičius: 1,07 milijardo spalvų
- ✓ Fokusas: Rankinis Priartinimo galimybė
- ✓ Ethernet LAN jungtis
- ✓ Įmontuoti garsiakalbiai 15 W
- ✓ AC 210 W





Aprašymas

OVERVIEW

The LS741HD is part of ViewSonic's Luminous Superior Series, a lamp-free projector lineup designed for commercial and educational spaces. It can project up to a 300" ultra-large screen in 1080p Full HD resolution with high native contrast. This DLP projector uses 3rd generation laser phosphor technology, delivering a brightness of 5,000 ANSI Lumens for up to 30,000 hours. Its lamp-free design offers an eco-friendly and cost-effective solution with less power consumption, while its lightweight and compact build reduces transportation costs. Equipped with features like a 1.6x optical zoom, H/V keystone, and 360° projection capabilities, the LS741HD offers flexible setup possibilities. Additionally, its comprehensive LAN control allows centralized management, making it perfect for boardrooms, lecture halls, and public spaces.

Bright, Compact, Durable

The LS741HD incorporates advanced 3rd-gen laser phosphor technology, enhancing brightness by 20% and achieving better luminous efficiency, all while being 32% more compact and more accessible than the previous generation. Its lamp-free light source offers instant power on/off and a lifespan of up to 30,000 hours without maintenance, ensuring consistent image quality even during extended periods of use.

Bright Images for Large Venues

Delivering 5,000 ANSI Lumens, the LS741HD provides vibrant and sharp projection in 1080p FHD in all lighting conditions for gallery, restaurant, gym, and other expansive spaces.

Save on Costs and Energy

With its advanced lamp-free light source, the LS741HD offers a highly energy-efficient and cost-saving display solution by consuming up to 51% less power than competing projectors.

Unmatched Contrasts, Enhanced Visibility

This projector utilizes the advanced 0.65" DMD chip from Texas Instruments, surpassing the capabilities of the 0.47" standard chip. It offers a high native contrast ratio for deeper blacks, resulting in clearer, more legible images with enhanced visual depth.

Enhanced Installation Flexibility

Equipped with a 1.6x optical zoom, the projector allows users to choose the most ideal set-up location within a range, getting the desired image size without needing to change the existing interior design.

Centralized Control for Management Efficiency

The LS741HD is compatible with Crestron, AMX, PJ Link, ATEN, and Extron systems, allowing for centralized device management for better operational efficiency.

Easy and Cost-effective Installation

The LS741HD is 33% lighter in weight and 32% smaller in size compared to its predecessor and even most competing projectors in the market, greatly reducing the cost of transportation and increasing the ease of installation.

Ultra-large Screen with Lower Cost-per-inch

This easy-to-install projector allows for an image size of up to 300", offering a lower cost-per-inch compared to other types of commercial displays.

Upgrade Your Projector with Wireless Content Casting

Enhance your projector with the WPD-700 Wireless Screen Casting Kit for seamless wireless content sharing. The projector's built-in 5V/1.5A USB-A output powers the dongle, enabling simultaneous multimedia streaming and power charging without adapters.

Get Perfectly-shaped Images Effortlessly

Horizontal and Vertical Keystone correction along with 4 corner adjustment features eliminate crooked or distorted images for a perfectly proportioned picture every time.

Improved Dust Resistance for Enhanced Durability

This DLP projector's innovative sealed engine, rated IP6X, prevents dust from affecting internal components without using an air filter. It ensures longer product life and consistent image quality, even in environments with poor air quality, saving on maintenance costs and efforts.

Versatile Creative Applications

The projector can rotate vertically at any angle, enabling projection onto ceilings, walls, or floors, and its portrait mode further expands its capabilities for projection mapping, staging, and creative advertising applications.

Non-stop 24/7 Operation

The projector's advanced cooling design enables 24/7 operation without any degradation in image quality or performance. This makes it the go-to solution for applications that require continuous projection in retail stores, malls, museums, airports, and other public spaces.

A Simpler Way to Update Projector Software

Skip trips to the service center by keeping software up to date easily via USB cable connection with your own laptop.

Techninė specifikacija

Prožektorius	
Projektoriaus ryškumas	5000 ANSI lumens
Projektavimo technologija	DMD
Projektoriaus natūrali rezoliucija	1080p (1920x1080)
Kontrasto santykis (tipinis)	3000000:1
Ekrano dydžio suderinamumas	762 - 7620 mm (30 - 300")
Projektavimo atstumas	0,93 - 14,88 m
Spalvų skaičius	1,07 milijardo spalvų
Horizontali diapazono riba	15 - 102 kHz

Vertikali diapazono riba	24 - 120 Hz
Pagrindo koregavimas, horizontalus	-30 - 30°
Pagrindo koregavimas, vertikalus	-30 - 30°
Šviesos šaltinis	
Šviesos šaltinio tipas	Lazeris
Šviesos šaltinio naudingo tarnavimo trukmė	20000 h
Šviesos šaltinio naudingo tarnavimo trukmė (ekonominis režimas)	30000 h
Lęšių sistema	
Fokusas	Rankinis
Židinio nuotolis	20.911 - 32.62 mm
Diafragmos intervalas	2,5 - 3,26
Priartinimo galimybė	Taip
Priartinimo santykis	0.8 - 2.0:1
Rodymo santykis	1.4 - 2.24
Kompensavimas	132%
Video	
Pilnas HD	Taip
Palaikomos grafikos rezoliucijos	640 x 480 (VGA)
Palaikomi vaizdo režimai	480i, 480p, 576i, 576p, 1080i, 1080p
Ryšys	
HDMI portų kiekis	2
Nuosekliosios sąsajos tipas	RS-232
HDMI jungties tipas	Viso dydžio
HDMI versija	1.4
USB 2.0 portų kiekis	1
USB 2.0 A tipo prievadų skaičius	1
Ausinių išvestys	1
„Enhanced Audio Return Channel“ (eARC)	Taip
Tinklas	
Ethernet LAN jungtis	Taip
Ethernet LAN (RJ-45) portų kiekis	1
Savybės	
Garso lygis	30 dB
Triukšmo lygis (ekonomiško veikimo režimas)	24 dB

HDCP	Taip
Virtualusis ekranas (OSD)	Taip
On Screen Display (OSD) kalbos	Arabų, Supaprastinta kinų, Tradicinė kinų, Čekų, Vokiečių kalba, Olandų kalba, Anglų kalba, Ispanų kalba, Suomių kalba, Prancūzų kalba, Graikų, Indoneziečių, Italų kalba, Japonų, Korėjiečių, Norvegų kalba, Lenkų kalba, Portugalų kalba, Rusų kalba, Švedų kalba, Tajų, Turkų, Vietnamiečių
OSD kalbų skaičius	23
Multimedija	
Įmontuoti garsiakalbiai	Taip
RMS galingumas	15 W
Įmontuotų garsakalbių skaičius	1
Konstrukcija	
Produkto spalva	Juoda, Balta
Ekranas	
Įmontuotas ekranas	Taip
Energijos valdymas	
Maitinimo šaltinis	AC
Energijos suvartojimas	210 W
Energijos suvartojimas (laukimo režimu)	0,5 W
AC įėjimo įtampa	100-240 V
AC įėjimo dažnis	50/60 Hz
Aplinkos sąlygos	
Darbo temperatūros diapazonas (TT)	0 - 40 °C
Svoris ir matmenys	
Svoris	2,97 kg
Plotis	286 mm
Ilgis	216 mm
Aukštis	129 mm
Pakuotės plotis	400 mm
Pakuotės gylis	155 mm
Pakuotės aukštis	280 mm
Paketo svoris	5,1 kg
Pakuotės turinys	
Pridedamas nuotolinio valdymo pultelis	Taip
Pridėti kabeliai	AC

Instrukcija	Taip
Logistikos duomenys	
Padėklo bendrasis ilgis	102 cm
Padėklo bendrasis plotis	122 cm
Padėklo bendrasis aukštis	181 cm
Gaminių skaičius pagrindinėje (išorinėje) dėžėje	1 vnt
Darniosios sistemos (DS) kodas	8528620000
Matmenys ir svoris	
Svoris	3,88kg

Dokumentai ir vaizdo įrašai

- › [Naudojimo instrukcija](#)
- › [Gaminio lankstinukas](#)
- › [Vaizdo įrašas](#) youtube.com/watch?v=0Bc_iGYbD1c

Gamintojo ir saugos informacija

GAMINTOJAS

Viewsonic

ATSAKINGAS ASMUO ES

ViewSonic Technology GMBH

Fürst-Leopold-Platz 1, 46284 Dorsten, DE

viewsonic.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt