

StarTech.com 2 Port VGA Video Splitter - USB Powered

Gamintojas: **STARTECH.COM** · Modelis: **ST122LE** · EAN: **065030825856** · Prekės kodas: **881139**



37,90 €

Kaina su PVM

Be PVM: **31,32 €**

Sandėlyje



Prekė internetu

Nuskuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Video port type: VGA Video ports quantity: 2 Black
- ✓ 2048 x 1536 pixels
- ✓ Maximum operating distance: 61 m
- ✓ Bandwidth: 300 MHz



Aprašymas

Compact USB-powered VGA splitter allows you to split a video source to two separate displays

This 2-Port VGA Video Splitter allows a computer to display VGA video on two monitors simultaneously.

Perfect for classrooms, tradeshow, or any environment requiring high quality video on several monitors, the ST122LE VGA splitter supports displays with up to 300 MHz of bandwidth and up to 2048x1536 resolution. Plus, to simplify placement of your VGA displays, the splitter features a built-in booster circuit that allows you to locate VGA monitors up to 200 ft away from your system, and can be powered through a USB connection to the host computer, eliminating the need to find an available power outlet.

Application Diagram

The ST122LE VGA Splitter supports easy plug and play installation, and is backed by StarTech.com's 2-year warranty and FREE lifetime tech support.

The StarTech.com Advantage

- USB-Powered VGA video splitter, no bulky external power adapter required

- Multiple screens let you communicate your message more effectively to large audiences with greater impact
- Integrated signal amplifier boosts your connection range to 210 feet (65 meters)

Techninė specifikacija

Ports & interfaces	
Video ports quantity	2
Video port type	VGA
Video out	2x VGA
Features	
Maximum resolution	2048 x 1536 pixels
Product colour	Black
Housing material	Plastic
Maximum operating distance	61 m
Bandwidth	300 MHz
Certification	REACH, CE, FCC, TAA
Power	
Output voltage	5 V
Output current	0.5 A
USB powered	Yes
Weight & dimensions	
Weight	100 g
Packaging data	
Package width	145 mm
Package depth	210 mm
Package height	40 mm
Package weight	235 g
Packaging content	
Manual	Yes
Operational conditions	
Operating temperature (T-T)	0 - 70 °C
Storage temperature (T-T)	-20 - 85 °C
Operating relative humidity (H-H)	0 - 95%
Technical details	

Connector 1	DB15
Connector 2	DB15
Compliance certificates	RoHS
Technical features	DDC, DDC2, DDC2B
Logistics data	
Harmonized System (HS) code	85176990

Gamintojo ir saugos informacija

GAMINTOJAS

StarTech.com Ltd.

Artisans Crescent 45, N5V 5E9 Ontario, London,
CA
startech.com

ATSAKINGAS ASMUO ES

StarTech.com Limited

Laarderhoogtweg 25, 1101 EB Amsterdam, NL
startech.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt