

# StarTech.com 10-Port Industrial USB 2.0 Hub, Rugged USB Hub w/ESD Level 4 Protection, DIN/Wall/Desk-Mountable USB-A HUB, USB Port Expander w/Lockable Ports, Multiport USB Hub

 Gamintojas: **STARTECH** · Modelis: **USB210AIND-USB-A-HUB** · EAN: **065030894616** · Prekės kodas: **881177**


## 69,90 €

Kaina su PVM

 Be PVM: **57,77 €**

Sandėlyje


**Prekė internetu**

 Nuskenuokite kodą arba apsilankykite [www.shopro.lt](http://www.shopro.lt)

## Pagrindinės savybės

- ✓ **10-PORT INDUSTRIAL USB 2.0 Hub:** Cold-rolled steel construction ensures durability in harsh environments (32 to 140°F/0 to 60°C at 95% RH); 10 Locking USB-A downstream ports; USB 2.0 Compliant; 480Mbps shared bandwidth; OS independent
- ✓ **ESD PROTECTION:** Level 4 ESD rugged USB Hub features 15kV air and 8kV contact electrostatic protection for the upstream and downstream ports preventing device dropouts or damage; The Hub supplies up to 5V 0.5A per port suitable for most USB peripherals
- ✓ **FLEXIBLE MOUNTING:** Multi-port USB Hub features built-in mounting brackets for wall/desk installations; Included DIN rail mounting kit; All the USB ports on the Hub feature screw-lock connectors for preventing accidental disconnection
- ✓ **POWER OPTIONS:** Ten-port industrial Hub features power redundancy using the DC barrel plug and Terminal Block port (AC adapter not incl); 5 to 24V DC external power is required; Power the Hub via the 2-wire Terminal Block using ITB20D3250 (sold separately)
- ✓ **CONNECTIVITY TOOLS:** Optimize the performance and security of this TAA-compliant mountable USB Hub, using the included USB Event Monitoring utility (available for download)





## Aprašymas

### Metal Construction | 6ft (1.8m) USB Host Cable Included

This TAA-compliant 10-port industrial USB 2.0 Hub delivers scalability and protection in harsh industrial environments by providing a high number of USB ports with ESD level 4 protection. The durable metal housing construction is ideal for industrial applications. For power connectivity, the Hub features power redundancy using the DC barrel plug and terminal block port. Finish the installation by mounting the Hub to a DIN rail using the included hardware or on a desk or wall with the built-in mounting brackets.

### Rugged Construction

This industrial USB 2.0 Hub delivers reliable performance in the most challenging conditions where operating temperatures range from 32 to 140°F (0 to 60°C) at 95% relative humidity.

The ESD level 4 protection (15kV air and 8kV contact) ensures your equipment is protected from electrostatic damage. An external power source is required, 5 to 24V DC. Optionally, StarTech.com offers part ITB20D3250 to power the Hub via the 2-wire terminal block port.

### Connect 10 USB Type-A USB Devices

The USB Hub features screw-lock USB ports for the upstream and downstream connections to prevent accidental disconnects. Driverless installation and OS-independent speed up any deployment ensuring little downtime and compatibility with many USB peripherals.

The rugged USB Hub supports 480Mbps total bandwidth of USB 2.0 and is backward compatible with USB 1.1 and 1.0 devices.

### Compatibility

The installation options include DIN rail mounting dual-bracket horizontal or single-bracket vertical and wall or desk mounting using the integrated mounting brackets. To finish the installation, the Hub includes a 6ft (1.8m) USB cable with screw-lock to prevent accidental disconnects during operation.

The industrial USB hub is USB 2.0 compliant and supports DC and terminal block power inputs 5 to 24V DC that provide compatibility and flexibility in different scenarios such as product and repair labs, conference rooms, or office workstations.

The 10-port Industrial Hub is backed for 2-years, including free lifetime 24/5 multi-lingual technical assistance.

The StarTech.com Advantage

### Techninė specifikacija

| Ports & interfaces     |                |
|------------------------|----------------|
| Ports quantity         | 10             |
| Host interface         | USB 2.0 Type-B |
| Hub interfaces         | USB 2.0        |
| USB 2.0 ports quantity | 10             |

|                                   |                          |
|-----------------------------------|--------------------------|
| Terminal block port               | Yes                      |
| DC-in jack                        | Yes                      |
| Features                          |                          |
| Data transfer rate                | 480 Mbit/s               |
| Product colour                    | Black                    |
| Plug and Play                     | Yes                      |
| Weight & dimensions               |                          |
| Width                             | 56 mm                    |
| Depth                             | 198 mm                   |
| Height                            | 31 mm                    |
| Weight                            | 340 g                    |
| Packaging data                    |                          |
| Package width                     | 245 mm                   |
| Package depth                     | 168 mm                   |
| Package height                    | 55 mm                    |
| Package weight                    | 600 g                    |
| Packaging content                 |                          |
| Cables included                   | USB Type-A to USB Type-B |
| DIN rail kit included             | Yes                      |
| Quick start guide                 | Yes                      |
| Operational conditions            |                          |
| Operating temperature (T-T)       | 0 - 60 °C                |
| Storage temperature (T-T)         | -20 - 75 °C              |
| Operating relative humidity (H-H) | 5 - 95%                  |
| Logistics data                    |                          |
| Master (outer) case width         | 530 mm                   |
| Master (outer) case length        | 440 mm                   |
| Master (outer) case height        | 340 mm                   |
| Products per master (outer) case  | 25 pc(s)                 |
| Other features                    |                          |
| Chipset                           | Terminus Tech - FE2.1    |
| Matmenys ir svoris                |                          |
| Svoris                            | 0,56kg                   |

## Dokumentai ir vaizdo įrašai

- > [Naudojimo instrukcija](#)
- > [Gaminio lankstinukas](#)

## Gamintojo ir saugos informacija

### GAMINTOJAS

#### StarTech.com Ltd.

Artisans Crescent 45, N5V 5E9 Ontario, London,  
CA  
[startech.com](http://startech.com)

### ATSAKINGAS ASMUO ES

#### StarTech.com Limited

Laarderhoogtweg 25, 1101 EB Amsterdam, NL  
[startech.com](http://startech.com)

### PLATINTOJAS

#### MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius  
[info@shopro.lt](mailto:info@shopro.lt)