StarTech.com 10-Port Industrial USB 2.0 Hub, Rugged USB Hub w/ESD Level 4 Protection, DIN/Wall/Desk-Mountable USB-A HUB, USB Port Expander w/Lockable Ports, Multiport USB Hub

Gamintojas: **STARTECH.COM** · Modelis: **USB210AIND-USB-A-HUB** · EAN: **065030894616** · Prekės kodas: **881221**



75,90 €

Kaina su PVM

Be PVM: **62,73 €**

Sandėlyje

Prekė internetu

Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 10-PORT INDUSTRIAL USB 2.0 Hub: Cold-rolled steel construction ensures durability in harsh environments (32 to 140°F/0 to 60°C at 95% RH); 10 Locking USB-A downstream ports; USB 2.0 Compliant; 480Mbps shared bandwidth; OS independent
- ✓ ESD PROTECTION: Level 4 ESD rugged USB Hub features 15kV air and 8kV contact electrostatic protection for the upstream and downstream ports preventing device dropouts or damage; The Hub supplies up to 5V 0.5A per port suitable for most USB peripherals
- ✓ FLEXIBLE MOUNTING: Multi-port USB Hub features built-in mounting brackets for wall/desk installations; Included DIN rail mounting kit; All the USB ports on the Hub feature screw-lock connectors for preventing accidental disconnection
- ✓ POWER OPTIONS: Ten-port industrial Hub features power redundancy using the DC barrel plug and Terminal Block port (AC adapter not incl); 5 to 24V DC external power is required; Power the Hub via the 2-wire Terminal Block using ITB20D3250 (sold separately)
- ✓ CONNECTIVITY TOOLS: Optimize the performance and security of this TAA-compliant mountable USB Hub, using the included USB Event Monitoring utility (available for download)










Aprašymas

Metal Construction | 6ft (1.8m) USB Host Cable Included

This TAA-compliant 10-port industrial USB 2.0 Hub delivers scalability and protection in harsh industrial environments by providing a high number of USB ports with ESD level 4 protection. The durable metal housing construction is ideal for industrial applications. For power connectivity, the Hub features power redundancy using the DC barrel plug and terminal block port. Finish the installation by mounting the Hub to a DIN rail using the included hardware or on a desk or wall with the built-in mounting brackets.

Rugged Construction

This industrial USB 2.0 Hub delivers reliable performance in the most challenging conditions where operating temperatures range from 32 to 140°F (0 to 60°C) at 95% relative humidity.

The ESD level 4 protection (15kV air and 8kV contact) ensures your equipment is protected from electrostatic damage. An external power source is required, 5 to 24V DC. Optionally, StarTech.com offers part ITB20D3250 to power the Hub via the 2-wire terminal block port.

Connect 10 USB Type-A USB Devices

The USB Hub features screw-lock USB ports for the upstream and downstream connections to prevent accidental disconnects. Driverless installation and OS-independent speed up any deployment ensuring little downtime and compatibility with many USB peripherals.

The rugged USB Hub supports 480Mbps total bandwidth of USB 2.0 and is backward compatible with USB 1.1 and 1.0 devices.

Compatibility

The installation options include DIN rail mounting dual-bracket horizontal or single-bracket vertical and wall or desk mounting using the integrated mounting brackets. To finish the installation, the Hub includes a 6ft (1.8m) USB cable with screw-lock to prevent accidental disconnects during operation.

The industrial USB hub is USB 2.0 compliant and supports DC and terminal block power inputs 5 to 24V DC that provide compatibility and flexibility in different scenarios such as product and repair labs, conference rooms, or office workstations.

The 10-port Industrial Hub is backed for 2-years, including free lifetime 24/5 multi-lingual technical assistance.

The StarTech.com Advantage

Techninė specifikacija

Ports & interfaces	
Ports quantity	10
Host interface	USB 2.0 Type-B
Hub interfaces	USB 2.0
USB 2.0 ports quantity	10

Terminal block port	Yes
DC-in jack	Yes
Features	
Data transfer rate	480 Mbit/s
Product colour	Black
Plug and Play	Yes
Weight & dimensions	
Width	56 mm
Depth	198 mm
Height	31 mm
Weight	340 g
Packaging data	
Package width	245 mm
Package depth	168 mm
Package height	55 mm
Package weight	600 g
Packaging content	
Cables included	USB Type-A to USB Type-B
DIN rail kit included	Yes
Quick start guide	Yes
Operational conditions	
Operating temperature (T-T)	0 - 60 °C
Storage temperature (T-T)	-20 - 75 °C
Operating relative humidity (H-H)	5 - 95%
Logistics data	
Master (outer) case width	530 mm
Master (outer) case length	440 mm
Master (outer) case height	340 mm
Products per master (outer) case	25 pc(s)
Other features	
Chipset	Terminus Tech - FE2.1

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Dokumentai ir vaizdo įrašai

- Naudojimo instrukcija
- Gaminio lankstinukas

Gamintojo ir saugos informacija

GAMINTOJAS

StarTech.com Ltd.
Artisans Crescent 45, N5V 5E9 Ontario, London, CA
startech.com

ATSAKINGAS ASMUO ES

StarTech.com Limited
Laarderhoogtweg 25, 1101 EB Amsterdam, NL
startech.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt