

TSC DA220 label printer Direct thermal 203 x 203 DPI 152.4 mm/sec Wired Ethernet LAN

Gamintojas: **TSC** · Modelis: **99-158A013-1102** · Prekės kodas: **882943**



391,89 €

Kaina su PVM

Be PVM: **323,88 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Small Parcel Shipping
- ✓ Mail Room Address and Routing Labels
- ✓ Shipping & Receiving
- ✓ Entertainment and Transportation Ticketing
- ✓ Retail Point-of-Sale
- ✓ File-Folder Labeling



Aprašymas

The DA210/DA220 Series of direct thermal desktop printers are ideal for a wide variety of applications including product marking, point of sale, retail, small office, shipping labels, and other labeling and tag applications at a very competitive price.

The DA210/DA220 Series is a perfect combination of affordability with a durable and reliable design. The DA200 series offers both 203 and 300 dots per inch print resolution with printing speeds up to a fast 6 inches per second. The large 60 watt power supply produces high quality printed labels, even at its fastest print speeds..

4 Models Available

The DA210/DA220 Series consists of 4 models designed to provide the right fit for your application. All four models handle up to 5" OD rolls of direct thermal labels and can print crisp, clear barcodes, graphics and text at up to 6 inches per second.

Affordable

The low cost DA210 and DA310 models are priced right and have the features you need for most basic label printing needs using a USB 2.0 or optional Bluetooth interface.

Wireless and Hardwire Communications

Need more communications power? The DA220 and DA320 models have more memory and support every communications option you could need including Serial RS-232, Ethernet, USB host, internal 802.11 a/b/g/n wireless, or internal Bluetooth.

Emulations and More

The DA220/DA230 has plenty of memory with 128 MB Flash & 64 MB DRAM that can be used for easy storage of fonts, international character sets and graphics, and it supports, "right out of the box," a fully compatible set of standard industry emulations, including Line Mode, Eltron®, Zebra® and Datamax languages, making it easy to replace old installed hardware.

Easy Loading

For easy loading, the DA210/DA220 Series employs a user-friendly double-wall clamshell design with a large five-inch (outside diameter) center-biased media bay. The spring-loaded label roll holder makes loading simple. Top-of-form sensing – by gap, black mark, or notch – is standard. The printer also comes with a head-open sensor.

The printers are ideal for a wide variety of applications including product marking, point of sale, retail, small office, shipping labels, and other labeling and tag applications at the best price anywhere.

Techninė specifikacija

Printing	
Print technology	Direct thermal
Colour	No
Maximum resolution	203 x 203 DPI
Print speed	152.4 mm/sec
Maximum printing width	10.8 cm
Number of printable dots	8 dot
Printing colours	Black
Rotated printing	Yes
Paper handling	
Maximum label width	11.4 cm
Maximum label length	25.4 m
Maximum roll diameter	3.8 cm
Media thickness	0.055 - 0.19 mm
Supported paper width	108 mm

Maximum media length	2.54 cm
----------------------	---------

Ports & interfaces

Connectivity technology	Wired
-------------------------	-------

Ethernet LAN	Yes
--------------	-----

USB port	Yes
----------	-----

Bluetooth	No
-----------	----

USB 2.0 ports quantity	1
------------------------	---

RS-232 ports	1
--------------	---

Performance

Page description languages	TSPL-EZ
----------------------------	---------

Internal memory	64 MB
-----------------	-------

Flash memory	128 MB
--------------	--------

Built-in barcodes	1D, 2D, CODABAR (NW-7), Code 11, Code 128 (A/B/C), Code 39, Code 93, Data Matrix, EAN128, GS1 DataBar, Interleaved 2/5, MSI, MicroPDF417, PDF417, PLESSEY, POSTNET, QR Code, UPC-A, UPC-E
-------------------	---

Built-in processor	Yes
--------------------	-----

Number of fonts	8
-----------------	---

Certification	FCC Class A, CE Class A, RCM, CB, CCC, ENERGY STAR, KC, BIS, UL, EAC, RoHS, WEEE
---------------	--

Design

Product colour	Black
----------------	-------

Display	No
---------	----

Built-in display	No
------------------	----

Power

Power consumption (printing)	60 W
------------------------------	------

AC input voltage	100 - 240 V
------------------	-------------

AC input frequency	50 - 60 Hz
--------------------	------------

AC adapter output voltage	24 V
---------------------------	------

AC adapter output current	2.5 A
---------------------------	-------

Power source type	AC
-------------------	----

Operational conditions

Operating relative humidity (H-H)	25 - 85%
-----------------------------------	----------

Storage relative humidity (H-H)	10 - 90%
---------------------------------	----------

Operating temperature (T-T)	5 - 40 °C
-----------------------------	-----------

Storage temperature (T-T)	-40 - 60 °C
---------------------------	-------------

Weight & dimensions

Width	172 mm
Depth	195 mm
Height	165 mm
Weight	1.5 kg

Packaging data

Package type	Box
--------------	-----

Packaging content

Cables included	AC
Bundled software	Windows labeling

Technical details

Sustainability certificates	ENERGY STAR
Compliance certificates	BIS, CB, CE, China Compulsory Certification (CCC), EAC, Federal Communications Commission (FCC), KC, RCM, RoHS, UL, WEEE

Matmenys ir svoris

Svoris	2,67kg
--------	--------

Dokumentai ir vaizdo įrašai

- > [Naudojimo instrukcija](#)
- > [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

TSC

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt