

Axagon RVC-HI2MC vaizdo kabelio adapteris 1,8 m C tipo USB HDMI Juoda

Gamintojas: **AXAGON** · Modelis: **RVC-HI2MC** · EAN: **8595247907158** · Prekės kodas: **883814**



21,90 €

Kaina su PVM

Be PVM: **18,10 €**

Sandėlyje







Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 1,8 m
- ✓ C tipo USB Tiesus Kištukinis
- ✓ HDMI Tiesus Kištukinis
- ✓ 4096 x 2160 pikseliai 240 Hz
- ✓ Palaikoma HDR „USB Type C DisplayPort Alternate Mode“
- ✓ Juoda
- ✓ 1 vnt





Aprašymas

Modern USB-C > HDMI active cable - adapter AXAGON RVC-HI2MC for connecting a HDMI monitor/TV/projector to a notebook or phone using USB-C connector.

A hardware converter ensures quality image up to 4K/60Hz Ultra HD resolution without any installation. Popular gaming resolution WQHD 2560 x 1440 at 60, 120 and 144 Hz or FullHD 1920 x 1080 at 60, 120, 144 and 240 Hz are also supported. Thanks to HDR (high dynamic range) support, you can enjoy a significantly expanded range of colors and contrasts without restrictions.

Durable cable is equipped with solid metal ends, connectors with a nickel-plated surface and gold-plated contacts. The final strength of the cable is provided by the nylon braid. The bonus is a practical strip for easy packing of the cable. Video and audio transfer from a computer, laptop, phone or Apple MacBook will now be easy.

Compact dimensions provide the possibility to use the cable in insufficient space. The converter dimensions are almost identical to the standard cable connectors. You have an ideal solution - you don't need a cable and converter, with this active cable everything is integrated into one compact unit.

The cable is only oneway, i.e. USB-C to HDMI, not otherwise. A USB-C port with DisplayPort Alternate Mode (DP Alt Mode) support of a device with Thunderbolt 3/4 port is required for the adapter to function properly.

Input:

- USB-C
- USB type C (M) male connector

Output:

- HDMI 2.1a 4K/60Hz HDR10 (before HDMI 2.0a)
- HDMI (M) male connector

Supported resolutions:

- max. 4096 x 2160 (19:10) @60Hz DCI 4K
- 3840 x 2160 (16:9) @60Hz UHD-1 4K (UHDTV)
- 3840 x 1600 (21:9) UW 4K (Ultrawide 1600p)
- 3840 x 1200 (32:10) 29:9 4K (Super ultrawide 1200p)
- 3840 x 1080 (32:9) 32:9 4K (Super ultrawide 1080p)
- 3440 x 1440 (21:9) UWQHD (Ultrawide 1440p)
- 2560 x 2048 (5:4) QSXGA
- 2560 x 1920 (4:3)
- 2560 x 1600 (16:10) WQXGA
- 2560 x 1440 (16:9) @60, 120 a 144Hz QHD
- 2560 x 1080 (21:9) UWFHD (Ultrawide 1080p)
- 2048 x 1536 (4:3) QXGA
- 2048 x 1152 (16:9) QWXGA
- 1920 x 1440 (4:3)
- 1920 x 1200 (16:10) WUXGA

- 1920 x 1080 (16:9) @60, 100, 120, 144 a 240Hz Full HD/1080p
- 1856 x 1392 (4:3)
- 1792 x 1344 (4:3)
- 1680 x 1050 (16:10) WSXGA+
- 1600 x 1200 (4:3) UXGA
- 1600 x 900 (16:9) HD+
- 1536 x 864 (16:9)
- 1440 x 900 (16:10) WXGA+
- 1400 x 1050 (4:3) SXGA+
- 1366 x 768 (16:9) HD
- 1360 x 768 (16:9) HD
- 1280 x 1024 (5:4) SXGA
- 1280 x 960 (4:3) SXGA-
- 1280 x 800 (16:10) WXGA
- 1280 x 768 (5:3) WXGA
- 1280 x 720 (16:9) HD/WXGA/720p
- 1280 x 600
- 1152 x 864 (4:3) XGA+
- 1024 x 768 (4:3) XGA
- 800 x 600 (4:3) SVGA

* the adjustable resolution and frequencies depend on monitor/TV/projector and graphics adapter parameters.

Other features:

- Supported modes: mirroring the desktop (default setting), extension of the primary monitor area.
- HPD (Hot-Plug-Detect) support - communication sequence controlling the connection/disconnection of the device while running,
- Support up to 8-channel sound - 96 kHz at 24 bits,
- HDR (High dynamic range, 10 bit support) support - realistic reproduction of light and dark details.
- Compliant with USB Type-C Cable and Connector Specification Revision 1.1 specification,
- Compliant with VESA DisplayPort Alt Mode on USB Type-C Standard Version 1.0 specification,
- Compliant with USB Device Class Definition for Billboard Devices Revision 1.0 specification.
- Compliant with HDMI Specification 2.1a 4K/60Hz HDR10 specification (before HDMI 2.0a).
- TMDS (Transition Minimized Differential Signaling) support - transfer of auxiliary image, sound and additional data.
- HDCP 2.2 (High-bandwidth Digital Content Protection) support - a mechanism used to protect the digital contents.
- Support of power saving modes with spinning down controlled by a source device (PC) and a viewing device (monitor/TV).
- Power supply via USB-C – no external power is needed.
- Dimensions of converter body 48 x 21 x 10 mm,
- Total cable length incl. connector 180 cm,
- Weight 70 g,
- Operating temperature 0 ~ 45°C.
- Storage temperature: -10 ~ 70°C.

Supported OS:

- Microsoft Windows, macOS, Android and Chrome OS – updated.
- Compatibility depends on the operating system and device manufacturer support.
- Graphics card drivers may also affect RVC-HI2MC functionality. We recommend downloading the latest version of the drivers.

Package contains:

- USB-C > HDMI cable length 1.8m,
- multilingual manual CZ / DE / DK / ENG / ESP / FIN / FR / GR / HR / HU / IT / NL / PL / PT / RO / RU / SK / SWE / BG / CN / TR / ARA,
- packed in a cardboard box with a hanging hole.

Techninė specifikacija

Savybės	
Kabelio ilgis	1,8 m
Jungtis 1	C tipo USB
Jungtis 2	HDMI
1 jungtis – vidinė ar išorinė	Kištukinis
2 jungtis – vidinė ar išorinė	Kištukinis
1 jungties forma	Tiesus
2 jungties forma	Tiesus
HDMI versija	2.1a
„USB Type C DisplayPort Alternate Mode“	Taip
Palaikoma HDR	Taip
Maksimali rezoliucija	4096 x 2160 pikseliai
Palaikomos grafikos rezoliucijos	1280 x 800, 2048 x 1152, 1280 x 768, 1360 x 768 (WXGA), 3840 x 1200, 3840 x 2160, 1366 x 768, 800 x 600 (SVGA), 1400 x 1050 (SXGA+), 2560 x 1440, 2560 x 1600 (WQXGA), 1440 x 900 (WXGA+), 2560 x 2048, 2560 x 1080, 2560 x 1920, 4096 x 2160, 1440 x 900, 1600 x 900, 1600 x 1200 (UXGA), 1024 x 768 (XGA), 1920 x 1080 (HD 1080), 1920 x 1200 (WUXGA), 1152 x 864 (XGA+), 1280 x 720 (HD 720), 1280 x 768 (WXGA), 1280 x 800 (WXGA), 1280 x 960, 2048 x 1536 (QXGA), 1280 x 1024 (SXGA)
Palaikomi vaizdo režimai	600p, 1600p, 1080p, 720p, 1280p, 800p, 1440p, 900p, 2160p, 960p, 1024p
Maksimalus atnaujinimo dažnis	240 Hz
Atnaujinimo dažnis, esant maksimaliai rezoliucijai	60 Hz
Produkto spalva	Juoda
Kabelio tipas	Apvalusis kabelis
„Plug and Play“ funkcija	Taip
Kilmės šalis	Kinija
Palaikomos „Windows“ operacinės sistemos	Taip
Palaikomos MAC operacinės sistemos	Taip
Didelio dinaminio diapazono (HDR) technologija	High Dynamic Range 10 (HDR10)
Kitos palaikomos operacinės sistemos	Android, ChromeOS
Sertifikatai	
Atitikties sertifikatai	RoHS, CE
Sertifikavimas	CE, RoHS
Svoris ir matmenys	
Svoris	70 g
Plotis	48 mm

Ilgis	21 mm
Aukštis	10 mm
Pakuotės duomenys	
Pakuotės plotis	170 mm
Pakuotės gylis	90 mm
Pakuotės aukštis	30 mm
Paketo svoris	103 g
Pakuotės tipas	„Box“
Pakuotės turinys	
Kiekis pakuotėje	1 vnt
Instrukcija	Taip
Logistikos duomenys	
Garantinis laikotarpis	3 metai
Matmenys ir svoris	
Matmenys (I × P × A)	3,00cm × 9,00cm × 17,00cm
Svoris	0,11kg

Dokumentai ir vaizdo įrašai

› [Naudojimo instrukcija](#)

Gamintojo ir saugos informacija

GAMINTOJAS

RealQ, s.r.o.

Železná 663/5, 619 00 Brno-jih, CZ

axagon.eu

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt