

StarTech.com ICUSB2324852 sąsajos plokštė / adapteris

Nuoseklusis

Gamintojas: **STARTECH** · Modelis: **ICUSB2324852** · EAN: **065030840965** · Prekės kodas: **890198**



124,90 €

Kaina su PVM

Be PVM: **103,22 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Priimančioji sąsaja: B tipo USB
- ✓ Išvesties sąsaja: Nuoseklusis
- ✓ Pilka



Aprašymas

Add RS232, RS422 and RS485 support to your laptop or desktop computer via USB

The ICUSB2324852 2 Port USB to RS232 RS422 RS485 Serial Adapter with COM Retention lets you connect every type of serial device to your USB-enabled computer, whether it be for RS232, RS422, or RS485 communication. The adapter features a 9-pin (DB9) male and a 5-pin terminal block serial connector as well as dip-switch controls for easy port configuration with minimal software requirements. The adapter also supports using 2 ports simultaneously, including with mixed protocols; for example RS-232 on port 1, and RS-485 on port 2, or a number of other combinations. For a convenient, and clean installation in office or industrial settings, the RS232/RS422/RS485 USB Adapter is wall-mountable and fully powered via the host USB connection, providing power to the attached serial device without requiring an external power adapter. Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Techninė specifikacija

Ports & interfaces

Host interface	USB Type-B
Output interface	Serial
Serial ports quantity	1
Serial interface type	RS-232/422/485

Design

Internal	No
Product colour	Grey
LED indicators	Power

Features

Chipset	FTDI - FT2232H
Baud rate	921.6 Kbit/s
FIFO (First In, First Out)	128 B
Data bits	7, 8
Stop bits	1, 2
Parity bit	Even, Mark, No, Odd, Space
Flow Control type	No, XON/XOFF

Power

Output voltage	5 V
----------------	-----

Operational conditions

Operating temperature (T-T)	0 - 55 °C
Storage temperature (T-T)	-25 - 85 °C
Operating relative humidity (H-H)	5 - 95%

System requirements

Windows operating systems supported	Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 IoT Enterprise, Windows 10 Pro, Windows 10 Pro x64, Windows 10 x64, Windows 11, Windows 11 x64, Windows 2000, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64, Windows 98SE, Windows CE, Windows Vista, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows Vista x64, Windows XP, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64
Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 13.0 Ventura
Linux operating systems supported	Yes
Server operating systems supported	Windows Server 2003, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019
Other operating systems supported	Windows XP Embedded
Technical details	
Compliance certificates	CE, RoHS
Sustainability compliance	Yes
Weight & dimensions	
Width	44.2 mm
Depth	82.3 mm
Height	23 mm
Weight	300 g
Packaging data	
Quantity per pack	1 pc(s)
Cables included	USB Type-A to USB Type-B
Mounting brackets included	Yes
Drivers included	Yes
Manual	Yes
Package width	145 mm
Package depth	209 mm
Package height	45 mm

Package weight 310 g

Logistics data

Harmonized System (HS) code 84733020

Products per master (outer) case 40 pc(s)

Master (outer) case width 406 mm

Master (outer) case length 500 mm

Master (outer) case height 330 mm

Other features

Compatible operating systems Windows 98SE/ ME/ 2000/ XP(32/64bit)/ 2003(32/64bit)/ Vista(32/64bit)/ Server 2008(32/64bit)/ 7(32/64bit)/ Server 2008 R2, Mac 9.8/OS X, Linux 2.4.x; Windows XP Embedded, CE 4.2/ 5.2/ 6.0, PocketPC 2003, Mobile 5, 6

Matmenys ir svoris

Matmenys (I × P × A) 22,00cm × 15,00cm × 5,00cm

Svoris 0,27kg

Dokumentai ir vaizdo įrašai

> [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

StarTech.com Ltd.

Artisans Crescent 45, N5V 5E9 Ontario, London, CA

startech.com

ATSAKINGAS ASMUO ES

StarTech.com Limited

Laarderhoogtweg 25, 1101 EB Amsterdam, NL

startech.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt