

D-Link 2-Port Gigabit PoE Extender

Gamintojas: **D-LINK** · Modelis: **DPE-302GE** · EAN: **790069435461** · Prekės kodas: **890844**



135,90 €

Kaina su PVM

Be PVM: **112,31 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Simplicity
- ✓ Plug-and-play with no software required
- ✓ Multiple mounting options for flexible placement
- ✓ Provides power over existing network cabling to remote PoE-capable devices
- ✓ Lightweight and compact
- ✓ One PoE input port to dual output ports
- ✓ Three arrow LEDs to indicate the direction of the power and data flow Gigabit Connectivity
- ✓ Deliver PoE (+) power over 10/100/1000 Mbps connections up to a 500 m
- ✓ Connect and power Gigabit devices
- ✓ Auto-negotiation on Ethernet ports



Aprašymas

The DPE-302GE 2-Port Gigabit PoE Extender allows a Gigabit Power-over-Ethernet connection to be extended up to 500 m1. It is designed to supply data and PoE power to devices such as PTZ IP cameras or 802.11ac wireless access points over extended distances. With several mounting options, the DPE-302GE allows PoE devices to be deployed virtually anywhere over longer distances, eliminating the need for a nearby power outlet and attached power supply.

Powers More Devices Over Longer Distances

The DPE-302GE offers a plug-and-play PoE solution, capable of transmitting up to 10 to 28 W of output power. It allows connection of up to two devices over a maximum distance of 500 m by daisy-chaining up to 4 units. With support for PoE/PoE+ and Gigabit speeds, the DPE-302GE is designed to be deployed in situations with high bandwidth requirements, over long distances.

Flexible Deployment

The DPE-302GE is powered by consuming only a very small fraction of PoE power. Combined with three flexible methods of mounting (built-in magnet, screw anchors, and Velcro), the DPE-302GE can be deployed virtually anywhere. This PoE solution frees network devices from the restrictions of power availability by removing the need for a local power source. The DPE-302GE has built-in 4 kV surge protection and is also capable of operating in temperatures of up to 60 °C (140 °F), allowing it to be deployed in harsher environments.

Reliable Connectivity

The DPE-302GE 2-Port Gigabit PoE Extender intelligently communicates the maximum available current with a Powered Device (PD). This protection feature keeps the device safe from damage by preventing it from powering on in case there is not enough current. This safety feature can also automatically disable the port in the event of an electrical short circuit.

Techninė specifikacija

Network	
Ethernet interface type	Gigabit Ethernet
Ethernet LAN data rates	10,100,1000 Mbit/s
Power over Ethernet (PoE)	Yes
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x
Duplex system	Full, Half
Features	
LED indicators	PoE
Ports & interfaces	
Ethernet LAN (RJ-45) ports	3
DC-in jack	Yes
Power	
Power consumption (max)	3.05 W
Certificates	
Certification	CE FCC LVD/CE IC

Operational conditions

Operating temperature (T-T)	-10 - 60 °C
Operating temperature (T-T)	-40 - 85 °F
Operating relative humidity (H-H)	10 - 95%
Storage temperature (T-T)	5 - 95 °C

Weight & dimensions

Weight	154 g
Dimensions (WxDxH)	155 x 60 x 40 mm

Packaging data

Package width	109 mm
Package depth	217 mm
Package height	59 mm
Package weight	292 g

Logistics data

Shipping (inner) case length	45.4 cm
Shipping (inner) case width	31.2 cm
Shipping (inner) case height	24.5 cm
Shipping (inner) case net weight	6 kg
Products per shipping (inner) case	20 pc(s)
Pallet gross weight (air)	301.4 kg
Master (outer) cases per pallet (air)	42 pc(s)
Products per pallet (air)	840 pc(s)
Pallet gross length	110 cm
Pallet gross width	120 cm
Pallet height (air)	185 cm
Pallet gross weight (sea)	301.4 kg
Master (outer) cases per pallet (sea)	42 pc(s)
Products per pallet (sea)	840 pc(s)
Pallet height (sea)	185 cm
Shipping (inner) case gross weight	6.67 kg
Harmonized System (HS) code	85044095

Dokumentai ir vaizdo įrašai

- › Greitos pradžios vadovas
- › Gaminio lankstinukas
- › Saugos informacija
- › Atitikties deklaracija

Gamintojo ir saugos informacija

GAMINTOJAS

D-Link

ATSAKINGAS ASMUO ES

D-Link Benelux

Postbus 48, 5480 AA Schijndel, NL
dlink.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Saugos dokumentai

- › Atitikties deklaracija
- › Saugos informacija