# InLine 33380J interface cards/adapter RJ-45

Gamintojas: **INLINE** · Modelis: **33380J** · EAN: **4043718341030** · Prekės kodas: **891573**




**53,91 €**

Kaina su PVM

Be PVM: **44,55 €**

**Sandėlyje**

**Prekė internetu**
Nuskenuokite kodą arba apsilankykite www.shopro.lt

## Pagrindinės savybės

- ✓ Host interface: USB Type-C
- ✓ Output interface: RJ-45
- ✓ Grey








## Aprašymas

**Versatile network access via USB-C:** The adapter reliably connects USB-C-enabled devices to an Ethernet network – ideal for IT environments without Wi-Fi.
**Simultaneous power supply of up to 10 W:** Supports USB-C Power Delivery for simultaneous power supply to compatible devices – efficient and space-saving.
**Robust aluminium housing for industrial use:** The high-quality metal housing provides reliable protection against mechanical impacts – even in harsh environments.
**Protection via integrated electronics:** Overvoltage and overcurrent protection ensure stable operation and maximum device safety.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

**Quick setup without drivers:**Thanks to Plug & Play, the adapter is ready for use immediately – no software installation required.

The InLine® USB-C to RJ45 PoE adapter is a professional solution for connecting USB-C devices to wired networks. Specifically designed for industry, IT infrastructures and demanding applications, the adapter offers a reliable connection via an RJ45 interface and supports the IEEE802.3af PoE standard with speeds of up to 100 Mb/s. At the same time, it delivers a charging power of up to 10 W via USB-C Power Delivery – an ideal combination for devices that require both network access and power.
With this adapter, you can, for example, connect a tablet to a network via a patch cable. If the device is connected to a PoE-enabled switch, power is supplied directly via the network. A separate power supply is not required.
Please note: Power is supplied exclusively from the network to the USB-C device. Power cannot be fed back from the USB-C port to the network.
The integrated protection concept, comprising overvoltage and overcurrent protection, ensures maximum operational reliability, even in critical environments. The robust aluminium housing protects the sensitive electronics from external influences and ensures a long service life in industrial applications. Thanks to its simple commissioning without drivers, the adapter is particularly flexible and quick to integrate – whether in mobile service applications, in server racks or for the temporary expansion of existing networks.
With its combination of performance, security and reliability, the InLine® USB-C to RJ45 PoE adapter is an indispensable tool for system integrators, technicians and IT administrators who rely on professional solutions.

Chipset: RTL8152
Connector A: RJ45
Connector B: USB-C (0.7 m cable)
LED indicator: Yes
PoE standard: IEEE802.3af
Data rate: 100 Mb/s
USB-C PD output: 5 V / 2 A (max. 10 W)
Operating temperature: 0 °C to +70 °C
Storage temperature: -40 °C to +125 °C
Dimensions: 79 x 30 x 21 mm
Weight: 58 g

## Techninė specifikacija

| | |
|---|---|
| **Ports & interfaces** | |
| Host interface | USB Type-C |
| Output interface | RJ-45 |
| Host interface gender | Male |
| **Design** | |
| Internal | No |
| Product colour | Grey |
| LED indicators | Yes |
| Country of origin | Taiwan |
| **Features** | |
| Chipset | RTL8152 |
| Plug and Play | Yes |
| **Power** | |
| Output current | 2 A |

| | |
|---|---|
| **Operational conditions** | |
| Operating temperature (T-T) | 0 - 70 °C |
| **Technical details** | |
| Compliance certificates | TÜV mark |
| **Weight & dimensions** | |
| Width | 30 mm |
| Depth | 79 mm |
| Height | 21 mm |
| Weight | 58 g |
| **Packaging data** | |
| Package width | 130 mm |
| Package depth | 175 mm |
| Package height | 25 mm |
| Package weight | 98 g |
| Package volume | 500 cm³ |
| **Other features** | |
| Dimensions (WxDxH) | 30 x 80 x 20 mm |
| Ethernet LAN (RJ-45) ports | 1 |
| Networking standards | IEEE 802.3af |

## Gamintojo ir saugos informacija

GAMINTOJAS

**InLine**

PLATINTOJAS

**MB KOMPIUTERIŲ GURU**
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt