

iiyama ProLite TF2234MC-B7AGB kompiuterio monitorius 54,6 cm (21.5") 1920 x 1080 pikseliai „Full HD“ LED Lietimui jautrus ekranas Daugybė naudotojų Juoda

Gamintojas: **IIYAMA** · Modelis: **TF2234MC-B7AGB** · EAN: **4948570118373** · Prekės kodas: **893832**



535,90 €

Kaina su PVM

Be PVM: **442,89 €**

Sandėlyje




Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 54,6 cm (21.5") Juoda
- ✓ HDMI „DisplayPort“ kiekis: 1
- ✓ Ekrano forma: Plokščias
- ✓ Reakcijos laikas: 8 ms Atsako trukmės matavimo tipas: GTG (Gray to Gray)
- ✓ 1920 x 1080 pikseliai „Full HD“ Skydo tipas: IPS
- ✓ Energijos vartojimo efektyvumo klasė (SDR): F ErP CE, cULus, EAC, REACH, RoHS, WEEE





Aprašymas

The ProLite TF2234MC-B7AGB uses PCAP Touch technology, and it is built into an eye-catching bezel with edge-to-edge glass. Featuring IPS LCD Screen technology, it offers exceptional colour performance and wide viewing angles. The higher brightness ensures crispy and clear images, even in a bright environment. In addition to the superb image quality, the screen is suitable for demanding environments. It comes with a rugged bezel and IP65 rating, meaning the monitor is dust and water resistant from the front. The Anti Glare Glass helps to avoid issues with reflections and external light sources affecting contrast and sharpness. The ProLite TF2234MC-B7AGB is the ideal screen for kiosk integrators and a superb display for use as Interactive Digital Signage, Instore Retail and Interactive Presentation display. For ease of integration, this monitor can be equipped with optional external mounting brackets (OMK1-1).

Techninė specifikacija

Display	
Display diagonal	54.6 cm (21.5")
Display resolution	1920 x 1080 pixels
Native aspect ratio	16:9
Display technology	LED
Touchscreen	Yes
HD type	Full HD
Panel type	IPS
Response time	8 ms
Screen shape	Flat
Contrast ratio (typical)	1000:1
Display number of colours	16.7 million colours
Touchscreen type	Multi-user
Touchscreen technology	Projected capacitive system
Touch technology	Multi-touch
Number of simultaneous touchpoints	10
Display brightness (typical)	350 cd/m²
Display brightness	300 cd/m²
Response time measurement type	GTG (Gray to Gray)
Anti-glare screen	Yes
Viewing angle, horizontal	178°
Viewing angle, vertical	178°

Pixel pitch	0.247 x 0.247 mm
Horizontal scan range	30 - 84 kHz
Viewable size, horizontal	47.6 cm
Viewable size, vertical	26.8 cm
Display diagonal (metric)	54.6 cm
Surface hardness	6H
Performance	
NVIDIA G-SYNC	No
AMD FreeSync	No
Palm rejection	Yes
Multimedia	
Built-in camera	No
Built-in microphone	No
Design	
Product colour	Black
Front bezel colour	Black
Glass thickness	1.5 mm
Ports & interfaces	
HDMI	Yes
USB Touch port	Yes
VGA (D-Sub) ports quantity	1
HDMI ports quantity	1
DisplayPorts quantity	1
HDCP	Yes
Ergonomics	
VESA mounting	Yes
Panel mounting interface	100 x 100 mm
Wall mountable	Yes
On Screen Display (OSD)	Yes
On Screen Display (OSD) languages	German, English, Spanish, French, Italian, Japanese, Dutch, Polish, Russian
Number of OSD languages	9
Power	
Energy efficiency class (SDR)	F
Energy consumption (SDR) per 1000 hours	19 kWh

Power consumption (typical)	18 W
Power consumption (standby)	1.5 W
Power consumption (off)	0.3 W
AC adapter output voltage	12 V
Power supply type	External
Energy efficiency scale	A to G
Weight & dimensions	
Width (with stand)	517.5 mm
Depth (with stand)	46 mm
Height (with stand)	313.5 mm
Weight (with stand)	4.4 kg
Width (without stand)	517.5 mm
Depth (without stand)	46 mm
Height (without stand)	313.5 mm
Weight (without stand)	4.4 kg
Packaging data	
Package width	610 mm
Package depth	160 mm
Package height	405 mm
Package weight	6.8 kg
Packaging content	
Cables included	AC, USB, HDMI, DisplayPort
Quick start guide	Yes
Sustainability	
Sustainability certificates	ErP
Other features	
International Protection (IP) code	IP65
Compatible operating systems	All iiyama monitors are Plug & Play and compatible with Windows and Linux. For details regarding the supported OS for the touch models, please refer to the driver instruction file available in the downloads section.
AC adapter included	Yes
Display viewable area (HxV)	476 x 267.7 mm
Placement supported	Horizontal/Vertical
Brightness	300 cd/m ²
Packaging content	AC adapter

Active display area (W x H)	476 x 267.7 mm
Weight	4.4 kg
Height	313.5 mm
Width	517.5 mm
Depth	46 mm
Compliance certificates	CE, cULus, EAC, REACH, RoHS, WEEE
User controls	picture (contrast, brightness, H.position, V.position, phase, clock, auto adjust), advanced (color temp., sharpness), OSD (time out, position, H-position, V-position, Touch switch), option (reset, language, source select, display mode, factory)
Touch method	stylus, finger, glove (latex)
Control panel	Menu, Scroll up/ Brightness, Scroll down/ Contrast, Select, Power


Logistics data

Products per pallet	48 pc(s)
Pallet net width	109 cm
Pallet net length	192.7 cm
Pallet net height	109 cm
Harmonized System (HS) code	85285210

Matmenys ir svoris

Matmenys (I × P × A)	61,00cm × 41,00cm × 16,00cm
Svoris	6,12kg


Energijos efektyvumas ir ekologinis projektavimas



Energijos efektyvumo klasė

F A-G

- › [Energijos etiketė](#)
- › [Gaminio informacijos lapas](#)
- › [EPREL duomenų bazė](#)



Dokumentai ir vaizdo įrašai

- > Naudojimo instrukcija
- > Gaminio lankstinukas
- > Vaizdo įrašas youtube.com/watch?v=AuPCFL8oUyU

Gamintojo ir saugos informacija

GAMINTOJAS

iiyama International

Wijkmeerstraat 8, 2131 HA Hoofddorp, NL

[iiyama.com](https://www.iiyama.com)

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt