

iiyama ProLite TF3215MC-B2 kompiuterio monitorius 80 cm (31.5") 1920 x 1080 pikseliai „Full HD“ LED Lietimui jautrus ekranas Terminalas Juoda

Gamintojas: **IIYAMA** · Modelis: **TF3215MC-B2** · EAN: **4948570123667** · Prekės kodas: **894724**



905,90 €

Kaina su PVM

Be PVM: **748,68 €**

Sandėlyje





Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 80 cm (31.5") Juoda
- ✓ HDMI „DisplayPort“ kiekis: 1
- ✓ Ekrano forma: Plokščias
- ✓ Reakcijos laikas: 8 ms Atsako trukmės matavimo tipas: GTG (Gray to Gray)
- ✓ 1920 x 1080 pikseliai „Full HD“ Skydo tipas: VA
- ✓ Energijos vartojimo efektyvumo klasė (SDR): F ErP CE, EAC, REACH, RoHS, UKCA, WEEE





Aprašymas

The ProLite TF3215MC-B2 with 30-point PCAP touch technology is a open frame monitor with an eye-catching edge-to-edge glass design. Thanks to this completely frame-less glass surface, it guarantees high durability and scratch resistance, making it perfect for kiosk systems and high-traffic public applications. The VA panel technology offers higher contrast and darker blacks. Equipped with a foam seal, the monitor supports seamless integration and the IP65 rating ensures dust and water resistance from the front. Portrait and landscape orientation ensures flexible mounting options for 24/7 operation in almost any installation. The TF3215MC-B2 is the ideal solution for kiosk integrators, industrial environments, control rooms and interactive multi-media applications.

Techninė specifikacija


Display	
Display diagonal	80 cm (31.5")
Display resolution	1920 x 1080 pixels
Native aspect ratio	16:9
Display technology	LED
Touchscreen	Yes
HD type	Full HD
Panel type	VA
Response time	8 ms
Screen shape	Flat
Contrast ratio (typical)	3000:1
Display number of colours	16.7 million colours
Touchscreen type	Kiosk
Touchscreen technology	Projected capacitive system
Touch technology	Multi-touch
Number of simultaneous touchpoints	30
Display brightness (peak)	500 cd/m²
Display brightness (typical)	500 cd/m²
Display brightness	460 cd/m²
Response time measurement type	GTG (Gray to Gray)
Contrast ratio (dynamic)	3000:1
Viewing angle, horizontal	178°

Viewing angle, vertical	178°
Pixel pitch	0.3637 x 0.3637 mm
Horizontal scan range	30 - 68 kHz
Vertical scan range	47 - 63 Hz
Viewable size, horizontal	69.8 cm
Viewable size, vertical	39.3 cm
Display diagonal (metric)	80 cm
Surface hardness	7H
Colour depth	8 bit
Performance	
NVIDIA G-SYNC	No
AMD FreeSync	No
Operating hours (hours/days)	24/7
Multimedia	
Built-in speaker(s)	No
Built-in camera	No
Design	
Market positioning	Office
Product colour	Black
Housing material	Metal
Front bezel colour	Black
Glass thickness	3 mm
Ports & interfaces	
HDMI	Yes
USB Touch port	Yes
VGA (D-Sub) ports quantity	1
HDMI ports quantity	1
DisplayPorts quantity	1
HDCP	Yes
Ergonomics	
VESA mounting	Yes
Cable lock slot	No
Panel mounting interface	200 x 200 mm
Wall mountable	Yes

Cable management	Yes
On Screen Display (OSD)	Yes
On Screen Display (OSD) languages	Traditional Chinese, German, English, Spanish, French, Italian, Japanese
Number of OSD languages	7
Plug and Play	Yes
Power	
Energy efficiency class (SDR)	F
Energy efficiency class (HDR)	Not available
Energy consumption (SDR) per 1000 hours	27.5 kWh
Power consumption (typical)	32 W
Power consumption (standby)	1.5 W
Power consumption (off)	0.3 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power supply type	Internal
Energy efficiency scale	A to G
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Weight & dimensions	
Width (with stand)	743 mm
Depth (with stand)	61 mm
Height (with stand)	437 mm
Weight (with stand)	10 kg
Width (without stand)	742.5 mm
Depth (without stand)	61 mm
Height (without stand)	437 mm
Weight (without stand)	10 kg
Packaging data	
Package width	890 mm
Package depth	155 mm
Package height	630 mm
Package weight	13.3 kg
Packaging content	

Cables included	AC, USB, HDMI
Quick start guide	Yes
Sustainability	
Sustainability certificates	ErP
Other features	
International Protection (IP) code	IP65
Compatible operating systems	All iiyama monitors are Plug & Play and compatible with Windows and Linux. For details regarding the supported OS for the touch models, please refer to the driver instruction file available in the downloads section.
Positional accuracy	2 mm
Brightness	460 cd/m²
Active display area (W x H)	698.4 x 392.8 mm
Weight	10 kg
Height	437 mm
Width	743 mm
Depth	61 mm
Compliance certificates	CE, EAC, REACH, RoHS, UKCA, WEEE
Mean time between failures (MTBF)	50000 h
User controls	Picture (contrast, brightness, H.position, V.position, phase, clock, auto adjust), advanced (color temp., sharpness), OSD (timeout, poition, H-Position, V-Position, touch switch), option (reset, language, source select, display mode, factory)
Touch method	finger, glove (latex), capacitive stylus
Control panel	Menu, Scroll up/ Brightness, Scroll down/ Mute, Select, Power
Supplied AC adapter type	AC
Matmenys ir svoris	
Matmenys (I × P × A)	89,00cm × 63,00cm × 16,00cm
Svoris	13,00kg

Energijos efektyvumas ir ekologinis projektavimas



Energijos efektyvumo klasė

F A-G

- › [Energijos etiketė](#)
- › [Gaminio informacijos lapas](#)
- › [EPREL duomenų bazė](#)



2019/09/23

Dokumentai ir vaizdo įrašai

- › [Naudojimo instrukcija](#)
- › [Gaminio lankstinukas](#)
- › [Vaizdo įrašas](#) [youtube.com/watch?v=wI5bmhGWbo4](https://www.youtube.com/watch?v=wI5bmhGWbo4)

Gamintojo ir saugos informacija

GAMINTOJAS

iiyama International

Wijkmeesterstraat 8, 2131 HA Hoofddorp, NL

[iiyama.com](https://www.iiyama.com)

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt