

HP LaserJet Enterprise 700 Printer M712dn

Gamintojas: **HP INC** · Modelis: **CF236A#B19** · EAN: **886112999674** · Prekės kodas: **895114**



2 283,90 €

Kaina su PVM

Be PVM: **1 887,52 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Verslui Lazeris
- ✓ 1200 x 1200 DPI
- ✓ Spausdinimo spalvos: Juoda
- ✓ A3 41 ppm
- ✓ Abipusis spausdinimas Tiesioginis spausdinimas
- ✓ USB prievadas Ethernet LAN jungtis
- ✓ LCD įmontuotas ekranas
- ✓ Veikos ciklas (maksimalus): 100000 lapai per mėnesį
- ✓ Bendras įvesties dėklų skaičius: 3 Bendra įvesties talpa: 600 lapai
Bendra išvesties talpa: 250 lapai
- ✓ Vidinė atmintis: 512 MB Integruotas procesorius 800 MHz



Aprašymas

Print two-sided, black-and-white documents at high speeds on paper sizes up to A3, save money with energy-saving features, and keep data secure. Enable high-volume, black-and-white printing on paper sizes up to A3, with capacity up to 4,600 sheets[1]. Control costs with

energy-saving features and two-sided printing. Protect sensitive business data and centrally manage printing policies.

Techninė specifikacija

Printing	
Colour	No
Print technology	Laser
Duplex printing	Yes
Maximum resolution	1200 x 1200 DPI
Print speed (black, normal quality, A4/US Letter)	41 ppm
Duplex printing mode	Auto
Print resolution black	1200 x 1200 DPI
Print speed (black, normal quality, A3)	20 ppm
Time to first page (black, normal)	10.5 s
Secure printing	Yes
Features	
Maximum duty cycle	100000 pages per month
Printing colours	Black
Number of print cartridges	1
Page description languages	PDF 1.4, PCL 5, PCL 6
Recommended duty cycle	5000 - 20000 pages per month
Country of origin	China
HP segment	Business
Input & output capacity	
Total number of input trays	3
Total input capacity	600 sheets
Total output capacity	250 sheets
Paper tray 1 input capacity	100 sheets
Paper tray 2 input capacity	250 sheets
Multi-Purpose tray	Yes
Multi-Purpose tray input capacity	100 sheets
Maximum number of input trays	6
Maximum input capacity	4600 sheets
Maximum output capacity	250 sheets
Paper handling	

Maximum ISO A-series paper size	A3
Paper tray media types	Plain paper, Bond paper, Recycled paper, Envelopes, Card stock, Labels, Transparencies, Lightweight paper, Rough paper, Letterhead
ISO A-series sizes (A0...A9)	A3, A4, A5
Maximum print size	297 x 420 mm
JIS B-series sizes (B0...B9)	B4, B5
Custom media width	76.2 - 312 mm
Custom media length	127 - 469.9 mm
Paper tray media weight	60 - 199 g/m ²
Ports & interfaces	
Direct printing	Yes
USB port	Yes
Standard interfaces	Ethernet, USB 2.0
USB 2.0 ports quantity	4
Network	
Wi-Fi	No
Ethernet LAN	Yes
Network ready	Yes
Cabling technology	10/100/1000Base-T(X)
Ethernet LAN data rates	10,100,1000 Mbit/s
Security algorithms	SNMPv3, SSL/TLS, WPA2-Enterprise, EAP-PEAP, EAP-TLS
Mobile printing technologies	Mopria Print Service, HP ePrint, Apple AirPrint
Performance	
Internal memory	512 MB
Maximum internal memory	1024 MB
Internal storage capacity	8 GB
Built-in processor	Yes
Processor frequency	800 MHz
Sound pressure level (printing)	54 dB
Sound power level (printing)	6.8 dB
Design	
Market positioning	Business
Product colour	Black, Grey
Built-in display	Yes
Display	LCD

Colour display	Yes
Display diagonal	5.08 cm (2")
Control type	Buttons
Certification	CISPR 22:2008 / EN 55022:2010 (Class A); EN 61000-3-2 :2006 +A1:2009 +A2:2009; EN 61000-3-3 :2008;EN 55024:1998 +A1 +A2; EMC Directive 2004/108/EC with CE Marking (Europe); other EMC approvals as required by individual countries

Power

Power consumption (printing)	786 W
Power consumption (ready)	22.1 W
Power consumption (standby)	22.1 W
Power consumption (off)	0.21 W
Energy Star Typical Electricity Consumption (TEC)	2.95 kWh/week
AC input voltage	220 - 240 V
AC input frequency	50/60 Hz

System requirements

Windows operating systems supported	Windows Vista x64, Windows Vista, Windows 7 x64, Windows 7, Windows 8 x64, Windows 8, Windows 10 x64, Windows 10
Mac operating systems supported	Mac OS X 10.6 Snow Leopard, MacOS
Server operating systems supported	Windows Server 2003, Windows Server 2008 R2, Windows Server 2008 R2 x64, Windows Server 2008 x64, Windows Server 2008
Other operating systems supported	Novell, Linux

Operational conditions

Operating temperature (T-T)	10 - 32.5 °C
Storage temperature (T-T)	0 - 60 °C
Operating relative humidity (H-H)	20 - 80%
Storage relative humidity (H-H)	10 - 90%

Sustainability

Sustainability certificates	Blue Angel
Sustainability compliance	Yes

Carbon footprint

Total carbon footprint (kg of CO2e)	510
Carbon emissions, manufacturing (kg of CO2e)	282
Carbon emissions, logistics (kg of CO2e)	14
Total carbon emissions, w/o use phase (kg of CO2e)	195

Weight & dimensions

Width	568 mm
-------	--------

Depth	596 mm
Height	392 mm
Weight	38.5 kg
Maximum dimensions (W x D x H)	858 x 989 x 392 mm
Pallet dimensions (W x D x H)	825 x 800 x 2082 mm
Packaging data	
Package width	810 mm
Package depth	785 mm
Package height	644 mm
Package weight	45.6 kg
Packaging content	
Cables included	AC
Bundled software	Windows Installer, HP PCL 6 discrete driver, Mac Installer, HP Postscript emulation driver
Brand-specific features	
HP Auto-On/Auto-Off	Yes
HP Security tools	Management security: SNMPv3, SSL/TLS, WPA2-Enterprise, 802.1X authentication (EAP-PEAP, EAP-TLS), IPP over TLS, IPsec/Firewall with Certificate, Pre-Shared Key Authentication, and Kerberos Authentication; Support for WJA-10 IPsec Configuration using IPsec Plug-in
HP GTIN (EAN/UPC) with options	(ABT) 886112999643; (ABY) 886112999650; (ACQ) 886112999667; (B13) 888182819876; (B19) 886112999674; (BAZ) 886112999681
HP GTIN (EAN/UPC)	886112999643, 886112999650, 886112999667, 888182819876, 886112999674, 886112999681
Logistics data	
Harmonized System (HS) code	84433210
Pallet gross weight	159.5 kg
Layers per pallet	3 pc(s)
Products per pallet	3 pc(s)
Technical details	
Master (outer) cases per pallet layer	1 pc(s)
General Product Safety Regulation (GPSR) URL	https://support.hp.com/gb-en/product/setup-user-guides/hp-laserjet-enterprise-700-printer-m712-series/model/5118226?sku=CF236A ; https://kaas.hpcloud.hp.com/pdf-public/pdf_10348385_en-US-1.pdf
Other features	

Recommended system requirements	Windows 10; Windows 8; Windows 7; Windows Vista; Windows Server 2008; Windows Server 2008 R2; Windows Server 2003 (SP1+); 200 MB available hard disk space. Mac OS X v10.6; v10.7; 200 MB available hard disk space; operating system compatible hardware system requirements.
Power supply type	Built-in power supply
Electromagnetic compatibility	CISPR 22:2008 / EN 55022:2010 (Class A); EN 61000-3-2 :2006 +A1:2009 +A2:2009; EN 61000-3-3 :2008;EN 55024:1998 +A1 +A2; EMC Directive 2004/108/EC with CE Marking (Europe); other EMC approvals as required by individual countries
Compatible operating systems	Windows 10, Windows 8, Windows 7, Windows Vista, Windows Server 2008 (32-bit/64-bit), Windows Server 2008 R2 (64-bit), Windows Server 2003 (SP1+); Mac OS X v10.6, v10.7; For the latest operating system support see: Citrix and Windows Terminal Services (http://www.hp.com/go/upd), Novell (http://www.novell.com/iprint), Linux (http://www.hplip.net), UNIX (http://www.hp.com/go/unix , http://www.hp.com/go/unixmodelscripts , http://www.hp.com/go/jetdirectunix_software), SAP device types (http://www.hp.com/go/sap/drivers , http://www.hp.com/go/sap/print), HP ePrint Mobile Driver (http://www.hp.com/go/eprintmobiledriver)
Printing	Mono printing
Package dimensions (WxDxH)	810 x 785 x 644 mm
Recommended humidity operating range	30 - 70%
Recommended operating temperature range (T-T)	10 - 32.5 °C
Custom media sizes	Tray 1: 76.2 x 127 to 312 x 469.9 mm; Tray 2: 148 x 210 to 297 to 363 mm; Tray 3: 148 x 210 to 297 to 431 mm
Print margin bottom (A4)	2 mm
Print margin left (A4)	2 mm
Print margin right (A4)	2 mm
Print margin top (A4)	2 mm
Envelope feeder	No
Standard output capacity for transparencies	250 sheets
Acoustic power emissions (ready)	Inaudible
Typical electricity consumption (TEC) number	2.95 kWh/Week
UNSPSC-code	43212105
Box contents	HP LaserJet Enterprise 700 M712dn; HP Black LaserJet Toner Cartridge (~10,000 pages); Automatic duplexer for two-sided printing; Getting Started Guide, CD containing drivers and electronic documentation; Power cord

Matmenys ir svoris

Svoris	46,54kg
--------	---------

Dokumentai ir vaizdo įrašai

- › Gaminio lankstinukas
- › CE ženklavimas

Gamintojo ir saugos informacija

GAMINTOJAS

HP Inc

Page Mill Road 1501, CA 94304 Palo Alto,
California, US

hp.com

ATSAKINGAS ASMUO ES

HP Printing and Computing Solutions S.L.U.

Calle Jose Echegaray 18, 28232 Las Rozas
(Madrid), ES

hp.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Saugos dokumentai

- › [CE ženklavimas](#)
- › [Gamintojo saugos informacija](#)