

iiyama T1531SR-B1S kompiuterio monitorius 38,1 cm (15") 1024 x 768 pikseliai XGA LCD Lietimui jautrus ekranas Juoda

Gamintojas: **IIYAMA** · Modelis: **T1531SR-B1S** · EAN: **4948570122073** · Prekės kodas: **895241**



373,90 €

Kaina su PVM

Be PVM: **309,01 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 38,1 cm (15") Juoda
- ✓ Įmontuoti garsiakalbiai
- ✓ HDMI „DisplayPort“ kiekis: 1
- ✓ Ekrano forma: Plokščias
- ✓ Maksimalus atnaujinimo dažnis: 60 Hz Reakcijos laikas: 18 ms
- ✓ 1024 x 768 pikseliai XGA Skydo tipas: VA
- ✓ Energijos vartojimo efektyvumo klasė (SDR): E ErP CE, cULus, EAC, REACH, RoHS, UKCA, VCCI, WEEE



Aprašymas

The ProLite T1531SR-B1S is based on 5 wire resistive touch technology. The price / performance ratio is ideal for the budget conscious user while quality and performance are certainly not compromised. The display inputs include both analogue and digital (HDMI and DisplayPort) with touchscreen connectivity via USB offering great flexibility. A solid and steady base supports the touchscreen with an adjustable stand offering full

90-degree angles. The ProLite T1531SR-B1S can be used in a variety of environments, especially recommended for shops, restaurants and industrial purposes.

Techninė specifikacija

Display	
Display diagonal	38.1 cm (15")
Display resolution	1024 x 768 pixels
Native aspect ratio	4:3
Display technology	LCD
Touchscreen	Yes
HD type	XGA
Panel type	VA
Response time	18 ms
Screen shape	Flat
Contrast ratio (typical)	2500:1
Maximum refresh rate	60 Hz
Display number of colours	16.2 million colours
Touchscreen technology	Resistive
Touch technology	Single-touch
Number of simultaneous touchpoints	1
Display brightness (peak)	350 cd/m²
Display brightness (typical)	350 cd/m²
Display brightness	270 cd/m²
Viewing angle, horizontal	176°
Viewing angle, vertical	176°
Pixel pitch	0.297 x 0.297 mm
Horizontal scan range	31.5 - 60 kHz
Viewable size, horizontal	30.4 cm
Viewable size, vertical	22.8 cm
Display diagonal (metric)	38 cm
Performance	
NVIDIA G-SYNC	No
AMD FreeSync	No
Multimedia	
Built-in speaker(s)	Yes

Built-in camera	No
Number of speakers	2
RMS rated power	2 W
Design	
Product colour	Black
Front bezel colour	Black
Ports & interfaces	
Built-in USB hub	No
HDMI	Yes
USB Touch port	Yes
VGA (D-Sub) ports quantity	1
HDMI ports quantity	1
DisplayPorts quantity	1
Audio input	Yes
HDCP	Yes
Ergonomics	
VESA mounting	Yes
Cable lock slot	Yes
Height adjustment	No
Panel mounting interface	100 x 100 mm
Cable management	Yes
Cable lock slot type	Kensington
Tilt adjustment	Yes
Tilt angle range	-5 - 90°
On Screen Display (OSD)	Yes
On Screen Display (OSD) languages	Traditional Chinese, German, English, Spanish, French, Italian, Japanese
Power	
Energy efficiency class (SDR)	E
Energy efficiency class (HDR)	Not available
Energy consumption (SDR) per 1000 hours	11 kWh
Power consumption (typical)	16 W
Power consumption (standby)	1.5 W
Power consumption (off)	0.3 W
AC input voltage	100 - 240 V

AC input frequency	50/60 Hz
Power supply type	Internal
Energy efficiency scale	A to G
Weight & dimensions	
Width (with stand)	351 mm
Depth (with stand)	200 mm
Height (with stand)	306.5 mm
Weight (with stand)	4.1 kg
Packaging data	
Package width	425 mm
Package depth	160 mm
Package height	410 mm
Package weight	5.9 kg
USB cable length	1.8 m
Packaging content	
Cables included	AC, USB, HDMI, DisplayPort, Audio
Quick start guide	Yes
Audio cable length	1.8 m
DisplayPort cable length	1.8 m
HDMI cable length	1.8 m
Power cable length	1.8 m
Sustainability	
Sustainability certificates	ErP
Other features	
International Protection (IP) code	IP54
Compatible operating systems	All iiyama monitors are Plug & Play and compatible with Windows and Linux. For details regarding the supported OS for the touch models, please refer to the driver instruction file available in the downloads section.
Brightness	270 cd/m²
Packaging content	Screwdriver
Active display area (W x H)	304 x 228 mm
Weight	4.1 kg
Height	306.5 mm
Width	351 mm
Depth	200 mm

Compliance certificates	CE, cULus, EAC, REACH, RoHS, UKCA, VCCI, WEEE
Mean time between failures (MTBF)	50000 h
User controls	picture (contrast, brightness, H. position, V. position, phase, clock, auto adjust), advanced (color temp., sharpness), OSD (timeout, position, H-position, V-position), option (reset, language, source select, display mode, volume, mute, factory)
Touch method	stylus, finger, glove, glove (latex)
Control panel	Menu, Scroll up/ Brightness, Scroll down/ Mute, Select, Power


Technical details

Native refresh rate	60 Hz
---------------------	-------

Matmenys ir svoris

Matmenys (I × P × A)	43,00cm × 40,00cm × 16,00cm
Svoris	5,82kg

Energijos efektyvumas ir ekologinis projektavimas



Energijos efektyvumo klasė

E A-G

- > [Energijos etiketė](#)
- > [Gaminio informacijos lapas](#)
- > [EPREL duomenų bazė](#)



2024/02/11

Dokumentai ir vaizdo įrašai

- > [Naudojimo instrukcija](#)
- > [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

iiyama International

Wijkmeesterstraat 8, 2131 HA Hoofddorp, NL

iiyama.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt