

Hannspree Open Frame Monitor

 Gamintojas: **HANNSPREE** · Modelis: **HO221PTB** · EAN: **4711404025037** · Prekės kodas: **895660**


308,90 €

Kaina su PVM

 Be PVM: **255,29 €**

Sandėlyje


Prekė internetu

 Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Glass Protection: Thickness 3.6 mm
- ✓ Built-in-Speakers
- ✓ AntiFingerprint-coating
- ✓ 10-Point Touch P-Cap Technology-
- ✓ 1920 x1080 Full HD Resolution
- ✓ USB 3.0 HUB
- ✓ HDMI + DP Inputs
- ✓ Optical Bonding
- ✓ VESA Mount
- ✓ 178° / 178° Ultra Wide Viewing Angle



Aprašymas

Designed for demanding professional environments, our new HO221PTB Touch Monitor is built for flexibility and durability. The monitor features a sturdy metal housing, 3.6 mm protective glass with anti-fingerprint coating, and a full-flat front design for seamless integration into kiosks, industrial

systems, and embedded applications. Multiple digital inputs (DP and HDMI), an integrated USB 3.0 hub, and built-in speakers ensure easy connectivity and enhanced usability.

Built for Integration, Designed to Perform

An excellent choice for commercial applications, interactive digital signage, instore retail, gaming and amusement arcades, POS terminals, interactive kiosks, and presentation purposes.

Seamless Touch, Endless Possibilities

Empower teams to play, create, and collaborate with PCAP technology supporting 10-point multi-touch functionality. Enjoy effortless annotation, smooth navigation, and precise control with intuitive tap, swipe, slide, and pinch gestures.

A durable glass overlay ensures reliable performance, resistant to dirt, dust, condensation, liquid spills, and cleaning solutions—making it the perfect choice for everyday, long-lasting use.

Crystal-Clear Precision with Optical Bonding

Experience exceptional clarity and responsiveness with Optical Bonding Technology in our HANNSpree HO221PTB Touch Monitor. By eliminating the air gap between the touch panel and display, this advanced bonding process reduces glare and reflections, enhances contrast, and increases durability.

The result? Vivid visuals and an ultra-responsive touch experience with superior accuracy—perfect for professional applications, gaming, and interactive environments.

See the difference. Feel the precision. Elevate your touch experience today.

Full HD Resolution and wide viewing angles 178°

The HANNSpree HO221PTB combines Full HD 1920 × 1080 resolution with 10-point projected capacitive (P-Cap) touch technology to deliver precise, responsive interaction and outstanding visual clarity. With an ultra-wide 178° viewing angle, content remains sharp and consistent from virtually any direction. This provides greater flexibility when extending your screen, ensuring superb color and contrast—even from extreme viewing positions—without colors washing out.

Multi-Touch Screen with 7H Surface Hardness

A 7H scratch-resistant surface ensures durability and a consistently high-quality touch experience. Scratch resistance is essential for touch solutions in education and public environments. A toughened glass overlay protects the screen, allowing the panel surface to withstand scratches and impacts from everyday objects—making it ideal for public spaces and educational institutions.

With its 7H hardness rating, the HO221PTB is engineered for integration into kiosks, industrial systems, and embedded applications - delivering long-lasting protection against impacts, dirt, and daily wear.

Support Multi-OS

The HO221PTB touch monitor is compatible with multiple operating systems, including Windows, Linux, Android, and macOS (single touch point, driver required), offering greater flexibility in your choice of operating system.

VESA Mount

The HO221PTB features a rugged bezel with edge-to-edge glass, making it suitable for applications like tabletop integration. It supports rear VESA and external mounting brackets for multiple mounting options. It's easy to install and flexible for different applications.

Techninė specifikacija

Display		
Display diagonal		54.5 cm (21.4")
Display technology		LCD
Display resolution		1920 x 1080 pixels
Display brightness		600 cd/m²
HD type		Full HD
Touchscreen		Yes
Panel type		TFT-LCD
LED backlight		Yes
Touchscreen technology		Projected capacitive system
Number of simultaneous touchpoints		10
Multi-touch		Yes
Native aspect ratio		16:9
Response time		14 ms
Contrast ratio (typical)		1000:1
Viewing angle, horizontal		178°
Viewing angle, vertical		178°
Display number of colours		16.7 million colours
Active display area (W x H)		0.241 x 0.2493 mm
Horizontal scan range		56 - 84.5 kHz
Vertical scan range		50 - 75 Hz
Surface hardness		7H
Glass thickness		3.6 mm
Ports & interfaces		
DisplayPorts quantity		1
USB port		Yes
DisplayPorts in		1
DisplayPort version		1.2
USB 3.2 Gen 1 (3.1 Gen 1) Type-B ports quantity		1
Number of speaker outputs		1
Audio		
Built-in speaker(s)		Yes
Number of built-in speakers		2

RMS rated power	4 W
-----------------	-----

Speaker impedance	4 Ω
-------------------	-----

Design

Product design	Digital signage flat panel
----------------	----------------------------

Product colour	Black
----------------	-------

Placement supported	Indoor
---------------------	--------

VESA mounting	Yes
---------------	-----

Panel mounting interface	100 x 100 mm
--------------------------	--------------

Performance

Purpose	Universal
---------	-----------

On Screen Display (OSD)	Yes
-------------------------	-----

Number of OSD languages	11
-------------------------	----

Smart modes	Game, Standard, Cinema
-------------	------------------------

Power

Input voltage	100 - 240 V
---------------	-------------

Power consumption (off)	0.3 W
-------------------------	-------

Energy efficiency class (SDR)	E
-------------------------------	---

Energy consumption (SDR) per 1000 hours	14 kWh
---	--------

AC input frequency	50/60 Hz
--------------------	----------

Energy efficiency scale	A to G
-------------------------	--------

Computer system

Computer system	No
-----------------	----

Built-in processor	No
--------------------	----

Windows operating systems supported	Yes
-------------------------------------	-----

Mac operating systems supported	Yes
---------------------------------	-----

Linux operating systems supported	Yes
-----------------------------------	-----

Weight & dimensions

Display width	572 mm
---------------	--------

Display depth	112 mm
---------------	--------

Display height	364 mm
----------------	--------

Display weight	5 kg
----------------	------

Packaging data

Package weight	6.5 kg
----------------	--------

Operational conditions

Operating temperature (T-T) 20 - 30 °C

Operating relative humidity (H-H) 10 - 90%

Other features

Headphone outputs 1

LED indicators Yes


Technical details

Power consumption 35 W

Matmenys ir svoris

Svoris 6,50kg

Energijos efektyvumas ir ekologinis projektavimas



Energijos efektyvumo klasė **E** A-G

- > [Energijos etiketė](#)
- > [Gaminio informacijos lapas](#)
- > [EPREL duomenų bazė](#)

Dokumentai ir vaizdo įrašai

- > [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

Hannspree Europe Holdings B.V.
Newtonweg 25, 5928 PN Venlo, NL
hannspree.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt