

Ernitec 0070-24113-WT-OS computer monitor 33 cm (13") 1920 x 1080 pixels LCD Touchscreen

Gamintojas: **ERNITEC** · Modelis: **0070-24113-WT-OS** · EAN: **5715328146549** · Prekės kodas: **896788**



822,90 €

Kaina su PVM

Be PVM: **680,08 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 33 cm (13")
- ✓ Built-in speaker(s)
- ✓ Response time: 5 ms
- ✓ 1920 x 1080 pixels



Aprašymas

Product Overview:

Ernitec introduces its latest touch screen monitors, designed specifically for harsh environments.

With operation Windows system - I5, 6G memory, ordinary hard disk, with 4G wireless network card

These monitors feature IP67 protection on the front and IP22 protection on the back, ensuring durability and reliability in wet and humid conditions.

The capacitive touch technology offers precise and responsive interaction, making them ideal for various applications.

Key Features:

IP67 Front Protection: Complete protection against dust and water, allowing the monitors to withstand immersion up to 1 meter for 30 minutes

IP22 Back Protection: Protection against dripping water when tilted up to 15 degrees, suitable for indoor environments

Capacitive Touch Technology: Provides accurate and responsive touch capabilities, enhancing user experience

Swimhall Ready: Specifically designed to perform optimally in swimhall environments, resisting humidity and water exposure

Target Audience:

Swimhalls and Aquatic Centers: Ideal for installations in swimhalls, aquatic centers, and other wet environments

Industrial Applications: Suitable for factories and industrial settings where water and humidity are prevalent.

Outdoor Venues: Perfect for outdoor installations requiring robust and weather-resistant monitors.

Benefits:

Durability: With IP67 and IP22 ratings, these monitors are built to last in challenging environments.

Enhanced User Experience: Capacitive touch technology ensures smooth and precise interaction.

Versatility: Suitable for a wide range of applications, from swimhalls to industrial settings.

Marketing Strategy:

Highlight Durability: Emphasize the IP67 and IP22 ratings in marketing materials to showcase the monitors' resilience.

Focus on User Experience: Promote the benefits of capacitive touch technology for improved interaction.

Target Specific Markets: Tailor marketing campaigns to swimhalls, industrial applications, and outdoor venues.

Conclusion: Ernitec's new touch screen monitors are the perfect solution for environments where water and humidity are a concern.

With their robust protection and advanced touch technology, they offer reliability and enhanced user experience, making them a valuable addition to any swimhall or industrial setting.

These specific monitors when installed outside needs to have a roof or being built into a wall to protect the backside of the monitor.

Techninė specifikacija

Display	
Display diagonal	33 cm (13")
Display resolution	1920 x 1080 pixels
Display technology	LCD
Touchscreen	Yes
Response time	5 ms
Contrast ratio (typical)	1000:1
Display number of colours	16.7 million colours
LED backlight	Yes
Touchscreen technology	Capacitive
Number of simultaneous touchpoints	10
Display brightness (typical)	119 cd/m²
Display brightness	119 cd/m²
Aspect ratio	16:9
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Pixel pitch	0.63 x 0.63 mm
Performance	
Operating hours (hours/days)	24/7
Multimedia	
Built-in speaker(s)	Yes
Number of speakers	2
RMS rated power	6 W

Design

Housing material	Metal
------------------	-------

Ports & interfaces

HDMI ports quantity	2
---------------------	---

Network

Wi-Fi	Yes
-------	-----

Ergonomics

VESA mounting	Yes
---------------	-----

Panel mounting interface	75 x 75 mm
--------------------------	------------

On Screen Display (OSD) languages	English
-----------------------------------	---------

Power

Power consumption (typical)	7 W
-----------------------------	-----

Power consumption (average)	7 W
-----------------------------	-----

Power supply type	External
-------------------	----------

Operational conditions

Operating temperature (T-T)	-30 - 85 °C
-----------------------------	-------------

Packaging data

Package width	380 mm
---------------	--------

Package depth	150 mm
---------------	--------

Package height	350 mm
----------------	--------

Package weight	4 kg
----------------	------

Other features

International Protection (IP) code	IP67
------------------------------------	------

Noise filter	Yes
--------------	-----

Active display area (W x H)	276.48 x 276.48 mm
-----------------------------	--------------------

USB ports quantity	1
--------------------	---

Weight	3 kg
--------	------

Height	350 mm
--------	--------

Width	380 mm
-------	--------

Depth	150 mm
-------	--------

Mean time between failures (MTBF)	50000 h
-----------------------------------	---------

Ethernet LAN (RJ-45) ports	1
----------------------------	---

Certification	EMC Class A
---------------	-------------

Matmenys ir svoris

Svoris

3,00kg

Energijos efektyvumas ir ekologinis projektavimas

[› Energijos etiketė](#)

Dokumentai ir vaizdo įrašai

[› Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

EET Group A/S

Bregnerødvej 133D, 3460 Birkerød, DK

eetgroup.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt