

APC Easy Rack PDU, Basic, Vertical, 1 Phase, 3.7kW, 230V, 16A, 14 x SCHUKO outlets, SCHUKO 16A

Gamintojas: **APC** · Modelis: **SEP6113G** · EAN: **731304804598** · Prekės kodas: **897581**



256,90 €

Kaina su PVM

Be PVM: **212,31 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ World class power distribution at an accessible price point.
- ✓ The uncomplicated rPDU that simply provides power for the customer's solutions.
- ✓ Perfect offering for smaller organizations that are without dedicated IT staff.
- ✓ An eco friendly design ensures business continuity and environmental friendliness.
- ✓ It offers a sustainability the reduces energy waste with a green premium.



Aprašymas

The SEP6 Extension for the Basic APC Easy rPDU provides the power for a rack full of devices while being easy to install and inexpensive. It's an integral piece of a plan to deliver a network infrastructure that is standardized and reliable. The SEP6 Extension for the Basic APC Easy rPDU slots perfectly into any data center and supports current solutions with ones to be deployed in the future. It's nominal power runs between 2.3-22kW and can operate at a maximum temperature of 60C, which is the highest of any Easy rPDU. The SEP6113G is vertical with 3.7kW, 230V and 16A with 14 SCHUKO outlets. In addition to the operating high temperature the SEP6 Extension for the Basic APC Easy rPDU has 42 outlets, also more than any other Easy rPDU offering. It's a key part of any environmental friendly policies and reduces energy waste with a Green Premium. The offerings of Single and Three Phase and the rPDU comes equipped with standardized one single platform with TUV certified safety and EMC report. Thanks to its budget friendly pricepoint, the rPDU is perfect when it comes to current and future AI technologies allowing for business growth and margin improvement. Customer satisfaction is guaranteed as the rPDU comes with a standard two year warranty for any field replacement units.

Techninė specifikacija

Design	
PDU types	Basic
Rack capacity	0U
Type	Single-phase
Mounting	Vertical
Product colour	Black
Ports & interfaces	
AC outlets quantity	14 AC outlet(s)
AC outlet types	Type F
Power plug	Type F
Power	
Maximum current	16 A
AC input frequency	50/60 Hz
Output voltage	230 V
Maximum power	3700 W
Certificates	
Certification	CE
Operational conditions	
Operating temperature (T-T)	-5 - 60 °C
Storage temperature (T-T)	-25 - 60 °C
Operating relative humidity (H-H)	5 - 95%
Weight & dimensions	
Width	56 mm
Depth	800 mm
Height	56 mm
Weight	1.35 kg
Packaging data	
Package weight	2.15 kg
Package width	170 mm
Package depth	960 mm
Package height	126 mm
Matmenys ir svoris	

Svoris

2,15kg

Dokumentai ir vaizdo įrašai

- › Naudojimo instrukcija
- › Gaminio lankstinukas

Gamintojo ir saugos informacija

GAMINTOJAS

Schneider Electric SE

rue Joseph Monier 35, 92500 RUEIL MALMAISON, FR

[se.com](https://www.se.com)

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt