

iiyama ProLite T1932MSC-W2AG computer monitor 48.3 cm (19") 1280 x 1024 pixels LED Touchscreen Black, White

Gamintojas: **IIYAMA** · Modelis: **T1932MSC-W2AG** · EAN: **4948570115167** · Prekės kodas: **897835**



360,89 €

Kaina su PVM

Be PVM: **298,26 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 48.3 cm (19") Black, White
- ✓ Screen shape: Flat
- ✓ Response time: 14 ms
- ✓ 1280 x 1024 pixels Panel type: IPS



Aprašymas

The ProLite T1932MSC-W2AG 19" multi touch screen is based on projective capacitive technology which thanks to a glass overlay covering the screen guarantees high durability, scratch-resistance and perfect picture performance. The IPS matrix guarantees high performance with accurate and consistent colour reproduction, and wide viewing angles. Anti Glare coating helps to avoid issues with reflections and external light sources affecting colour reproduction, contrast and sharpness. Its touch function remains unaffected even if the glass is scratched. A solid and steady base supports the touch screen with an adjustable stand offering full 90 degree positioning angles. In addition, the edge-to-edge glass design creates an eye-catching finish with high light transmission guaranteeing perfect picture clarity and brilliant colours.

IPS

IPS technology offers higher contrast, darker blacks and much better viewing angles than standard TN technology. The screen will look good no matter what angle you look at it.

Touch technology - Capacitive

This technology uses a sensor-grid of micro-fine wires integrated into the glass that covers the screen. Touch is detected because electrical characteristics of the sensor grid change when human finger is placed on the glass. Thanks to the glass overlay this technology is highly durable, and the touch function remains unaffected even if the glass is scratched. It offers perfect picture performance and will work with human finger (also latex gloved) and magnetic ball.

IP54

The IP Code classifies how resistant a device is to foreign objects and moisture. IP54 means that the monitor will operate in dusty conditions, and will resist splashing water.

Scratch resistance

Scratch resistance is essential for touch solutions used in public places and schools. This is achieved thanks to a glass overlay covering the screen. It guarantees high durability of the touch function and even more importantly the touch function remains unaffected even if the glass is scratched.

AG Coating

The Anti Glare coating is used in professional-grade displays to help avoid issues with reflections and external light sources affecting colour reproduction, contrast and sharpness. It also makes the screen less susceptible to dust, grease and dirt marks.

Techninė specifikacija

Display	
Display diagonal	48.3 cm (19")
Display resolution	1280 x 1024 pixels
Native aspect ratio	5:4
Display technology	LED
Touchscreen	Yes
Panel type	IPS
Response time	14 ms
Screen shape	Flat

Contrast ratio (typical)	1000:1
Display number of colours	16.78 million colours
Touchscreen technology	Capacitive
Touch technology	Multi-touch
Display brightness	215 cd/m²
Aspect ratio	5:4
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Pixel pitch	0.294 x 0.294 mm
Horizontal scan range	31.4 - 80 kHz
Vertical scan range	56 - 75 Hz
Display diagonal (metric)	48 cm
Separate H/V sync	Yes

Performance

NVIDIA G-SYNC	No
AMD FreeSync	No
Windows operating systems supported	Windows 2000, Windows 2000 Professional, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows CE, Windows NT, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64
Mac operating systems supported	Mac OS X 10.0 Cheetah, Mac OS X 10.1 Puma, Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.2 Jaguar, Mac OS X 10.3 Panther, Mac OS X 10.4 Tiger, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks
Linux operating systems supported	Yes
OmniTapps Multitouch compatibility	No
Number of simultaneous touchpoints (Windows 7)	10

Multimedia

Built-in camera	No
Number of speakers	2
RMS rated power	2 W
Built-in microphone	No

Design

Product colour	Black, White
----------------	--------------

Ports & interfaces

Number of upstream ports	1
--------------------------	---

VGA (D-Sub) ports quantity	1
----------------------------	---

DVI port	Yes
----------	-----

DVI-D ports quantity	1
----------------------	---

HDMI ports quantity	0
---------------------	---

DisplayPorts quantity	0
-----------------------	---

Ergonomics

VESA mounting	Yes
---------------	-----

Cable lock slot	Yes
-----------------	-----

Panel mounting interface	100 x 100 mm
--------------------------	--------------

Wall mountable	Yes
----------------	-----

Tilt adjustment	Yes
-----------------	-----

Tilt angle range	-5 - 90°
------------------	----------

On Screen Display (OSD) languages	Simplified Chinese, Traditional Chinese, German, English, Spanish, French, Italian, Japanese
-----------------------------------	--

Number of OSD languages	7
-------------------------	---

Plug and Play	Yes
---------------	-----

Power

Power consumption (typical)	20 W
-----------------------------	------

AC input voltage	100-240 V
------------------	-----------

AC input frequency	50 - 60 Hz
--------------------	------------

Power supply type	AC
-------------------	----

Operational conditions

Operating temperature (T-T)	0 - 40 °C
-----------------------------	-----------

Storage temperature (T-T)	-20 - 60 °C
---------------------------	-------------

Operating relative humidity (H-H)	20 - 80%
-----------------------------------	----------

Storage relative humidity (H-H)	10 - 90%
---------------------------------	----------

Weight & dimensions

Dimensions (W x D x H) with stand	432 x 391 x 219 mm
-----------------------------------	--------------------

Width (with stand)	432 mm
--------------------	--------

Depth (with stand)	391 mm
--------------------	--------

Height (with stand)	219 mm
---------------------	--------

Weight (with stand)	6.9 kg
Width (without stand)	432 mm
Depth (without stand)	54.5 mm
Height (without stand)	358 mm
Packaging content	
Cables included	AC, Audio (3.5mm), DVI, USB, VGA
Quick start guide	Yes
Other features	
International Protection (IP) code	IP54
Display viewable area (HxV)	301.1 x 376.5 mm
Glass protection	Yes
Power management	Yes
Certification	CE, CB, TÜV, VCCI, CU, cULus
Logistics data	
Harmonized System (HS) code	85285210
Matmenys ir svoris	
Svoris	8,61kg

Dokumentai ir vaizdo įrašai

- › [Naudojimo instrukcija](#)
- › [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

iiyama International

Wijkmeerstraat 8, 2131 HA Hoofddorp, NL

[iiyama.com](https://www.iiyama.com)

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt