

iiyama ProLite T1532MSC-B3X computer monitor 38.1 cm (15") 1024 x 768 pixels LED Touchscreen Tabletop Black

Gamintojas: **IIYAMA** · Modelis: **T1532MSC-B3X** · EAN: **4948570114559** · Prekės kodas: **897836**



292,90 €

Kaina su PVM

Be PVM: **242,07 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 38.1 cm (15") Black
- ✓ Screen shape: Flat
- ✓ Response time: 8 ms
- ✓ 1024 x 768 pixels



Aprašymas

15" Projective Capacitive 10pt touch screen

The ProLite T1532MSC 15" multi-touch screen is based on projected capacitive technology which thanks to a glass overlay covering the screen guarantees high durability, scratch-resistance and perfect picture performance. The touch function remains unaffected even if the glass is scratched. A solid and steady base supports the TouchScreen with an adjustable stand offering full 90 degree positioning angles. Menu Buttons are located on the side of the screen which can be locked to prevent tampering and includes a handy function to deactivate the TouchScreen for cleaning. In addition the edge-to-edge glass design creates an eye-catching finish with high light transmission guaranteeing perfect picture clarity and brilliant colours.

TOUCH TECHNOLOGY - CAPACITIVE

This technology uses a sensor-grid of micro-fine wires integrated into the glass that covers the screen. Touch is detected because electrical characteristics of the sensor grid change when human finger is placed on the glass. Thanks to the glass overlay this technology is highly durable, and the touch function remains unaffected even if the glass is scratched. It offers perfect picture performance and will work with human finger (gloved or not) and magnetic ball.

IP54

The IP Code classifies how resistant a device is to foreign objects and moisture. IP54 means that the monitor will operate in dusty conditions, and will resist splashing water.

SCRATCH RESISTANCE

Scratch resistance is essential for touch solutions used in public places and schools. This is achieved thanks to a glass overlay covering the screen. It guarantees high durability of the touch function and even more importantly the touch function remains unaffected even if the glass is scratched.

SPEAKERS

This LED monitor is equipped with two high quality stereo speakers.

VESA

VESA mount compliance means you can easily mount the LFD to any mounting that complies with the VESA standard.


Techninė specifikacija

Display	
Display diagonal	38.1 cm (15")
Display resolution	1024 x 768 pixels
Native aspect ratio	4:3
Display technology	LED
Touchscreen	Yes
Response time	8 ms
Screen shape	Flat

Contrast ratio (typical)	700:1
Display number of colours	16.78 million colours
Touchscreen type	Tabletop
Touchscreen technology	Capacitive
Touch technology	Multi-touch
Display brightness	330 cd/m²
Aspect ratio	4:3
Viewing angle, horizontal	170°
Viewing angle, vertical	160°
Pixel pitch	0.297 x 0.297 mm
Digital horizontal frequency	31.4 - 60 kHz
Digital vertical frequency	56 - 75 Hz
Display diagonal (metric)	38 cm
Colour gamut	90%
Separate H/V sync	Yes
Performance	
NVIDIA G-SYNC	No
AMD FreeSync	No
Mac operating systems supported	Yes
Multimedia	
Built-in camera	No
Number of speakers	2
RMS rated power	2 W
Megapixel (approx.)	0.8 MP
Design	
Product colour	Black
Ports & interfaces	
Number of upstream ports	1
VGA (D-Sub) ports quantity	1
DVI port	Yes
DVI-D ports quantity	1
HDMI ports quantity	0
DisplayPorts quantity	0
Audio input	1

Ergonomics	
VESA mounting	Yes
Cable lock slot	Yes
Wall mountable	Yes
Tilt angle range	-5 - 90°
On Screen Display (OSD) languages	English, Spanish, Italian, Simplified Chinese, Japanese, Traditional Chinese, French, German
Number of OSD languages	8
Plug and Play	Yes
LED indicators	Yes
Power	
Power consumption (typical)	20 W
Power consumption (standby)	2 W
AC input voltage	100-240 V
AC input frequency	50 - 60 Hz
Weight & dimensions	
Width (with stand)	351 mm
Depth (with stand)	202 mm
Height (with stand)	306.5 mm
Weight (with stand)	4.5 kg
Packaging content	
Cables included	AC, DVI, Audio (3.5mm), USB, VGA
Other features	
Display viewable area (HxV)	228 x 304 mm
Power management	Yes
Certification	CE, CB, CU, TÜV-Bauart, VCCI, cULus, IP54
Logistics data	
Harmonized System (HS) code	85285210
Matmenys ir svoris	
Svoris	6,25kg

Energijos efektyvumas ir ekologinis projektavimas



› [Energijos etiketė](#)

Dokumentai ir vaizdo įrašai

- › Naudojimo instrukcija
- › Gaminio lankstinukas

Gamintojo ir saugos informacija

GAMINTOJAS

iiyama International

Wijkmeerstraat 8, 2131 HA Hoofddorp, NL

[iiyama.com](https://www.iiyama.com)

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt