Axagon N HMC-5HL USB 5Gbps hub 2x USB-A HDMI 4k/60Hz RJ-45 GLAN PD 100W kabel USB-C Vielinis USB 3.2 Gen 1 (3.1 Gen 1) Type-C Sidabras

Gamintojas: **AXAGON** · Modelis: **HMC-5HL** · EAN: **8595247907516** · Prekės kodas: **898698**



39,91 €

Kaina su PVM

Be PVM: **32,98 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Vielinis
- ✓ Priimančioji sąsaja: USB 3.2 Gen 1 (3.1 Gen 1) Type-C
- ✓ „USB Power Delivery“
- ✓ Ethernet LAN jungtis 10,100,1000 Mbit/ai Wake-on-LAN pasirengimas
- ✓ „Plug and Play“ funkcija













Aprašymas

The multi-port USB-C 5Gbps hub AXAGON HMC-5HL expands your laptop with five ports. You can easily and quickly connect a monitor, two USB devices and a Gigabit Ethernet network to the computer at the same time via the double-sided USB-C connector. You also get the possibility to

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

supply laptop using Power Delivery technology. The USB-C hub will provide you with a universal and powerful 5in1 docking station for modern laptops.

The USB hub offers two USB outputs with standard USB-A connectors. The hub can also handle permanent connection of several external drives simultaneously. Transfer rate up to 5Gb/s thanks to the fast USB 3.2 Gen 1 interface. The hub will also enable charging of phones and tablets with a current of up to 1.5A/5V, so you can easily charge e.g. Android smartphone, Apple iPhone, Apple iPad etc.

The USB-C connector is reserved only for powering and simultaneous charging of laptops using Power Delivery 3.0 technology with a power of up to 100W. Connect the USB-C Power Delivery charger to the hub and connect the hub to the laptop. This saves one USB-C port. The condition is a laptop with Power Delivery charging support from the USB-C port and a suitable PD charger.

HDMI video output provides high-quality images up to 4K/60Hz Ultra HD resolution. High frequencies at popular gaming resolutions of 2K/144Hz or FullHD/240Hz are also supported. Thanks to HDR (high dynamic range) support, you can enjoy a significantly expanded range of colors and contrasts without restrictions. DisplayPort Alternate Mode (DP Alt Mode) enabled USB-C port or Thunderbolt 3/4 port is necessary for the proper function of video output.

Gigabit network card extends your computer by a fast and stable network connection, adds the missing RJ-45 network connector or another network card.

The aluminum cover ensures mechanical durability and cooling of the USB hub. Thanks to the Plug and Play and Hot Plug functions, connecting the hub itself is very simple without complicated installation, and peripherals can also be easily connected and disconnected while the computer is running.

Input:
• USB 5Gbps (USB 3.2 Gen 1 / USB 3.0).
• Compatible with Thunderbolt 3/4.
• Connection via reversible USB type C female connector.

USB outputs:
• 2x USB 5Gbps port, USB-A female connector.
• 1x Power Delivery port (power only), USB-C female connector.
• USB-C hub can handle the connection up to two external drives simultaneously.
• Charging of mobile devices (including iPad) with a current of up to 1.5A from the hub's USB-A ports.

Video output:
• 1x HDMI A port, HDMI A female connector.
• 4K resolution 4096 x 2160 at up to 60Hz.
• 2K / WQHD resolution 2560 x 1440 at up to 120Hz.
• FHD resolution 1920 x 1080 at up to 240Hz.
• Support for the above max. supported resolutions and frequencies requires connection to a computer with DisplayPort version 1.4.
• For the video output function, the hub must be connected to a USB-C port supporting DisplayPort Alternate Mode (DP Alt Mode) or to a USB-C port supporting Thunderbolt 3/4. A suitable OS is also required. The video output function will not be available without these requirements.
• HDR support (High dynamic range, 10 bit support) - realistic reproduction of light and dark details.
HPD (Hot-Plug-Detect) support.
• TMDS (Transition Minimized Differential Signalling) support.
• HDCP 1.4 and 2.3 (High-bandwidth Digital Content Protection) full support.
• Support for 2-channel audio sampling rate up to 192 kHz and up to 24-bit audio - depends on source and end device, i.e. laptop/phone and TV/monitor/AV receiver.

RJ-45 output:
• Gigabit Ethernet interface with RJ-45 connector for UTP or STP cable connection.

• Supported transmission rates for the Ethernet interface 10/100/1000 Mb/s.
• Supported IEEE 802.3 10Base-T, IEEE 802.3u 100Base-TX, IEEE 802.3ab 1000Base-T specifications.
• 10/100/1000 Mb/s auto-detection.
• Wake-on-LAN support.

Power Delivery:
• Power Delivery 3.0 support – device power supply from the wall charger via USB-C hub.
• Maximum power supply power via PD USB-C hub output 100W - 20V/5A.
• Required PD support from the device (laptop, phone) and a suitable PD wall charger.

Other features:
• Possibility to connect your device while running thanks to the Hot Plug support.
• Full Plug and Play support.
• Standby mode support.
• Power via USB bus - USB bus power or from PD wall charger.
• Heavy-duty aluminium body for better hub cooling. Higher surface hub temperature is not a problem - the heat generated by the hub operation is better dissipated and transferred to the surroundings.
• The blue LED indicates with constant light the hub connection to the computer.
• High quality shielded cable ensures fast communication speed and minimal unwanted interference.
• Dimensions 65 x 77 x 15 mm.
• Weight 61 g.
• USB-C male cable length 20 cm

Supported operating systems:
• Windows 10 / 11 and later macOS, Linux, Android a Chrome OS.
• Compatibility depends on the operating system and device manufacturer support.
• DisplayPort Alternate Mode (DP Alt Mode) is only supported in updated OS and also depends on support from device (notebook, phone) manufacturer.
• Graphics card drivers may also affect the correct operation of the product. We recommend downloading the latest version of drivers.

Package contains:
• USB-C hub,
• multilingual manual CZ / DE / DK / ENG / ESP / FIN / FR / GR / HR / HU / IT / NL / PL / PT / RO / RU / SK / SWE / BG / CN / TR / ARA,
• packed in a cardboard box with a hanging hole.

Techninė specifikacija

Ryšys	
Ryšio technologija	Vielinis
Priimančioji sąsaja	USB 3.2 Gen 1 (3.1 Gen 1) Type-C
USB 3.2 (3.1 1 kart.) A tipo prievadų skaičius	2
HDMI portų kiekis	1
Mikrofonas, line-in jack	Ne
USB 3.2 (3.1 1 kart.) C tipo prievadų skaičius	1
„USB Power Delivery“	Taip
USB maitinimo šaltinio peržiūra	3.0

USB maitinimo tiekimas iki	100 W
Jungtinis ausinių / mikrofono prievadas	Ne
HDCP	Taip
HDCP versija	1.4/2.3
„USB Type C DisplayPort Alternate Mode“	Taip
DC įėjimo lizdas	Ne

Tinklas

Ethernet LAN jungtis	Taip
Ethernet LAN (RJ-45) portų kiekis	1
Eterneto LAN duomenų perdavimo norma	10,100,1000 Mbit/ai
Wake-on-LAN pasirengimas	Taip
Tinklo standartai	IEEE 802.3, IEEE 802.3ab, IEEE 802.3u

Veikimo charakteristikos

Produkto spalva	Sidabras
Integruotas kortelių skaitytuvas	Ne
Duomenų perdavimo sparta	5 Gbit/s
HD tipas	4K Ultra HD
Maksimali skaitmeninė raiška	4096 x 2160 pikseliai
Maksimalus atnaujinimo dažnis	240 Hz
Hot-Plug palaikymas	Taip
Palaikoma HDR	Taip
Lizdo sąsajos	HDMI, RJ-45, USB 3.2 Gen 1 (3.1 Gen 1) Type-A, USB 3.2 Gen 1 (3.1 Gen 1) Type-C
LED indikatoriai	Taip
„Plug and Play“ funkcija	Taip
Įkrovimo funkcija	Taip
Korpuso medžiaga	Aliuminis
Kilmės šalis	Kinija
Modelio suderinamumas	Universalus
Sertifikavimas	CE, RoHS

Garsas

Įmontuoti garsiakalbiai	Ne
Įmontuotas mikrofonas	Ne

Aušinimas

Įmontuotas ventiliatorius	Ne

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Energijos valdymas	
Maitinimo šaltinio tipas	USB
Maitinimo jungtis	C tipo USB
USB kabelio ilgis	0,2 m
Belaidis įkrovimas	Ne
Programinė įranga	
Palaikomos „Windows“ operacinės sistemos	Taip
Palaikomos MAC operacinės sistemos	Taip
Palaikoma operacinė sistema „Linux“	Taip
Palaikomos serverio valdymo sistemos	Taip
Palaikomos mobiliosios operacinės sistemos	Taip
Kitos palaikomos operacinės sistemos	Taip
Svoris ir matmenys	
Plotis	65 mm
Ilgis	77 mm
Aukštis	15 mm
Svoris	61 g
Pakuotės duomenys	
Kiekis pakuotėje	1 vnt
Pakuotės plotis	172 mm
Pakuotės gylis	113 mm
Pakuotės aukštis	18 mm
Paketo svoris	99 g
Pakuotės turinys	
Pridėti kabeliai	C tipo USB
Instrukcija	Taip
Techninė informacija	
Garantinis laikotarpis	3 metai
Atitikties sertifikatai	RoHS, CE
Matmenys ir svoris	
Matmenys (I × P × A)	2,00cm × 12,00cm × 17,00cm
Svoris	0,10kg

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Dokumentai ir vaizdo įrašai

› Naudojimo instrukcija

Gamintojo ir saugos informacija

GAMINTOJAS

RealQ, s.r.o.
Železná 663/5, 619 00 Brno-jih, CZ
axagon.eu

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.