

TP-Link VIGI C230I MINI(2.8MM) security camera Dome IP security camera Indoor & outdoor 2304 x 1296 pixels Ceiling

 Gamintojas: **TP-LINK** · Modelis: **VIGI C230I MINI(2.8MM)** · EAN: **4897098688922** · Prekės kodas: **899176**


59,89 €

Kaina su PVM

 Be PVM: **49,50 €**

Sandėlyje


Prekė internetu

 Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Indoor & outdoor IP security camera
- ✓ CMOS 25.4 / 2.8 mm (1 / 2.8") 3 MP 2304 x 1296 pixels
- ✓ Wired Ethernet LAN
- ✓ Night vision 30 m IR
- ✓ Dome Ceiling
- ✓ IK08
- ✓ White



Aprašymas

Looking for a higher resolution? It's right here.

3MP Super-High Definition

The VIGI C230I Mini Camera comes with 3MP—more than enough pixels to pick up some of the more discrete details.

Human & Vehicle Classification

Integrated AI chips support advanced algorithms to distinguish humans and vehicles from other objects. You can flexibly customize alarm rules to match your monitoring needs and receive more accurate event notifications.

We keep an eye on your business.

Smart Detection

Backed by AI algorithms, the VIGI camera offers more smart detection. You will receive notifications when someone crosses a boundary, enters an area you've set, obstructs the camera, or removes/abandons objects.

Small but compact with wide views

With a small, compact form factor and a 2.8 mm ultra-wide angle lens, the VIGI C230I Mini Camera is ideal for corridors, elevators, small warehouses, and convenience stores, where space is limited and a wide view is required.

Every Event is Under Your Control.

VIGI camera intelligently detect activities, inform you instantly and response automatically by smart detection and two-way audio.

IK08 Vandal-Proof

Equipped with a vandal-proof dome encasing, the VIGI dome camera withstands damage and provides more reliable security protection in important scenarios, such as ATMs, corridors, and checkout counters.

More compression. More savings. Same quality.

Without using any extra bandwidth, your cameras transmit compressed crystal-clear video to save disk space, ease network loads, and reduce monitoring costs without sacrificing image quality.

Never miss a detail.

SmartVid-Smart Video Enhancement

VIGI's professional technologies process videos to greatly improve their quality that is vital to your monitoring, including Smart IR, WDR, 3D DNR, and Night Vision.

Corridor Mode

Corridor mode allows you to change the image aspect ratio from 16:9 to 9:16. This helps to monitor long and narrow areas and provides a more pleasant viewing experience.

No need to check long compatibility lists.

Onvif Ensures Compatibility

Easily add IPCs from VIGI and other brands to establish a powerful and varied network thanks to barrier-free compatibility [△](#).

Flexible Management and Storage

Take full control over your security via four management methods: the web UI, NVR UI, VIGI app, and VIGI Security Manger. Local storage is available for each methods, as well as onboard storage with SD card slot (up to 256 GB).

One system. Full security.

Run your business with peace of mind.

The VIGI professional surveillance system by TP-Link is dedicated to protecting the business you've worked hard to build — whenever, wherever. Our outstanding functions, reliable quality guarantees, and simplified installation work together to ensure your business stays safe and sound.

Techninė specifikacija

Performance	
Type	IP security camera
Placement supported	Indoor & outdoor
Connectivity technology	Wired

Day/night mode	Yes
Certification	CE/VCCI/BSMI/KC/ONVIF
Design	
Mounting type	Ceiling
Product colour	White
Form factor	Dome
Housing material	Plastic
IK code	IK08
Camera	
Lens viewing angle, horizontal	106.9°
Lens viewing angle, vertical	56.9°
Lens viewing angle, diagonal	127.9°
Image sensor	
Sensor type	CMOS
Optical sensor size	25.4 / 2.8 mm (1 / 2.8")
Lens system	
Fixed focal length	2.8 mm
Night vision	
Night vision	Yes
Night vision distance	30 m
LED type	IR
Video	
Maximum resolution	2304 x 1296 pixels
Total megapixels	3 MP
Video compression formats	H.264, H.264+, H.265, H.265+
Supported graphics resolutions	320 x 240, 352 x 288, 640 x 480 (VGA), 704 x 576, 1280 x 720 (HD 720), 1920 x 1080 (HD 1080), 2048 x 1280, 2304 x 1296
Noise reduction	Yes
Noise reduction technology	3D noise reduction
Image quality adjustment	Brightness, Contrast, Mirror, Saturation, Sharpness
Back Light Compensation (BLC)	Yes
Highlight Compensation (HLC)	Yes
Digital Wide Dynamic Range (DWDR)	Yes
Audio	

Built-in speaker(s)	Yes
Built-in microphone	Yes
Network	
Ethernet LAN	Yes
Wi-Fi	No
Bluetooth	No
Ethernet interface type	Fast Ethernet
Supported network protocols	TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, DNS, RTSP, NTP, UPnP UDP, SSL/TLS
Storage	
Built-in HDD	No
Card reader integrated	Yes
Compatible memory cards	MicroSD (TransFlash)
Maximum memory card size	256 GB
Ports & interfaces	
Ethernet LAN (RJ-45) ports	1
Security	
Password protection	Yes
IP address filtering	Yes
HTTPS encryption	Yes
Management features	
Reset button	Yes
Power	
Power source type	DC, PoE
Power consumption (max)	7.5 W
DC output voltage	12
Operational conditions	
Operating temperature (T-T)	-30 - 60 °C
Weight & dimensions	
Width	114 mm
Depth	58 mm
Height	114 mm
Packaging content	
Number of cameras	1
Matmenys ir svoris	

Matmenys (I × P × A)	20,00cm × 15,00cm × 11,00cm
Svoris	0,41kg

Gamintojo ir saugos informacija

GAMINTOJAS

TP-Link

ATSAKINGAS ASMUO ES

TP-Link Deutschland GmbH

Niederkasseler Lohweg 175, 40547 Düsseldorf,
DE

tp-link.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt