# TP-Link VIGI 4MP Outdoor Full-Color Bullet Network Camera

Gamintojas: **TP-LINK** · Modelis: **VIGI C340(2.8MM)** · EAN: **4897098688618** · Prekės kodas: **899182**



**70.91€**

Kaina su PVM

Be PVM: **58.60€**

**In Stock**

**Prekė internetu**
Nuskenuokite kodą arba apsilankykite www.shopro.lt

## Pagrindinės savybės

- ✓ 4MP High Definition: The camera comes with 4MP–more than enough pixels to pick up some of the more discrete details
- ✓ 24h Full-Color: Obtain 24-hour color details, even in pitch-black conditions, via high-sensitivity sensor and included spotlight LEDs
- ✓ Waterproof: Reliable IP66 for stable outdoor performance
- ✓ Smart Detection (human detection, motion detection, area intrusion, line-crossing, video tampering): Receive notifications and check feeds when someone crosses a boundary, enters an area you've set, or obstructs the camera
- ✓ H.265+: Without using any extra bandwidth, your cameras transmit compressed crystal-clear video to save disk space, ease network loads, and reduce monitoring costs without sacrificing image quality
- ✓ PoE/12V DC: Two power supply ways not only give you more convenience but also make your wiring remarkably easy
- ✓ VIGI App: Manage your security from the palm of your hand with the VIGI app
















## Aprašymas

**All The Colors,**
**All The Time**
4MP Outdoor Full-Color Bullet Camera

## Outdoor PoE Connection, Simple Wiring

Just connect your camera via an RJ45 cable, then power supply and data transmission are all settled. Waterproof hardware protect stable performance in outdoor scenarios.

## Clarity and Colors, All in One

Monitor 24-hour clear and colorful details even in pitch dark night. VIGI’s Full-Color camera provides maximum 4MP resolutions and ensures colorful monitoring with its large-aperture lens, high-sensitivity sensor, and attached supplemental lights.

**We keep an eye on your business.**
**Smart Detection**
Receive notifications and check feeds when someone crosses a boundary, enters an area you've set, or obstructs the camera.

## Motion Detection

Get instant notifications when your camera detects motion.

## Area Intrusion

Set customized activity zones around key areas for more focused monitoring.

## Line-Crossing

Set a boundary and receive an alert anytime a person crosses it from either or both directions.

## Camera Tampering

Receive alerts when someone obstructs the camera.

**Active Defense**
Warn potential intruders instantly with sound and light when abnormal events

**Every Event is Under Your Control.**
VIGI camera intelligently detect activities, inform you instantly and response automatically by smart detection and two-way audio.

**Never miss a detail.**
SmartVid-Smart Video Enhancement

## Smart IR

Keeps objects from being under-rendered when far away or overexposed when close to camera at night.

## Wide Dynamic Range

Adjusts for lighting contrast to minimize shadowing effects and renders images true to life.

## 3D DNR

Removes abnormal pixelation to provide clearer video and eliminate distortion.

**More compression. More savings. Same quality.**
Without using any extra bandwidth, your cameras transmit compressed crystal-clear video to save disk space, ease network loads, and reduce monitoring costs without sacrificing image quality.

## Flexible Management and Storage

Take full control over your security via four management methods: the web UI, NVR UI, VIGI app, and VIGI Security Manger. Local storage is available for each method, as well as on-board storage with SD card slot (up to 256 GB).

**Discover the best way to power your camera.**
**PoE/12V DC**
Two power supply ways not only give you more convenience but also make your wiring remarkably easy.

## Flexible Installation

Find the perfect vantage point by simply securing your camera to ceiling, pole or wall.

**One system. Full security.**
**Run your business with peace of mind.**
The VIGI professional surveillance system by TP-Link is dedicated to protecting the business you've worked hard to build — whenever, wherever. Our outstanding functions, reliable quality guarantees, and simplified installation work together to ensure your business stays safe and sound.

### Techninė specifikacija

| | |
|---|---|
| **Performance** | |
| Type | IP security camera |
| Placement supported | Outdoor |
| Connectivity technology | Wired |
| Day/night mode | Yes |
| **Design** | |
| Mounting type | Ceiling/Wall/Pole |
| Product colour | Black, White |
| Form factor | Bullet |
| LED indicators | Yes |
| Housing material | Plastic |
| International Protection (IP) code | IP66 |
| **Camera** | |
| Minimum illumination | 0.005 lx |
| Lens viewing angle, horizontal | 102° |
| Lens viewing angle, vertical | 55° |
| Lens viewing angle, diagonal | 122° |
| Tilt angle range | -90 - 90° |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

| | |
|---|---|
| Pan range | -90 - 90° |
| Camera shutter speed | 1/3 - 1/10000 s |
| Number of Privacy masking areas | 4 |
| **Image sensor** | |
| Sensor type | CMOS |
| Number of sensors | 1 |
| Optical sensor size | 25.4 / 3 mm (1 / 3") |
| Progressive scan | Yes |
| **Lens system** | |
| Number of lenses | 1 |
| Detect distance | 64 m |
| Observe distance | 27 m |
| Recognize distance | 13 m |
| Maximum aperture number | 1.6 |
| Identify distance | 6 m |
| Fixed focal length | 2.8 mm |
| **Night vision** | |
| Night vision | Yes |
| Night vision distance | 30 m |
| LED type | IR |
| Number of illumination LEDs | 2 |
| Infra-red wavelength | 850 nm |
| **Video** | |
| Maximum resolution | 2560 x 1440 pixels |
| Total megapixels | 4 MP |
| Video formats supported | H.264, H.264+, H.265, H.265+ |
| Video compression formats | H.264, H.264+, H.265, H.265+ |
| Supported graphics resolutions | 1280 x 720 (HD 720), 1920 x 1080 (HD 1080), 2048 x 1280, 2304 x 1296, 2560 x 1440 |
| Frame rate | 30 fps |
| Image quality adjustment | Brightness, Contrast, Mirror, Saturation |
| Privacy masking | Yes |
| Bit rate control | Constant Bit Rate (CBR)/Variable Bit Rate (VBR) |
| Bit rate | 256 Kbps - 4 Mbps |
| Back Light Compensation (BLC) | Yes |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

| | |
|---|---|
| Highlight Compensation (HLC) | Yes |
| Digital Wide Dynamic Range (DWDR) | Yes |
| Region of Interest (ROI) encoding | Yes |
| Smart IR | Yes |
| 3D positioning | Yes |
| **Audio** | |
| Built-in speaker(s) | Yes |
| Audio system | 2-way |
| Audio input channels | 1.0 channels |
| Audio output channels | 1.0 channels |
| Sample rate | 8 kHz |
| Signal-to-Noise Ratio (SNR) | 52 dB |
| Built-in microphone | Yes |
| Bit rate range | 0 - 64 Kbit/s |
| **Network** | |
| Ethernet LAN | Yes |
| Wi-Fi | No |
| Bluetooth | No |
| Ethernet interface type | Fast Ethernet |
| Networking standards | IEEE 802.3af, IEEE 802.3at |
| Supported network protocols | TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, DNS, RTSP, NTP, UPnP UDP, SSL/TLS |
| Live view | Yes |
| Number of simultaneous live view channels | 3 channels |
| **Storage** | |
| Built-in HDD | No |
| Card reader integrated | Yes |
| Compatible memory cards | MicroSD (TransFlash) |
| Maximum memory card size | 256 GB |
| **Ports & interfaces** | |
| Ethernet LAN (RJ-45) ports | 1 |
| DC-in jack | Yes |
| **Security** | |
| Password protection | Yes |
| Video motion detection | Yes |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

| | |
|---|---|
| IP address filtering | Yes |
| HTTPS encryption | Yes |
| Automatic Network Replenishment (ANR) | Yes |
| Network access storage (NAS) | Yes |
| **Management features** | |
| Web browser | Yes |
| Reset button | Yes |
| **Power** | |
| Power source type | DC, PoE |
| Power consumption (typical) | 3.4 W |
| Power consumption (max) | 7 W |
| DC output voltage | 12 |
| **Operational conditions** | |
| Operating temperature (T-T) | -30 - 60 °C |
| Storage temperature (T-T) | -40 - 60 °C |
| Operating relative humidity (H-H) | 0 - 95% |
| Storage relative humidity (H-H) | 0 - 95% |
| **Weight & dimensions** | |
| Width | 174 mm |
| Height | 70 mm |
| Length | 78 mm |
| Weight | 280 g |
| **Packaging data** | |
| Package width | 128 mm |
| Package depth | 218 mm |
| Package height | 103 mm |
| Package weight | 424 g |
| Package type | Box |
| **Sustainability** | |
| Compliance certificates | BSMI, CE, KC |
| Sustainability compliance | Yes |
| **Packaging content** | |
| Number of cameras | 1 |
| Mounting kit | Yes |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

| | |
|---|---|
| Manual | Yes |
| **Matmenys ir svoris** | |
| Matmenys (I × P × A) | 10.00cm × 22.00cm × 13.00cm |
| Svoris | 0.46kg |

## Dokumentai ir vaizdo įrašai

- User manual
- Quick start guide
- Product leaflet

## Gamintojo ir saugos informacija

MANUFACTURER

**TP-Link**

EU RESPONSIBLE PERSON

**TP-Link Deutschland GmbH**
Niederkasseler Lohweg 175, 40547 Düsseldorf, DE
tp-link.com

DISTRIBUTOR

**MB KOMPIUTERIŲ GURU**
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt