

TP-Link VIGI C440I 4MM security camera Turret IP security camera Indoor 2560 x 1440 pixels Ceiling

Gamintojas: **TP-LINK** · Modelis: **VIGI C440I(4MM)** · EAN: **4897098689073** · Prekės kodas: **899190**



46,90 €

Kaina su PVM

Be PVM: **38,76 €**

Sandėlyje





Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ **4MP Super-High Definition:** The VIGI C440I camera comes with 4MP — more than enough pixels to pick up some of the more discrete details
- ✓ **Human & Vehicle Classification:** Distinguishes humans and vehicles from other objects, so you receive more accurate event notifications
- ✓ **Smart Detection:** Receive notifications and check feeds when someone crosses a boundary, enters an area you've set, obstructs the camera, or removes/abandons objects
- ✓ **H.265+:** Without using any extra bandwidth, your cameras transmit compressed crystal-clear video to save disk space, ease network loads, and reduce monitoring costs without sacrificing image quality
- ✓ **Smart Video Enhancement:** VIGI's professional technologies process videos to greatly improve their quality that is vital to your monitoring, including Smart IR, WDR, 3D DNR, and Night Vision
- ✓ **Corridor Mode:** Allows you to change the image aspect ratio from 16:9 to 9:16, and helps to monitor long and narrow areas
- ✓ **12V DC/PoE:** Two types of power supply not only give you more convenience but also make your wiring remarkably easy
- ✓ **2.8/4 mm Lens:** Whether you need a wide-angle lens to cover enclosed spaces or a higher millimeter lens for longer distances in open spaces, C440I comes with two different lens types to better suit your security needs
- ✓ **Flexible Management:** Take full control over your security via four management methods: the web UI, NVR UI, VIGI app, and VIGI Security Manager





Aprašymas

Security Never

Shuts Down

4MP IR Turret Network Camera

Looking for a higher resolution? It's right here.

4MP Super-High Definition

The VIGI C440I camera comes with 4MP—more than enough pixels to pick up some of the more discrete details.

Human & Vehicle Classification

Integrated AI chips support advanced algorithms to distinguish humans and vehicles from other objects. You can flexibly customize alarm rules to match your monitoring needs and receive more accurate event notifications.

We keep an eye on your business.

Smart Detection

Backed by AI algorithms, the VIGI camera offers more smart detection. You will receive notifications when someone crosses a boundary, enters an area you've set, obstructs the camera, or removes/abandons objects.

Never miss a detail.

SmartVid-Smart Video Enhancement

VIGI's professional technologies process videos to greatly improve their quality that is vital to your monitoring, including Smart IR, WDR, 3D DNR, and Night Vision.

More compression. More savings. Same quality.

Without using any extra bandwidth, your cameras transmit compressed crystal-clear video to save disk space, ease network loads, and reduce monitoring costs without sacrificing image quality.

Corridor Mode

Rotate the live image and lens 90° clockwise simultaneously. This way, your image aspect ratio changes from 16:9 to 9:16, helping you monitor long and narrow areas and providing a more natural viewing experience.

Discover the best way to power your camera.

PoE/12V DC

Two power supply ways not only give you more convenience but also make your wiring remarkably easy.

Choose the right lens for your security.

2.8/4 mm Lens

Whether you need a wide angle lens to cover enclosed spaces like elevators or a higher millimeter lens for longer distances in open spaces like

parking lots, C440I comes with two different lens versions to better suit your security needs.

Flexible Installation

Easily route your camera's cable into a dropped ceiling or avoid drilling by slotting it through the camera's side outlet

Flexible Management

Take full control over your security via four management methods: the web UI, NVR UI, VIGI app, and VIGI Security Manager.

One system. Full security.

Run your business with peace of mind.

The VIGI professional surveillance system by TP-Link is dedicated to protecting the business you've worked hard to build — whenever, wherever. Our outstanding functions, reliable quality guarantees, and simplified installation work together to ensure your business stays safe and sound.

Techninė specifikacija

Performance	
Type	IP security camera
Placement supported	Indoor
Connectivity technology	Wired
Wide Dynamic Range (WDR)	Yes
Day/night mode	Yes
Infrared (IR) cut-off filter	Yes
Design	
Mounting type	Ceiling
Product colour	White
Form factor	Turret
Housing material	Plastic
Camera	
Minimum illumination	0.1 lx
Lens viewing angle, horizontal	75.1°
Lens viewing angle, vertical	41.5°
Lens viewing angle, diagonal	88.7°
Image sensor	
Sensor type	CMOS
Optical sensor size	25.4 / 3 mm (1 / 3")
Progressive scan	Yes
Lens system	
Number of lenses	1

Maximum aperture number	2.2
Fixed focal length	4 mm
Night vision	
Night vision	Yes
Night vision distance	30 m
LED type	IR
Infra-red wavelength	850 nm
Video	
Maximum resolution	2560 x 1440 pixels
Total megapixels	4 MP
Video compression formats	H.264, H.264+, H.265, H.265+
Supported graphics resolutions	320 x 240, 352 x 288, 640 x 480 (VGA), 1280 x 720 (HD 720), 1920 x 1080 (HD 1080), 2048 x 1280, 2304 x 1296, 2560 x 1440
Supported video modes	240p, 480p, 720p, 1080p, 1280p, 1440p
Frame rate	30 fps
Video streaming	Yes
Noise reduction	Yes
Noise reduction technology	3D noise reduction
Image quality adjustment	Brightness, Contrast, DNR, Mirror, Saturation
Bit rate	64 Kbps - 4 Mbps
Back Light Compensation (BLC)	Yes
Highlight Compensation (HLC)	Yes
Digital Wide Dynamic Range (DWDR)	Yes
Region of Interest (ROI) encoding	Yes
Smart IR	Yes
3D positioning	Yes
Network	
Ethernet LAN	Yes
Wi-Fi	No
Bluetooth	No
Networking standards	IEEE 802.3af, IEEE 802.3at
Supported network protocols	TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, DNS, RTSP, NTP, UPnP UDP, SSL/TLS
Number of simultaneous live view channels	3 channels
Ports & interfaces	
Ethernet LAN (RJ-45) ports	1

Security

Password protection	Yes
Video motion detection	Yes
Active tampering alarm	Yes
IP address filtering	Yes
HTTPS encryption	Yes
Mirror	Yes
Password reset via email	Yes
Human and vehicle targets classification	Yes
Digest authentication	Yes

Management features

Behavior analysis	Intrusion detection, Line crossing detection, Object removal detection, Region entrance detection, Region exiting detection
-------------------	---

Power

Power source type	DC, PoE
Power consumption (max)	5 W
DC output voltage	12

Operational conditions

Operating temperature (T-T)	-30 - 60 °C
-----------------------------	-------------

Weight & dimensions

Width	123 mm
Depth	83 mm
Height	123 mm

Packaging data

Package width	163 mm
Package depth	163 mm
Package height	116 mm
Package weight	340 g

Sustainability

Compliance certificates	BSMI, CE
Sustainability compliance	Yes

Packaging content

Number of cameras	1
Mounting kit	Yes

Manual

Yes

Matmenys ir svoris

Matmenys (I × P × A)

12,00cm × 16,00cm × 16,00cm

Svoris

0,37kg

Dokumentai ir vaizdo įrašai

- › [Naudojimo instrukcija](#)
- › [Greitos pradžios vadovas](#)
- › [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

TP-Link

ATSAKINGAS ASMUO ES

TP-Link Deutschland GmbHNiederkasseler Lohweg 175, 40547 Düsseldorf,
DEtp-link.com

PLATINTOJAS

MB KOMPIUTERIŲ GURUV. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt