

TP-Link MC112CS network media converter 100 Mbit/s Single-mode Black

Gamintojas: **TP-LINK** · Modelis: **MC112CS** · EAN: **1210002608831** · Prekės kodas: **899205**



28,89 €

Kaina su PVM

Be PVM: **23,88 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Complies with 802.3u 10/100Base-TX, 100Base-FX standards
- ✓ Auto-negotiation of Half-Duplex / Full-Duplex transfer mode
- ✓ Adopts WDM technology, transmitting and receiving data on one single fiber
- ✓ Work with MC112CS WDM single fiber media converter
- ✓ Extends fiber distance up to 20km (12.5 miles)

Aprašymas

The MC112CS is a media converter designed to convert 100BASE-FX fiber to 10/100Base-TX copper media and vice versa. Adopting WDM technology, MC112CS takes only one fiber cable to transmit and receive data, which will save half cabling cost for you. Designed under IEEE 802.3u 100Base-TX and 100Base-FX standards, the MC112CS is designed for use with single-mode fiber cable utilizing the SC-Type connector. The MC112CS supports longwave (LX) laser specification at a full wire speed forwarding rate. It works at 1310nm on transferring data and at 1550nm on receiving data. So the other end device to cooperate with the MC112CS should work at 1550nm on transferring data and at 1310nm on receiving data. Another TP-Link's media converter MC111CS is just one of the examples to cooperate with MC112CS. Auto MDI/MDI-X for TX port, Auto negotiation of duplex mode on TX port. The MC112CS will transmit at extended fiber optic distances utilizing single-mode fiber up to 20 kilometers (12.5 miles).

Techninė specifikacija

Network	
Maximum data transfer rate	100 Mbit/s
Networking standards	IEEE 802.3, IEEE 802.3u
Ethernet LAN data rates	10,100 Mbit/s

Copper ethernet cabling technology	10BASE-TX, 100BASE-FX, 100BASE-TX
Auto MDI/MDI-X	Yes
Duplex system	Full, Half
Cable types supported	Cat3, Cat4, Cat5
Performance	
Maximum transfer distance	20000 m
Wavelength-division multiplexing (WDM)	Yes
Fiber mode structure	Single-mode
Features	
Internal	No
LED indicators	Yes
Product colour	Black
Ports & interfaces	
Fiber optic connector	SC
Connectivity technology	Wired
Ethernet LAN (RJ-45) ports	1
Fiber ports quantity	1
Power	
Power consumption (max)	2.41 W
Weight & dimensions	
Width	95 mm
Depth	73 mm
Height	27 mm
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%
Certificates	
Compliance certificates	RoHS
Logistics data	
Harmonized System (HS) code	85176990
Matmenys ir svoris	
Matmenys (I × P × A)	21,00cm × 17,00cm × 7,00cm

Svoris

0,37kg

Gamintojo ir saugos informacija

GAMINTOJAS

TP-Link

ATSAKINGAS ASMUO ES

TP-Link Deutschland GmbH

Niederkasseler Lohweg 175, 40547 Düsseldorf,

DE

[tp-link.com](https://www.tp-link.com)

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt