

TP-Link TL-SF1016 tinklo komutatorius Ne-valdomas Fast Ethernet (10/100) 1U Juoda

Gamintojas: **TP-LINK** · Modelis: **TL-SF1016** · EAN: **6935364021511** · Prekės kodas: **899239**



53,91 €

Kaina su PVM

Be PVM: **44,55 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Ne-valdomas
- ✓ Adreso lentelės dydis: 8000 įrašai Perjungimo pajėgumas: 3,2 Gbit/s
- ✓ Pagrindinių perjungimo RJ-45 eterneto prievadų skaičius: 16
- ✓ 1U Stovo montavimas
- ✓ 10BASE-T, 100BASE-TX

Aprašymas

What This Product Does

The 16-Port 10/100Mbps Rackmount Switch TL-SF1016 provides you with a high-performance, low-cost, easy-to-use, seamless and standard upgrade to improve old network to 100Mbps network. All 16 ports support auto MDI/MDIX, no need to worry about the cable type, simply plug and play. Moreover, with the innovative energy-efficient technology, the TL-SF1016 can save up to 70%* of the power consumption and 80% of the packaging material can be recycled, making it an eco-friendly solution for your business network.

TP-LINK Green Technology

This new generation The 16-Port 10/100Mbps Switch TL-SF1016 features the latest innovative energy-efficient technologies that can greatly expand your network capacity with much less power. It automatically adjusts power consumption according to the link status and cable length to limit the carbon footprint of your network. It also complies with the EU'S RoHS, prohibiting the use of certain hazardous materials. Besides, 80% of the packaging material can be recycled.

High Performance

The rack-mount size steel case design, combined with a safety-certified internal power supply, make the switch the most robust product, which is very cost-effective for a less than 16-user environment. Featuring non-blocking switching architecture, TL-SF1016 forwards and filters packets at full wire-speed for maximum throughput. And IEEE 802.3x flow control for Full Duplex mode and backpressure for Half Duplex mode alleviate the traffic congestion and make TL-SF1016 work reliably.

Easy to Use

The auto features of this fast ethernet switch make installation plug and play and hassle-free. No configuring is required. Auto MDI/MDIX eliminates the need for crossover cables. Auto-negotiation on each port senses the link speed of a network device (10, 100 Mbps) and intelligently adjusts for compatibility and optimal performance.

- Innovative energy-efficient technology saves power up to 70%

- Supports IEEE 802.3x flow control for Full Duplex mode and backpressure for Half Duplex mode
- Non-blocking switching architecture that forwards and filters packets at full wire-speed for maximum throughput
- 3.2 Gbps Switching Capacity
- Store and forward Switching scheme
- Auto-MDI/MDIX eliminates the need for crossover cables
- Supports MAC address auto-learning and auto-aging
- Auto-negotiation ports provide smart integration between 10Mbps, 100Mbps hardware.
- Plug and Play design simplifies installation
- Fanless design to make sure it works quietly

Techninė specifikacija

Valdymo funkcijos	
Perjungimo tipas	Ne-valdomas
Ryšys	
Pagrindinių perjungimo RJ-45 ethernet prievadų skaičius	16
Pagrindinių perjungimo RJ-45 ethernet prievadų tipas	Fast Ethernet (10/100)
Įdiegtų SFP modulių kiekis	0
Įdiegtų SFP+ modulių kiekis	0
Maitinimo jungtis	DC lizdas
Tinklas	
Tinklo standartai	IEEE 802.3i, IEEE 802.3u, IEEE 802.3x
10G parama	Ne
Varinių ethernet kabelių technologija	10BASE-T, 100BASE-TX
Auto MDI/MDI-X	Taip
Duomenų perdavimas	
Adreso lentelės dydis	8000 įrašai
Perjungimo pajėgumas	3,2 Gbit/s
Paketo buferio atmintis	2 MB

Konstrukcija

Stovo montavimas	Taip
Forma	1U
Produkto spalva	Juoda
LED indikatoriai	Taip

Energijos valdymas

AC įėjimo įtampa	100 - 240 V
AC įėjimo dažnis	50 - 60 Hz
Galios suvartojimas (maks.)	2,23 W

„Power over Ethernet“ (PoE)

Maitinimas per Ethernetą (PoE)	Ne
--------------------------------	----

Aplinkos sąlygos

Darbo temperatūros diapazonas (TT)	0 - 40 °C
Sandėliavimo temperatūros norma (T-T)	-40 - 70 °C
Darbo santykinės drėgmės diapazonas	10 - 90%
Sandėliavimo santykinis drėgmės diapazonas	5 - 90%

Svoris ir matmenys

Plotis	440 mm
Ilgis	180 mm
Aukštis	44 mm

Pakuotės turinys

Pridėti kabeliai	AC
Stovo montavimo rinkinys	Taip

Logistikos duomenys

Darniosios sistemos (DS) kodas	85176990
--------------------------------	----------

Matmenys ir svoris

Matmenys (I × P × A)	8,00cm × 53,00cm × 25,00cm
Svoris	2,27kg

Dokumentai ir vaizdo įrašai

- › [Naudojimo instrukcija](#)
- › [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

TP-Link

ATSAKINGAS ASMUO ES

TP-Link Deutschland GmbH

Niederkasseler Lohweg 175, 40547 Düsseldorf,
DE

tp-link.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt