

TP-Link Archer MR505 belaidis maršrutizatorius Gigabitinis eternetas Dviguba juosta (2,4 GHz / 5 GHz) 4G Balta

Gamintojas: **TP-LINK** · Modelis: **ARCHER MR505** · EAN: **8885020620078** · Prekės kodas: **899259**



93,90 €

Kaina su PVM

Be PVM: **77,60 €**

Sandėlyje






Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Stalinis / stulpinis maršrutizatorius Balta
- ✓ Dviguba juosta (2,4 GHz / 5 GHz) Wi-Fi 5 (802.11ac) 1200 Mbit/ai
- ✓ Gigabitinis eternetas
- ✓ Eterneto WAN SIM kortelės anga
- ✓ Ethernet LAN (RJ-45) portų kiekis: 3



Aprašymas

A 4G+ Router for Flexible Connections

AC1200 Dual Band Wi-Fi LTE Router

Fast 4G+ Connection Where You Need It

Simple, just one SIM card

Traditional broadband or cable installation is expensive and time-consuming for your vacation home, farm, or suburban warehouse. Long contract periods also create headaches for short-rentals, pop-up venues, and temporary shops to access the internet. Archer MR505 ensures a comfortable and no-block network installation. Plug in your SIM card and enjoy high-speed internet!

Superfast 4G+ LTE Speed for Reliable Wi-Fi

Thanks to 4G+ Carrier Aggregation technology which combines different carrier signals for even faster bandwidth, MR505 boosts 300 Mbps download speeds fulfills your devices' needs. It can also share a dual-band Wi-Fi network with speeds of 867 Mbps on 5 GHz for bandwidth-intensive tasks like HD streaming and gaming and 300 Mbps on 2.4 GHz for internet surfing, email, and social media.

Ideal for Small Business

with 64 Devices Connection Simultaneously

Easily share a 3G/4G connection with up to 64 wireless devices, such as phones, tablets, and laptops, at the same time. 3 LAN ports stand ready to provide internet for wired devices like desktop computers.

Powerful CPU

for Stable Data Processing

MU-MIMO

Serves Multiple Devices at once

Beamforming

Concentrate Signal Strength

Amplifier with External Antennas

Boost Signal Coverage

Flexibly Create Whole Home Mesh WiFi

If you have any dead zones at home, just add another EasyMesh-compatible router/range extender to further form your whole home multi-gigabit mesh WiFi. No more searching for a stable connection.

WiFi Dead Zone Killer

Eliminate weak signal areas with WiFi coverage for the whole house

Smart Roaming

Uninterrupted streaming when moving around your home

One WiFi Name

No more switching WiFi network names

Available WAN Connection Backup

With a fully functional WAN/LAN port, Archer MR505 can work as a router that is compatible with cable, fiber, and DSL modems, or provide internet for wired devices. The reliable access is for up to 64 devices Simultaneously.

Easy Setup and Use

Set up the Archer MR505 in minutes thanks to its intuitive web interface and the powerful Tether app. Manage network settings, including Parental Controls and Access Control, from any Android or iOS device. Tether also provides Automatic Firmware Updates to always give your network the latest performance and security.

Techninė specifikacija

WAN jungtis

Eterneto WAN	Taip
SIM kortelės anga	Taip

Belaidžio interneto funkcijos

„Wi-Fi“ dažnių juosta	Dviguba juosta (2,4 GHz / 5 GHz)
„Wi-Fi“ standartas	Wi-Fi 5 (802.11ac)
WLAN duomenų perdavimo sparta (maks.)	1200 Mbit/ai
Wi-Fi standartai	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)
WLAN duomenų perdavimo sparta (pirmoji juosta)	300 Mbit/ai
WLAN duomenų perdavimo sparta (antroji juosta)	867 Mbit/ai

Tinklas

Ethernet LAN jungtis	Taip
Eterneto LAN sąsajos tipas	Gigabitinis ethernetas
Eterneto LAN duomenų perdavimo norma	10,100,1000 Mbit/ai
Kabelių technologija	10/100/1000Base-T(X)
Dinaminis DNS (DDNS)	Taip
Statinis maršrutas	Taip
Svečių tinklų (2,4 GHz) skaičius	1
Svečių tinklų (5 GHz) skaičius	1
VPN serveris	Y

Mobilusis ryšys

Mobiliojo tinklo generavimas	4G
3G standartai	DC-HSPA+, HSPA+, UMTS
4G standartai	LTE-TDD & LTE-FDD
Palaikomi 4G dažniai	700,800,850,900,1800,2100,2300,2500,2600 MHz
Palaikomi 3G dažniai	850,900,2100 MHz

Ryšys

Ethernet LAN (RJ-45) portų kiekis	3
USB prievadas	Ne
DC įėjimo lizdas	Taip

Saugumas

Apsaugos algoritmų palaikymas	64-bit WEP, 128-bit WEP, WPA, WPA3
Parental kontrolė	Taip

Protokolai

DHCP klientas	Taip
DHCP serveris	Taip

Konstrukcija

Gaminio tipas	Stalinis / stulpinis maršrutizatorius
Produkto spalva	Balta
Indikacijos šviesa	Taip

Pakuotės turinys

Kintamosios srovės adapteris	Taip
Greitos pradžios vadovas	Taip

Antena

Antenos konstrukcija	Vidinis
Antenų kiekis	2
Nuimama antena	Taip

Energijos valdymas

Maitinimo šaltinio tipas	DC
Išėjimo įtampa	12 V
Išėjimo srovė	1,5 A

Aplinkos sąlygos

Darbo temperatūros diapazonas (TT)	0 - 40 °C
Darbo santykinės drėgmės diapazonas	10 - 90%
Sandėliavimo santykinis drėgmės diapazonas	5 - 90%

Svoris ir matmenys

Plotis	212 mm
Ilgis	157,5 mm
Aukštis	57 mm

Pakuotės duomenys

Pakuotės tipas	„Box“
----------------	-------

Matmenys ir svoris

Matmenys (I × P × A)	31,00cm × 23,00cm × 9,00cm
Svoris	0,94kg

Dokumentai ir vaizdo įrašai[› Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

TP-Link

ATSAKINGAS ASMUO ES

TP-Link Deutschland GmbH

Niederkasseler Lohweg 175, 40547 Düsseldorf,
DE

tp-link.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt