

TP-Link TL-WR840N belaidis maršrutizatorius Greitas eternetas Viena juosta (2,4 GHz) Pilka, Balta

Gamintojas: **TP-LINK** · Modelis: **TL-WR840N** · EAN: **6935364070533** · Prekės kodas: **899261**



16,90 €

Kaina su PVM

Be PVM: **13,97 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Stalinis maršrutizatorius Pilka, Balta
- ✓ Viena juosta (2,4 GHz) Wi-Fi 4 (802.11n) 300 Mbit/ai
- ✓ Greitas eternetas
- ✓ Eterneto WAN
- ✓ Ethernet LAN (RJ-45) portų kiekis: 4
- ✓ Web pagrįstas valdymas Paslaugos kokybės (QoS) palaikymas



Aprašymas

Highlights:

- 300Mbps wireless transmission rate ideal for both bandwidth sensitive tasks and basic work;
- Easy wireless security encryption at a push of WPS button;
- IP based bandwidth control allows administrators to determine how much bandwidth is allotted to each PC;
- WDS wireless bridge provides seamless bridging to expand your wireless network.

What This Product Does

The 300Mbps Wireless N Router TL-WR840N is a combined wired/wireless network connection device designed specifically for small business and home office networking requirements. The TL-WR840N creates an exceptional and advanced wireless performance, making it ideal for streaming HD

video, VoIP and online gaming. Also, Wi-Fi Protected Setup (WPS) button on the sleek and fashionable exterior ensures WPA2 encryptions, preventing the network from outside intrusions.

300Mbps Wireless N Speed - Fast Download Speed

TP-LINK's TL-WR840N is a high speed solution that is compatible with IEEE 802.11b/g/n. Based on 802.11n technology, TL-WR840N gives users wireless performance at up to 300Mbps, which can meet your most demanding home networking needs, such as HD streaming, online gaming and large files downloading.

CCA Technology - Stable Wireless Signals

Clear Channel Assessment (CCA) automatically avoids channel conflicts using its clear channel selection feature and fully realizes the advantages of channel binding, greatly enhancing wireless performance.

IP QoS -- Manage your Bandwidth

Within the wireless network, indiscriminate Internet surfing and bandwidth-guzzling downloads by internal users often leave homes or small offices with insufficient bandwidth. TL-WR840N supports an IP QoS function, allowing optimum utilization of bandwidth and offering bandwidth control over congestion, preventing bandwidth abuse. In this way, users of a small network receive committed and specific bandwidth, preventing non-critical applications from degrading network performance.

Easy To Use

With the TL-WR840N even novice users can setup their networks. The device comes with a CD featuring an Easy Setup Assistant that leads users through the setup process step-by-step, and even helps with wireless network settings and security configurations.

Features:

- Wireless N speed of up to 300Mbps makes it ideal for bandwidth consuming or interruption sensitive applications like video streaming, online gaming and VoIP;
- 2T2R MIMO™ delivers greater throughput at range versus conventional 1T1R;
- Easily setup a WPA encrypted secure connection at a push of the QSS button;
- WDS wireless bridge provides seamless bridging to expand your wireless network;
- QoS function assures the quality of VoIP and multimedia streaming;
- Wi-Fi On/Off Button allows users to simply turn their wireless radio on or off;
- Features parental control function managing the internet access of children or employee's computer;
- Supports virtual server, special application and DMZ host ideal for creating a website within your LAN;
- Offers Auto-mail function for system log, convenient for managing the router;
- Backward compatible with 802.11b/g products;
- Easy Setup Assistant provides quick & hassle free installation;
- Sleek exterior, can be mounted on a wall or placed horizontally on a table or desk.

Techninė specifikacija

WAN jungtis	
Eterneto WAN	Taip
DSL WAN	Ne
SIM kortelės anga	Ne
3G/4G USB modemo suderinamumas	Ne
WAN tinklo prisijungimo tipas	RJ-45

Belaidžio interneto funkcijos

„Wi-Fi“ dažnių juosta	Viena juosta (2,4 GHz)
„Wi-Fi“ standartas	Wi-Fi 4 (802.11n)
WLAN duomenų perdavimo sparta (maks.)	300 Mbit/ai
Wi-Fi standartai	802.11b, 802.11g, Wi-Fi 4 (802.11n)

Tinklas

Ethernet LAN jungtis	Taip
Eterneto LAN sąsajos tipas	Greitas eternetas
Eterneto LAN duomenų perdavimo norma	10,100 Mbit/ai
Kabelių technologija	10/100Base-T(X)
Tinklo standartai	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.3, IEEE 802.3u
Portų ekspedijavimas	Taip
Prievado suaktyvinimas	Taip
Svečių tinklų (2,4 GHz) skaičius	1
VPN palaikymas	PPTP, L2TP, IPSec
Imtuvo jautrumas	270M: -68dBm@10% PER 130M: -68dBm@10% PER 108M: -68dBm@10% PER 54M: -68dBm@10% PER 11M: -85dBm@8% PER 6M: -88dBm@10% PER 1M: -90dBm@8% PER

Ryšys

Ethernet LAN (RJ-45) portų kiekis	4
USB prievadas	Ne
DC įėjimo lizdas	Taip

Valdymo funkcijos

Web pagrįstas valdymas	Taip
Paslaugos kokybės (QoS) palaikymas	Taip
Atstatymo mygtukas	Taip
WPS paspaudžiamasis mygtukas	Taip

Saugumas

Apsaugos algoritmų palaikymas	WEP, WPA, WPA-Enterprise, WPA2, WPA2-Enterprise
Ugniasienė	Taip
Firewall apsauga	SPI
Svečių prieiga	Taip
Filtravimas	Taip
MAC adresų filtravimas	Taip
URL filtravimas	Taip
DMZ palaikymas	Taip

Protokolai

DHCP klientas	Taip
DHCP serveris	Taip
Universali „Plug and Play“ jungtis (UPnP)	Taip
Palaikomi tinklo protokolai	IPv4, IPv6

Konstrukcija

Gaminio tipas	Stalinis maršrutizatorius
Produkto spalva	Pilka, Balta
LED indikatoriai	Taip
On/off mygtukas	Taip

Sertifikatai

Atitikties sertifikatai	RoHS, Federalinė ryšių komisija (FCC), CE
-------------------------	---

Pakuotės turinys

Pridėti kabeliai	LAN (RJ-45)
Kintamosios srovės adapteris	Taip
Greito diegimo vadovas	Taip

Antena

Antenos konstrukcija	Išorinis
Antenos stiprinimo lygis (max)	5 dBi
Antenų kiekis	2

Savybės

Integruotas procesorius	Taip
Procesoriaus branduoliai	1

Energijos valdymas

Maitinimo šaltinio tipas	DC
Išėjimo įtampa	9 V
Išėjimo srovė	0,6 A

Aplinkos sąlygos

Darbo temperatūros diapazonas (TT)	0 - 40 °C
Sandėliavimo temperatūros norma (T-T)	-40 - 70 °C
Darbo santykinės drėgmės diapazonas	10 - 90%
Sandėliavimo santykinis drėgmės diapazonas	5 - 90%

Sistemos reikalavimai

Palaikomos „Windows“ operacinės sistemos

Windows 2000, Windows 2000 Professional, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64

Palaikoma operacinė sistema „Linux“

Taip

Palaikomos MAC operacinės sistemos

Taip

Svoris ir matmenys

Plotis182 mm

Ilgis128 mm

Aukštis35 mm

Pakuotės duomenys

Pakuotės plotis265 mm

Pakuotės gylis180 mm

Pakuotės aukštis86 mm

Paketo svoris430 g

Kitos savybės

WLAN duomenų perdavimo grečio palaikymas11,54,300 Mbit/ai

Tvarumas

Tvarumo reikalavimų laikymasisTaip

Matmenys ir svoris

Matmenys (I × P × A)9,00cm × 27,00cm × 18,00cm

Svoris0,48kg

Gamintojo ir saugos informacija

GAMINTOJAS

TP-Link

ATSAKINGAS ASMUO ES

TP-Link Deutschland GmbHNiederkasseler Lohweg 175, 40547 Düsseldorf,
DEtp-link.com

PLATINTOJAS

MB KOMPIUTERIŲ GURUV. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt