

ASUS Hyper M.2 x16 Gen 4 interface cards/adapter Internal

Gamintojas: **ASUS** · Modelis: **90MC08A0-M0EAY0** · EAN: **4718017624923** · Prekės kodas: **902299**



67,91 € ~~69,90 €~~

Kaina su PVM

Be PVM: **56,12 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Two-phase power solution with up to 14-watt output supports the latest NVMe drives
- ✓ Large heatsink and active fan reduces M.2 SSD temperatures for unthrottled transfer speeds and enhanced reliability
- ✓ Adapted server-grade PCB supports up to four PCIe 4.0/3.0 M.2 drives, with up to 256 Gbps bandwidth for smooth data transfers
- ✓ Compatible with AMD TRX40/X570 PCIe 4.0 for NVMe RAID and supports Intel® platform RAID-on-CPU functions
- ✓ Also support other vendors' motherboards via PCIe bifurcation in BIOS setting



Aprašymas

ASUS Hyper M.2 x16 Gen 4 Card (PCIe 4.0/3.0) supports four NVMe M.2 (2242/2260/2280/22110) devices up to 256 Gbps for AMD TRX40/X570 PCIe 4.0 NVMe RAID and Intel platform RAID-on-CPU functions

RAID on CPU

The ASUS Hyper M.2 x16 Gen 4 Card is compatible with the Intel X299, Z390, Z370 and future platforms' RAID-on-CPU function, and supports PCIe 4.0 NVMe RAID on the AMD TRX40 and X570 platforms. Unused CPU PCIe lanes can be assigned to storage, allowing you to create a bootable RAID array with up to four M.2 SSDs.

One card, 8X the bandwidth

The ASUS Hyper M.2 x16 Gen 4 Card uses PCIe 4.0, which doubles the bandwidth per lane compared to PCIe 3.0. With four M.2 slots, it offers up to 256 Gbps of bandwidth per card, 8X the bandwidth of a single PCIe 3.0 drive.

Design for unthrottled transfer speed

The ASUS Hyper M.2 x16 Gen 4 Card has four M.2 slots — supporting both PCIe 3.0 and 4.0 — that allow you to expand your system with high-performance SSD storage. Designed for the latest generation of NVMe drives, the card features an upgraded power supply that provides up to 14W of power per drive, as well as a large heatsink and active fan to ensure that drives stay cool for optimum performance.

Techninė specifikacija

Ports & interfaces	
Host interface	PCIe
Output interface	M.2
Expansion card standard	PCIe 4.0
Design	
Internal	Yes
Product colour	Silver
Purpose	PC
Cooling type	Active
Number of fans	1 fan(s)
Number of expansion slots	4
LED indicators	Access
Easy to install	Yes
Features	
Data transfer rate (max)	256 Gbit/s
Weight & dimensions	
Width	270 mm
Depth	122 mm
Height	15 mm
Packaging data	
Quantity	1
Package type	Box
Logistics data	
Harmonized System (HS) code	84733020
Matmenys ir svoris	

Matmenys (I × P × A)	33,00cm × 27,00cm × 5,00cm
----------------------	----------------------------

Svoris	0,91kg
--------	--------

Dokumentai ir vaizdo įrašai

› [Naudojimo instrukcija](#)

Gamintojo ir saugos informacija

GAMINTOJAS

ASUSTeK Computer Inc

Li-Te Road 15, 112 Taipei, TW

[asus.com](https://www.asus.com)

ATSAKINGAS ASMUO ES

ASUS France S.A.R.L.

Allee bienvenue 10, 93160 Paris, FR

channel.asus.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt