

ASUS Hyper M.2 x16 Gen5 Card sąsajos plokštė / adapteris Vidinis

Gamintojas: **ASUS** · Modelis: **90MC0CY0-M0EAY0** · EAN: **4711387353288** · Prekės kodas: **902341**



89,90 €

Kaina su PVM

Be PVM: **74,30 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Vidinis
- ✓ Priimančioji sąsaja: PCIe
- ✓ Išvesties sąsaja: M.2
- ✓ NVMe
- ✓ Paskirtis: PC
- ✓ 512 Gbit/s
- ✓ Juoda



Aprašymas

ASUS Hyper M.2 x16 Gen5 Card (PCIe 5.0/4.0) supports up to four NVMe M.2 (2242/2260/2280/22110) devices at up to 512 Gbps for RAID functions across diverse CPU platforms

Support RAID Function

The ASUS Hyper M.2 x16 Gen5 Card is able to support RAID functions across different CPU platforms. For ultimate flexibility , unused CPU PCIe lanes can be assigned to storage to create a bootable RAID array with up to four M.2 SSDs*.

One Card, 8X The Bandwidth

The ASUS Hyper M.2 x16 Gen5 Card uses PCIe 5.0, which offers twice the bandwidth per lane compared to PCIe 4.0. With four M.2 slots, it enables up to 512 Gbps of bandwidth per card — 8X the bandwidth of a single PCIe 4.0 drive.

Enhanced Cooling

The ASUS Hyper M.2 x16 Gen5 Card not only enhances hardware but also incorporates advanced software solutions for efficient thermal management, effectively dissipating heat to keep SSDs at optimal temperature for unwavering performance.

A full-cover heatsink that attaches to the M.2 SSD and features air duct and blower-style fan. Plus, the four M.2 slots are supported by top and bottom thermal pads to reduce temperature-induced throttling during heavy, sustained data transfers.

The integrated blower-style active fan easily connects to the motherboard chassis fan header, allowing users to adjust fan speed in ASUS Fan Xpert 4.

Designed For Unthrottled Transfer Speeds

The ASUS Hyper M.2 x16 Gen5 Card has four M.2 slots — supporting both PCIe 5.0 and 4.0 — that allow users to supplement entire Designed for latest-generation NVMe drives, the card features a stable power supply that provides up to 14 watts of power per drive. The card also supports RAID functions across four M.2 slots ,providing up to 128 GT/s bandwidth per M.2 slot.

Techninė specifikacija

Ryšys	
Priimančioji sąsaja	PCIe
Išvesties sąsaja	M.2
Išplėtimo kortelės standartas	PCIe 5.0
NVMe	Taip
Konstrukcija	
Vidinis	Taip
Produkto spalva	Juoda
Paskirtis	PC
Aušinimo tipas	Aktyvus
Ventiliatorių skaičius	1 ventiliatorius(iai / ių)
Plėtimosi angų skaičius	4
LED indikatoriai	Access
Lengvas instaliavimas	Taip
Savybės	
Duomenų perdavimo sparta (maks.)	512 Gbit/s

Svoris ir matmenys

Plotis	290 mm
Ilgis	122 mm
Aukštis	15 mm

Pakuotės duomenys

Kiekis pakuotėje	1 vnt
------------------	-------

Matmenys ir svoris

Matmenys (l × P × A)	33,00cm × 27,00cm × 5,00cm
Svoris	0,85kg

Dokumentai ir vaizdo įrašai

- › [Naudojimo instrukcija](#)
- › [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

ASUSTeK Computer Inc
Li-Te Road 15, 112 Taipei, TW
[asus.com](https://www.asus.com)

ATSAKINGAS ASMUO ES

ASUS France S.A.R.L.
Allee bienvenue 10, 93160 Paris, FR
channel.asus.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt