

APC AP7821B maitinimo paskirstymo įrenginys 8 AC išvestis(ys / čių) 0U/1U Juoda

Gamintojas: **APC** · Modelis: **AP7821B** · EAN: **731304331513** · Prekės kodas: **902712**



748,91 €

Kaina su PVM

Be PVM: **618,93 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Išmatuotas 0U/1U Juoda
- ✓ 3680 W
- ✓ 8 AC išvestis(ys / čių) C13 šakotuvais



Aprašymas

Marketing Features

Wide range of input and output connections

Product family includes a variety of input and output connections to distribute 120V, 208V, or 230V power to multiple outlets. Having a variety of inputs and outputs allow users to adapt to varying power requirements. APC offers units that bring up to 14.4kW using a single branch whip.

Alarm Thresholds

Define alarm thresholds in order to avoid overloaded circuits. Network and visual alarms inform the user of possible problems.

Load indicator LED

Indicates overload and warning conditions based on the user-defined alarm thresholds. Alerts users of potential overloaded circuits.

Local Current Monitoring Display

The aggregate current draw per power distribution unit is displayed on the unit via a digital display. The local digital display helps installers avoid overloaded circuits by providing a visible warning when the current draw is close to the maximum amperage draw of the strip.

Local and web-based monitoring

Status available to customers both in the data center and remotely.

Availability

Alarm Thresholds

Define alarm thresholds in order to avoid overloaded circuits. Network and visual alarms inform the user of possible problems. (Note: Only available on units with the current monitoring capabilities. Please see SKU specifications for availability)

Local Current Monitoring Display

The aggregate current draw per rack PDU is displayed on the unit via a digital display. The local digital display helps installers avoid overloaded circuits by providing a visible warning when the current draw is close to the maximum amperage draw of the strip. (Available on designated SKUs only)

Integrates with StruxureWare Data Center Expert

An IT-ready, scalable access monitoring system that collects, organizes, and distributes critical alerts, surveillance video and key information, providing a unified view of complex physical infrastructure environments from anywhere on the network.

Load indicator LED

Indicates overload and warning conditions based on the user-defined alarm thresholds. Alerts users of potential overloaded circuits.

Flash Upgradeable

Quickly and easily upgrade firmware via network download for future product enhancements. Eliminates the need to replace products already installed in the field when new features are released. (Note: Networked units only)

Remote Management Capabilities

Full-featured network management interfaces that provide standards-based management via Web, SNMP, and Telnet. Allows users to access, configure, and manage units from remote locations to save valuable time. Associated with this feature is the ability to quickly and easily upgrade the firmware via network download to installed units for future product enhancements.

Agility

Rack-Mountable

Includes horizontal, vertical, and toolless-mount varieties. Puts power where it is needed most - in the racks near the equipment.

Single input power source

Supply power from one branch whip to multiple pieces of equipment, conveniently powering rack-mount equipment. Saves time and money during installation by using one branch whip and standard connections.

Wide range of input and output connections

Product family includes a variety of input and output connections to distribute 120V, 208V, or 230V power to multiple outlets. Having a variety of inputs and outputs allow users to adapt to varying power requirements. APC offers units that bring up to 14.4kW using a single branch whip.

Techninė specifikacija

Design	
PDU types	Metered
Rack capacity	0U/1U
Mounting	Horizontal/Vertical
Product colour	Black
Ports & interfaces	
AC outlets quantity	8 AC outlet(s)
AC outlet types	C13 coupler
Power plug	C20 coupler
Input connection type	IEC-320 C20
Features	
LED indicators	Yes
Management features	
Monitoring	Current, Power, Voltage
Power	
Nominal input voltage	200-230 V
Maximum current	20 A
AC input frequency	50 - 60 Hz
Output voltage	230 V
Load capacity	3680 VA
Maximum input current per phase	16 A
Maximum total current draw per phase	16 A
Maximum power	3680 W
Certificates	
Compliance certificates	RoHS
Certification	cUL, C-tick, CE, CSA, FCC 15 A, GOST, ICES-003, UL 60950, UL Listed, VCCI, VDE
Operational conditions	

Operating temperature (T-T)	-5 - 45 °C
Storage temperature (T-T)	-25 - 65 °C
Operating relative humidity (H-H)	5 - 95%
Storage relative humidity (H-H)	5 - 95%
Operating altitude	0 - 3000 m
Non-operating altitude	0 - 15000 m

Weight & dimensions

Width	444 mm
Depth	102 mm
Height	44 mm
Weight	1.74 kg

Packaging content

Packaging content	Cord Retention Bracket(s), Installation Guide, Rack Mounting Brackets, User Manual
-------------------	--

Packaging data

Package weight	2.92 kg
Package width	470 mm
Package depth	337 mm
Package height	64 mm

Matmenys ir svoris

Matmenys (I × P × A)	49,00cm × 35,00cm × 8,00cm
Svoris	3,53kg

Dokumentai ir vaizdo įrašai

› [Naudojimo instrukcija](#)

Gamintojo ir saugos informacija

GAMINTOJAS

Schneider Electric SE

rue Joseph Monier 35, 92500 RUEIL MALMAISON, FR

se.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt