

StarTech.com HDMI Extender Over CAT5e/CAT6, 4K 60Hz, Up to 200ft (60m), Transmitter and Receiver Kit, Power Over Cable, Compact Form Factor

Gamintojas: **STARTECH** · Modelis: **4K50IC-EXTEND-HDMI** · EAN: **065030918299** · Prekės kodas: **902875**



166,90 €

Kaina su PVM

Be PVM: **137,93 €**

[Sandėlyje](#)



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ **HDMI OVER ETHERNET CABLING:** HDMI Extender transmits visually lossless and low latency 4K 60Hz video and 7.1ch audio up to 200ft (60m) over a single network cable; HDMI 2.0 compliant extender supports HDR, HDCP 2.2, DTS, & Dolby Digital audio
- ✓ **POWER-OVER-CABLE:** Extend HDMI signals to areas that have limited power outlets using Power-over-Cable (PoC); Included power adapter connects to the HDMI Extender Kit's transmitter while the HDMI receiver is powered over the CAT5e/6 cable
- ✓ **NO DRIVERS OR SOFTWARE:** Point-to-Point connection uses a single CAT6/5e cable and requires no drivers/software or IP configuration, reducing setup time; Works w/any operating system (Windows/macOS/ChromeOS) and hardware platform (Intel/AMD/Apple Silicon)
- ✓ **VERSATILE MOUNTING OPTIONS:** Mount the HDMI extender on a wall, ceiling, or beneath a table using the included mounting brackets; Compact form factor allows for installation in tight spaces
- ✓ **APPLICATIONS:** HDMI extender offers a longer range than HDMI cables, and Ethernet cables are easier to run in walls, behind furniture, or through cable trays; Compact form factor makes it ideal for boardrooms, digital signage, trade shows, and classrooms





Aprašymas

Extend a 4K 60Hz HDMI signal over CAT6/6A cabling for distances of up to 200ft (60m) with Power over Cable

The HDMI Extender is designed to transmit visually lossless and low latency 4K 60Hz video and 7.1 channel audio up to 200 feet (60 meters) over a single network cable.

4K 60Hz Resolution

This HDMI over CAT5e extender is HDMI 2.0 compliant and supports up to 4K 60Hz resolutions, HDR, HDCP 2.2, DTS, and Dolby Digital audio. This makes it suitable for high-quality video and audio transmission over long distances.

Power-Over-Cable

The extender features Power-over-Cable (PoC) technology, allowing the included power adapter to connect only to the transmitter while providing power to both the transmitter and receiver through the CAT5e/6 cable. This feature reduces the need for additional power sources at the receiver end.

Versatile Installation Options

A point-to-point connection uses a single CAT6/5e cable and requires no drivers, software, or IP configuration, significantly reducing setup time. The HDMI extender can be mounted on a wall, ceiling, or the underside of a table using the included brackets, offering versatile professional installation options. The HDMI extender offers a longer range than HDMI cables, and Ethernet cables are easier to run in walls, behind furniture, or through cable trays. Its compact form factor makes it ideal for boardrooms, digital signage, trade shows, and classrooms.

Techninė specifikacija

Features	
Type	AV transmitter & receiver
Maximum resolution	3840 x 2160 pixels
Cable types supported	Cat5e, Cat6
Maximum transfer distance	60 m
Maximum refresh rate	60 Hz
Audio output channels	7.1 channels
Supported graphics resolutions	800 x 600 (SVGA), 1024 x 768 (XGA), 1152 x 864 (XGA+), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1280 x 768 (WXGA), 1280 x 800 (WXGA), 1280 x 960, 1360 x 768 (WXGA), 1400 x 1050 (SXGA+), 1440 x 900 (WXGA+), 1440 x 900, 1600 x 1200 (UXGA), 1600 x 900, 1680 x 1050 (WSXGA+), 1920 x 1080 (HD 1080), 1920 x 1200 (WUXGA), 1920 x 1440, 2048 x 1152, 2048 x 1536 (QXGA), 2560 x 1440, 2560 x 1600 (WQXGA), 2560 x 1920, 2560 x 2048
HDCP	Yes

Material	Metal
Rack mounting	No
HDCP version	2.2
Product colour	Black
Ports & interfaces	
Connectivity technology	Wired
RJ-45 input ports	1
RJ-45 output ports	1
HDMI in	1
Number of HDMI outputs	1
HDMI version	2
USB ports quantity	1
USB connector type	USB Type-C
Power	
Power source type	USB
AC input voltage	100 - 240 V
Input current	0.3 A
Operating voltage (transmitter)	5 V
Output current	2 A
Operating voltage (receiver)	5 V
Power consumption (typical)	10 W
USB Power Delivery (USB PD)	Yes
External power adapter	Yes
Operational conditions	
Operating temperature (T-T)	-20 - 60 °C
Storage temperature (T-T)	-30 - 70 °C
Operating relative humidity (H-H)	0 - 90%
Weight & dimensions	
Receiver dimensions (WxDxH)	40 x 67 x 23 mm
Receiver weight	92 g
Transmitter dimensions (WxDxH)	40 x 67 x 23 mm
Transmitter weight	92 g
Packaging data	
Package width	150 mm

Package depth	117 mm
---------------	--------

Package height	77 mm
----------------	-------

Package weight	364 g
----------------	-------

Packaging content

AC adapter included	Yes
---------------------	-----

Included power plug types	ANZ, EU, NA, UK
---------------------------	-----------------

Quick start guide	Yes
-------------------	-----

Mounting brackets included	Yes
----------------------------	-----

Technical details

Compliance certificates	Federal Communications Commission (FCC), RoHS
-------------------------	---

Logistics data

Master (outer) case width	430 mm
---------------------------	--------

Master (outer) case length	330 mm
----------------------------	--------

Master (outer) case height	380 mm
----------------------------	--------

Products per master (outer) case	30 pc(s)
----------------------------------	----------

Matmenys ir svoris

Matmenys (l × P × A)	16,00cm × 12,00cm × 8,00cm
----------------------	----------------------------

Svoris	0,49kg
--------	--------

Dokumentai ir vaizdo įrašai

› [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

StarTech.com Ltd.

Artisans Crescent 45, N5V 5E9 Ontario, London,
CA
startech.com

ATSAKINGAS ASMUIO ES

StarTech.com Limited

Laarderhoogtweg 25, 1101 EB Amsterdam, NL
startech.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt