

APC EPDU2016S maitinimo paskirstymo įrenginys 8 AC išvestis(ys) / čių) 1U Juoda

Gamintojas: **APC** · Modelis: **EPDU2016S** · EAN: **731304761242** · Prekės kodas: **902897**



813,89 €

Kaina su PVM

Be PVM: **672,64 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ input: 1PH, 16A, 200-240VAC
- ✓ Outlets: (8) C13
- ✓ Switched
- ✓ Full-featured network management capability
- ✓ Interactive LCD display



Aprašymas

Schneider Easy Switched Rack PDU EPDU1016S is Easy-to-install and easy-to-use PDU, making rack power distribution easy and intelligent. This provides on/off outlet switching, advanced power management, load monitoring and much more features than the average power strip. EPDU2016S has IEC 320 C20 200-240V type inlet and eight IEC C13 type outlet sockets. This is horizontal rack mountable PDU in ultra light weight and smart, multifunctional new designed display. Remotely manage outlets so users can turn outlets off that are not in use (prevent overloads) or recycle power to locked-up equipment (minimize costly downtime and avoid travel time to equipment) Full-featured network management interfaces that provide standards-based management via Web, SNMP, and Command Line Interface. Allows users to access, configure, and manage units from remote locations to save valuable time. Quickly and easily upgrade firmware via network download for future product enhancements. Eliminates the need to replace products already installed in the field when new features are released. Connect and manage multiple PDUs from one IP address to simplify and speed deployment while saving the cost required in having a dedicated network connection for each PDU Quickly and easily upgrade firmware via network download for future product enhancements. Eliminates the need to replace products already installed in the field when new features are released. Allows users to configure the sequence in which power is turned on or off for each outlet. This helps avoid in-rushes at start-up, which can

cause overloaded circuits and dropped loads Sequencing also allows users to predetermine which piece of equipment is turned on first so other equipment dependant on that unit will function properly. Indicates overload and warning conditions based on the user-defined alarm thresholds. Alerts users of potential overloaded circuits. The green packaging includes cable, installation guide and horizontal mounting brackets for quick and easy mounting in the enclosure. This can operate from -5° to +50°C temperation range and comes with 1 year of standard warranty. The aggregate current draw per power distribution unit is displayed on the unit via a digital display. The local digital display helps installers avoid overloaded circuits by providing a visible warning when the current draw is close to the maximum amperage draw of the strip.

Techninė specifikacija

Konstrukcija	
PDU tipai	Perjungta
Rėmo pajėgumas	1U
Tipas	Vienfazis
Montavimas	Vertikaliai
Produkto spalva	Juoda
Ryšys	
Lizų kiekis	8 AC išvestis(ys / čių)
AC išėjimo tipai	C13 šakotuvai
Maitinimo laido kištukas	C20 šakotuvai
Energijos valdymas	
Nominali įėjimo įtampa	230 V
Maksimali srovė	16 A
AC įėjimo dažnis	50/60 Hz
Išėjimo įtampa	208 V
Leistinoji apkrova	3680 VA
Etapų skaičius	1
Sertifikatai	
Atitikties sertifikatai	CE, UKCA
Aplinkos sąlygos	
Darbo temperatūros diapazonas (TT)	-5 - 50 °C
Sandėliavimo temperatūros norma (T-T)	-25 - 65 °C
Darbo santykinės drėgmės diapazonas	5 - 95%
Sandėliavimo santykinis drėgmės diapazonas	5 - 95%
Darbinis aukštis	0 - 3000 m
Svoris ir matmenys	
Plotis	482 mm
Ilgis	150 mm

Aukštis	44 mm
---------	-------

Svoris	2,45 kg
--------	---------

Pakuotės duomenys

Paketo svoris	3,8 kg
---------------	--------

Pakuotės plotis	260 mm
-----------------	--------

Pakuotės gylis	570 mm
----------------	--------

Pakuotės aukštis	680 mm
------------------	--------

Logistikos duomenys

Bendrasis anglies pėdsakas (kg of CO2e)	814
---	-----

Matmenys ir svoris

Matmenys (I × P × A)	58,00cm × 27,00cm × 7,00cm
----------------------	----------------------------

Svoris	3,46kg
--------	--------

Dokumentai ir vaizdo įrašai

- › [Naudojimo instrukcija](#)
- › [Gaminio lankstinukas](#)
- › [Anglies pėdsakas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

Schneider Electric SE

rue Joseph Monier 35, 92500 RUEIL MALMAISON, FR

[se.com](https://www.se.com)

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt