

StarTech.com 4-Port HDMI Extender and Splitter Over CAT6, 4K 60Hz, Up to 230ft (70m), 1x4 HDMI over Ethernet Distribution Kit with IR and Power Over Cable

Gamintojas: **STARTECH** · Modelis: **4K7014IC-EXTEND-HDMI** · EAN: **065030916165** · Prekės kodas: **902910**



650,90 €

Kaina su PVM

Be PVM: 537,93 €

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ **HDMI Over Ethernet Cabling:** Extend HDMI signals to four remote displays over CAT6/6a with one transmitter; Supports lossless, low-latency 4K 60Hz video with 2ch audio up to 230ft (70m); Ideal for boardrooms, digital signage, education, and hospitality
- ✓ **Power-Over-Cable:** A single power adapter connects to the transmitter, and all four receivers are powered over the CAT6/6a cabling, simplifying installation in environments with limited power access while reducing cable clutter
- ✓ **No Drivers or Software:** One-to-many HDMI Extender requires no drivers, software, or IP configuration, reducing setup time; Works with any operating system (Windows, macOS, and ChromeOS) and hardware platform (Intel, AMD, and Apple Silicon)
- ✓ **Versatile Mounting Options:** 1x4 HDMI distribution kit includes mounting brackets for wall, ceiling, or under-table installation at both the transmitter and receivers; Compact form factor allows for discrete installation in tight spaces
- ✓ **The IT Pro's Choice:** Backed by decades of connectivity expertise from legacy VGA to modern USB4 and AVoIP solutions; Work with a single trusted partner for all your A/V connectivity needs; Free lifetime 24/5 multi-lingual technical assistance





Aprašymas

Split and extend a single 4K 60Hz HDMI signal to four HDMI displays over a distance of up to 230ft (70m) with Power over Cable

This HDMI extender and splitter delivers reliable 4K AV distribution to four displays over Ethernet cabling for professional AV installations. Enables flexible deployment using Ethernet cables for longer-range and in-wall runs. Ideal for centralized AV distribution in boardrooms, digital signage, educational facilities, and hospitality environments.

HDMI Over Ethernet Cabling

Extend HDMI signals to four remote displays over CAT6/6a cabling using a single transmitter. Transmitter features a HDMI output providing a direct connection for a local display. Supports 4K 60Hz video and 2 channel audio up to 230ft (70m). Includes IR extension support for remote control of the source device from any connected display.

Powered with a Single Power Adapter

Single power adapter connects to the transmitter; all four receivers are powered directly over the CAT6/6a cables. Simplifies installation in environments with limited power access and reduces overall cable clutter.

No Drivers, Software, or IP Configuration

Plug-and-play installation with no additional drivers, software, or network setup required. Supports any operating system including Windows, macOS, and ChromeOS, and is compatible with all hardware platforms including Intel, AMD, and Apple Silicon.

Versatile Mounting Options

1x4 HDMI distribution kit includes mounting brackets for wall, ceiling, or under-table installation at both transmitter and receiver locations. Compact form factor enables discreet installation in tight spaces.

Techninė specifikacija

Features	
Type	AV transmitter & receiver
Maximum resolution	3840 x 2160 pixels
Cable types supported	Cat6, Cat6a
Maximum transfer distance	70 m
Chipset	GSV5100
Maximum refresh rate	60 Hz
Audio output channels	2.0 channels
LED indicators	Yes

Rack mounting	No
Daisy chain	No
Product colour	Black
Windows operating systems supported	Yes
Mac operating systems supported	Yes
Ports & interfaces	
Connectivity technology	Wired
RJ-45 input ports	4
RJ-45 output ports	4
HDMI in	1
Number of HDMI outputs	5
Remote (IR) input	4
Remote (IR) output	1
DC-in jack	Yes
Power	
AC input voltage	100 - 240 V
Operating voltage	12 V
Input current	0.8 A
Output current	2 A
Power consumption (typical)	24 W
Power plug type	Type M
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-10 - 70 °C
Operating relative humidity (H-H)	5 - 90%
Weight & dimensions	
Width	103 mm
Depth	180 mm
Height	23 mm
Weight	375 g
Packaging data	
Package width	423 mm
Package depth	345 mm
Package height	60 mm

Package weight	1.2 kg
----------------	--------

Packaging content

AC adapter included	Yes
Included power plug types	ANZ, EU, NA, UK
Quick start guide	Yes
IR blaster included	Yes
IR receiver included	Yes
Mounting kit	Yes

Packaging content	1 - HDMI Transmitter 4 - HDMI Receiver
-------------------	--

Technical details

Compliance certificates	Federal Communications Commission (FCC), RoHS
-------------------------	---

Logistics data

Master (outer) case width	450 mm
Master (outer) case length	367 mm
Master (outer) case height	525 mm
Products per master (outer) case	6 pc(s)

Matmenys ir svoris

Matmenys (l × p × A)	32,00cm × 24,00cm × 8,00cm
Svoris	2,02kg

Dokumentai ir vaizdo įrašai

› [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

StarTech.com Ltd.

Artisans Crescent 45, N5V 5E9 Ontario, London,
CA

startech.com

ATSAKINGAS ASMUO ES

StarTech.com Limited

Laarderhoogtweg 25, 1101 EB Amsterdam, NL

startech.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt