

StarTech.com NETRS2322P nuosekliųjų įrenginių serveris RS-232

Gamintojas: **STARTECH** · Modelis: **NETRS2322P** · EAN: **065030864145** · Prekės kodas: **902952**



266,90 €

Kaina su PVM

Be PVM: 220,58 €

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Two RS232 (DB9) serial ports, integrated into a durable, metal housing that's ideal for industrial environments
- ✓ Built-in mounting brackets let you easily install the device server to a wall or surface
- ✓ Redundant power input using the provided power adapter, or 9~36V DC terminal block input
- ✓ Extended operating temperature range — 0°C to 85°C (32°F to 185°F)
- ✓ Up to 460.8Kbps serial baud rate
- ✓ Remote management and customization using the provided Windows based VCOM software or the Web interface
- ✓ Supports Telnet, ICMP, IP, TCP, UDP, DHCP, HTTP, and BOOTP protocols
- ✓ 15kV Air and 8kV contact ESD (Electrostatic Discharge) Protection
- ✓ 10/100Mbps RJ45 port that supports IEEE 802.3 (10BASE-T) and IEEE 802.3u (100BASE-TX) protocols



Aprašymas

Connect, configure and manage two remote RS232 serial devices, over an IP network

This 2-port serial device server is a cost-effective way to remotely connect to and manage two serial devices over your typical IP network. The device server integrates two RS232 ports into a rugged metal housing with an extended operating temperature range, so it's perfect for factory and

industrial settings.

Flexible installation, in a range of environments

If you're looking for a reliable serial-over-IP control solution, then this device server can help. With a rugged metal housing and an extended operating temperature range, you can rest assured that the device server can deliver the reliable performance you need, even in harsh environments.

Plus, it features two integrated mounting brackets, so you can mount the device server to a surface or a wall as needed, for out-of-the-way installations.

Backup power keeps your devices connected

With redundant power input, this dual-port serial device server ensures seamless operation, even in the event of power dips or failures. It features a wide-range, terminal block power input (9~36V DC), and includes a universal power adapter.

Because it features two power inputs, if you experience a power disruption the device server automatically switches to its secondary power source. With redundant power input, the device server remains operational if one of the power sources fails, so you can continue to connect to and manage your serial devices when needed.

Completely customizable

This highly customizable device server is easy to configure to suit your application. For easy setup, Windows® users can use the provided Virtual COM port software, or the versatile Web-based interface.

The RS232 device server supports Telnet (an operating system independent communication protocol), so it can be integrated into mixed OS environments (Windows, Mac, Linux®). Plus, it supports VCOM, TCP, ICMP, IP, TCP, UDP, DHCP, and BOOTP protocols.

The NETRS2322P is backed by a StarTech.com 2-year warranty and free lifetime technical support.

Techninė specifikacija

Techninė informacija	
Serijinių portų kiekis	2
Nuosekliosios sąsajos tipas	RS-232
Eterneto LAN duomenų perdavimo norma	10,100 Mbit/ai
Apsauga nuo elektrostatinės iškrovos (ESD)	15 kV
Tinklo standartai	IEEE 802.3, IEEE 802.3u
Sparta	460,8 Kbit/ai
Auto MDI/MDI-X	Taip
Duomenų bitai	7, 8
Srauto reguliavimo tipas	Ne, RTS/CTS, XON/XOFF
Pariteto bitas	Vienoda, „Mark“, Nelyginis, Kosmosas
Apsauga nuo elektrostatinės iškrovos (ESD; oras)	15 kV
Apsauga nuo elektrostatinės iškrovos (ESD; kontaktas)	8 kV
Atitikties sertifikatai	RoHS
Sertifikavimas	CE, FCC

Ryšys

Ethernet LAN (RJ-45) portų kiekis	1
Kabelių technologija	10/100Base-T(X)

Energijos valdymas

Maitinimo šaltinio tipas	AC
Iėjimo įtampa	100 - 240 V
Išėjimo įtampa	12 V
Išėjimo srovė	3 A
Suderinamų energijos šaltinio kištukinių lizdų tipai	AU, EU, UK, US
Įvesties srovė	1.5 A

Protokolai

Palaikomi tinklo protokolai	ICMP, IP, TCP, UDP, DHCP, BOOTP, Telnet
-----------------------------	---

Indikacija

LED indikatoriai	Aktyvumas, LAN, Jungtis, Būseną
------------------	---------------------------------

Programinė įranga

Palaikomos „Windows“ operacinės sistemos	Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 Pro, Windows 10 Pro x64, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64
Palaikomos serverio valdymo sistemos	Windows Server 2008 R2, Windows Server 2012

Svoris ir matmenys

Svoris	320 g
Matmenys (WxDxH)	81 x 112 x 23 mm
Pakuotės plotis	151 mm
Pakuotės gylis	217 mm
Pakuotės aukštis	55 mm
Paketo svoris	685 g

Aplinkos sąlygos

Darbo temperatūros diapazonas (TT)	0 - 85 °C
------------------------------------	-----------

Sandėliavimo temperatūros norma (T-T)	-45 - 130 °C
Darbo santykinės drėgmės diapazonas	20 - 80%
Konstrukcija	
Produkto spalva	Juoda
Korpuso medžiaga	Plienas
Pakuotės turinys	
Naudojimo žinynas	Taip
Kintamosios srovės adapteris	Taip
Logistikos duomenys	
Gaminių skaičius pagrindinėje (išorinėje) dėžėje	16 vnt
Pagrindinės (išorinės) dėžės ilgis	476 mm
Pagrindinės (išorinės) dėžės plotis	344 mm
Pagrindinės (išorinės) dėžės aukštis	246 mm
Matmenys ir svoris	
Matmenys (I × P × A)	22,00cm × 15,00cm × 6,00cm
Svoris	0,62kg

Dokumentai ir vaizdo įrašai

- › [Naudojimo instrukcija](#)
- › [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

StarTech.com Ltd.

Artisans Crescent 45, N5V 5E9 Ontario, London,
CA

startech.com

ATSAKINGAS ASMUO ES

StarTech.com Limited

Laarderhoogtweg 25, 1101 EB Amsterdam, NL

startech.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt