

TP-Link Tapo Solar Panel

 Gamintojas: **TP-LINK** · Modelis: **TAPO A200** · EAN: **4897098686140** · Prekės kodas: **903152**


51,90 €

Kaina su PVM

 Be PVM: **42,89 €**




Sandėlyje


Prekė internetu

 Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Non-Stop Solar Power-Captures free, clean solar energy and provides non-stop power supply for your Tapo battery-powered cameras (Tapo C425, Tapo C420, and Tapo C400) to ensure they protect you all year round
- ✓ Up to 4.5W Charging Power-Made of premium monocrystalline silicon cells, Tapo A200 captures plentiful solar energy and provides continuous power supply efficiently
- ✓ IP65 Weatherproof-Offers excellent waterproof and dustproof performance for outdoor scenarios
- ✓ 4m Charging Cable-Offers flexible installation with a 13ft/4m charging cable
- ✓ 360° Adjustable Mounting Bracket-Adjust your solar panel for the perfect angle to capture sufficient light



Aprašymas

**Non-Stop Power,
Year-Round Protection.**

Solar Panel Tapo A200

Up to 4.5W Charging Power, Non-Stop Power Supply

Made of premium monocrystalline silicon cells, Tapo A200 provides high-power(up to 4.5W*), which means only 30mint of standard sunlight every day can keep your Tapo battery cameras working around the clock.

Works with Tapo Battery Cameras

Compatible with Tapo C425, Tapo C420, and Tapo C400, enabling your Tapo battery camera to protect you all year round.

More products will be supported in the future.

360° Angle Adjustable for Sufficient Sunlight

Mount your solar panel on the wall or roof and adjust its angle flexibly to capture enough sunlight with an angle-adjustable bracket.

4m Charging Cable for Flexible Installation

No need to worry about the distance limit of your solar panel and camera. Just find the best position, place it there, and enjoy free solar energy.

IP65 Weatherproof

Offers reliable performance and keeps your battery cameras stay charged even in harsh environments with rain and dust.

Techninė specifikacija

Power	
Rated power	4.5 W
Minimum output voltage	5.2 V
Features	
Tilt angle range	0 - 360°
International Protection (IP) code	IP65
USB port	Yes
USB connector type	Micro-USB
USB ports quantity	1
Compatible products	Tapo C425, Tapo C420, Tapo C400
Cable length	4 m
Packaging content	
Manual	Yes
Packaging data	

Package width	200 mm
Package depth	266 mm
Package height	88 mm
Package weight	840 g

Operational conditions

Operating temperature (T-T)	-20 - 45 °C
Storage temperature (T-T)	-40 - 60 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%

Weight & dimensions

Width	238 mm
Depth	174.8 mm
Height	17.5 mm

Dokumentai ir vaizdo įrašai

- › [Naudojimo instrukcija](#)
- › [Greitos pradžios vadovas](#)
- › [Gaminio lankstinukas](#)
- › [Vaizdo įrašas](#) youtube.com/watch?v=vFQyzUq_hdM

Gamintojo ir saugos informacija

GAMINTOJAS

TP-Link

ATSAKINGAS ASMUO ES

TP-Link Deutschland GmbH

Niederkasseler Lohweg 175, 40547 Düsseldorf,
DE
tp-link.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt