

Zalman ZM750-GVII power supply unit 750 W 20+4 pin ATX ATX Black

Gamintojas: **ZALMAN** · Modelis: **ZM750-GVII** · EAN: **8809213769610** · Prekės kodas: **903577**



50,90 €

Kaina su PVM

Be PVM: **42,07 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Active PFC with up to 99.5% maximum power factor
- ✓ 12V DC-TO-DC converter with 99% availability
- ✓ System standby power at 0.5W or less
- ✓ Built-in EMI filter for noise reduction
- ✓ 105°C capacitor
- ✓ 120mm fan with FDB Bearing
- ✓ ErP Lot 6 Certified



Aprašymas

80 Plus Bronze 230V EU certified Power Supply Unit. It supplies smooth power to the PC while reducing unnecessary power consumption by using high-performance parts that are very durable and reliable.

Techninė specifikacija

Power

Total power	750 W
AC input voltage	200 - 240 V

AC input frequency	50 - 60 Hz
Input current	6 A
Maximum input current (@110V)	6 A
Power factor	99
Power Factor Correction (PFC) type	Active
Combined power (+3.3V)	120 W
Combined power (+12V)	744 W
Combined power (+5V)	120 W
Combined power (-12V)	3.6 W
Combined power (+5Vsb)	12.5 W
Max output current (+3.3V)	20 A
Max output current (+12V)	62 A
Max output current (+5V)	20 A
Max output current (-12V)	0.3 A
Max output current (+5Vsb)	2.5 A
Efficiency	88%
Power protection features	Over current, Over power, Over voltage, Under current, Under voltage

Ports & interfaces

Motherboard power connector	20+4 pin ATX
Peripheral (Molex) power connectors (4-pin)	1
Motherboard power cable length	55 cm
Number of SATA power connectors	2
SATA power cable length	400 mm
Peripheral (Molex) power cable length	400 mm
PCI Express power connectors (6+2 pin)	2
PCI Express power cable length	50 cm
CPU power connector (4+4 pin)	Yes
CPU power cable length	65 cm
ATX power connector (20+4 pin)	Yes
PCI Express connector	Yes
Cabling type	Non-Modular

Performance

Purpose	PC
Power supply unit (PSU) form factor	ATX
80 PLUS certification	80 PLUS Bronze

Supported motherboard form factors	ATX, micro ATX, Mini-ITX
Noise level	37.7 dB
Bearing technology	FDB
Mean time between failures (MTBF)	100000 h

Design

Product colour	Black
Cooling type	Active
Fan diameter	12 cm
Number of fans	1 fan(s)
Fan location	Top
On/off switch	Yes

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	5 - 85%
Storage relative humidity (H-H)	5 - 95%

Packaging content

Cables included	AC, CPU, PCIe, Peripheral (Molex), SATA
-----------------	---

Certificates

Compliance certificates	RoHS
Certification	80 Plus, CB, CE, KC, EAC, RoHS

Safety regulation & standards

Safety	CB, CE, KC, EAC, RoHS
--------	-----------------------

Weight & dimensions

Width	140 mm
Depth	150 mm
Height	86 mm
Weight	2.09 kg

Packaging data

Package width	180 mm
Package depth	280 mm
Package height	100 mm
Package weight	2.12 kg
Package type	Box

Logistics data

Country of origin

China

Dokumentai ir vaizdo įrašai

[› Naudojimo instrukcija](#)

Gamintojo ir saugos informacija

GAMINTOJAS

ZALMAN TECH CO., Ltd

Beolmal-ro, Dongan-gu 126, Anyang-si, KR

zalman.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt