

Seagate Barracuda 7200.7 80GB PATA internal hard drive 7200 RPM 16 MB 3.5" Parallel ATA

Gamintojas: **SEAGATE** · Modelis: **ST380013A** · Prekės kodas: **904586**



46,90 € ~~50,90 €~~

Kaina su PVM

Be PVM: **38,76 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 80 GB 3.5" 7200 RPM Parallel ATA
- ✓ SMART technology
- ✓ HDD
- ✓ 635 g
- ✓ Storage drive buffer size: 16 MB

Aprašymas

- 7,200-RPM spindle speed
- 8-Mbyte buffer
- High instantaneous (burst) data transfer rates (up to 100 Mbytes per second) using Ultra DMA mode 5.
- Giant magnetoresistive (GMR) recording heads and EPRML technology, which provide the drives with increased areal density.
- State-of-the-art cache and on-the-fly error-correction algorithms.
- Full-track multiple-sector transfer capability without local processor intervention.
- Quiet operation.
- 350 Gs nonoperating shock.
- SeaTools diagnostic software performs a drive self-test that eliminates unnecessary drive returns.
- The 3D Defense System™, which includes Drive Defense, Data Defense, and Diagnostic Defense, offers the industry's most comprehensive protection for disc drives.
- Support for S.M.A.R.T. drive monitoring and reporting.
- Support for Read Multiple and Write Multiple commands.
- Support for autodetection of master/slave drives that use cable select (CSEL).

Techninė specifikacija

Features	
HDD capacity	80 GB
HDD speed	7200 RPM
HDD size	3.5"
Interface	Parallel ATA
Type	HDD
Storage drive buffer size	16 MB
HDD number of heads	2
HDD number of cylinders	16383
Read seek time	8.5 ms
Write seek time	9.5 ms
Track to track seek time	1.2 ms
Average latency	4.16 ms
SMART technology	Yes
Bytes per sector	512
Start/stop cycles	50000
Mean time between failures (MTBF)	600000 h
Power	
Power consumption (standby)	0.9 W
Power consumption (PowerSave)	0.9 W
Power consumption (read)	12 W
Power consumption (write)	12 W
Power consumption (idle)	7.5 W
Operating voltage	5 / 12 V
Start-up current	2.8 A
Operational conditions	
Operating temperature (T-T)	0 - 60 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	5 - 90%
Storage relative humidity (H-H)	5 - 95%
Operating vibration	0.5 G
Non-operating vibration	5 G
Operating shock	63 G

Non-operating shock	350 G
---------------------	-------

Weight & dimensions

Width	101.6 mm
-------	----------

Height	26 mm
--------	-------

Depth	147 mm
-------	--------

Weight	635 g
--------	-------

Packaging data

Quantity per pack	1 pc(s)
-------------------	---------

Other features

Wi-Fi	No
-------	----

Ethernet LAN	No
--------------	----

Product colour	Black
----------------	-------

Internal	No
----------	----

Maximum data transfer rate	85.4 Mbit/s
----------------------------	-------------

USB powered	Yes
-------------	-----

eSATA	Yes
-------	-----

FireWire 400	No
--------------	----

FireWire 800	No
--------------	----

Fibre Channel	No
---------------	----

USB 3.2 Gen 1 (3.1 Gen 1) ports quantity	0
--	---

USB 2.0 ports quantity	0
------------------------	---

Windows operating systems supported	Yes
-------------------------------------	-----

Matmenys ir svoris

Svoris	1,00kg
--------	--------

Gamintojo ir saugos informacija

GAMINTOJAS

Seagate

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt