

SERVER ACC PSU 860W REDUNDANT/PWS-860P-1R2 SUPERMICRO

Gamintojas: **SUPERMICRO** · Modelis: **PWS-860P-1R2** · Prekės kodas: **905175**

211,90 € ~~230,90 €~~

Kaina su PVM

Be PVM: **175,12 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Aprašymas

The Supermicro PWS-860P-1R2 is an 80 Plus Platinum level redundant power supply capable of continuously supplying 800W/860W output power at 94% efficiency. Enjoy the simplicity of active power factor correction (PFC) and automatically correct AC input for a full range of voltages. Features a card edge output to interface with a 2x25 card edge connector. This power supply is designed to not only provide you reliable power to your Supermicro server but also protects it from over voltage, over current and short circuiting via protective circuitry embedded into the unit. Rest easy knowing your hardware will be up and running with a mean-time between failure (MTBF) of greater than 250,000 hours and an LED indicator to keep you informed on normal/abnormal conditions for your PSU. This power supply is redundant to safe-guard your system from power failure and allows for hot-swap replacement to eliminate system downtime. All materials contained comply with RoHS requirements and is certified by Supermicro.

- Designed for Supermicro Server
- Redundant PSU with PMBus 1.2 Support for Remote Management
- 80 Plus Platinum Efficiency
- Supermicro Certified

Summary: Supermicro PWS-860P-1R2. Total power: 860 W, AC input voltage: 100 - 240 V, AC input frequency: 50/60 Hz. Purpose: Server, Power supply unit (PSU) form factor: 1U, 80 PLUS certification: 80 PLUS Platinum. Compliance certificates: REACH, RoHS. Width: 54.5 mm, Depth: 40.2 mm, Height: 322 mm | Vendor Homepage: https://store.supermicro.com/us_en/800w-1u-pws-860p-1r2.html | Total power: 860 | AC input voltage: 100 - 240 | AC input frequency: 50/60 | Efficiency: 94 | 80 PLUS certification: 80 PLUS Platinum | Purpose: Server | Power supply unit (PSU) form factor: 1U | Mean time between failures (MTBF): 250000 | LED indicators: Yes | Compliance certificates: REACH/RoHS | Width: 54.5 | Depth: 40.25 | Height: 322 | Unit Calculated Weight: 1.12 | Product Net Weight: 1.12 | Unit Calculated Volume: 0.00624 | Units per Shipping Box: 1 | Unit Width: 13 | Shipping Box Height: 12 | Unit Depth: 40 | Unit Height: 12 | Name: SERVER ACC PSU 860W REDUNDANT/PWS-860P-1R2 SUPERMICRO | Model: PWS-860P-1R2 | Model name: PWS-860P-1R2

Techninė specifikacija

Matmenys ir svoris

Matmenys (I × P × A)

40,00cm × 13,00cm × 12,00cm