

Dahua Technology HAC-HDW1549X-IL-A-PRO Turret IP security camera Outdoor 2880 x 1620 pixels Ceiling/Wall/Pole

Gamintojas: **DAHUA** · Modelis: **HAC-HDW1549X-IL-A-PRO-0280B-DIP** · EAN: **6937552409446** · Prekės kodas: **905207**



113,90 €

Kaina su PVM

Be PVM: **94,13 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ High-Quality Imaging with 5MP 16:9 Resolution
- ✓ Smart Dual Light: Built-in IR and LED Lights with 3 Illumination Modes Supported
- ✓ WizColor Technology: Exceptional Image Quality in Low-Light Conditions
- ✓ Built-In Dual Mic : Enhances Video Assistance with Dual Mic Technology
- ✓ Smart Light+ : Clear Details with Advanced LED Processing Technology
- ✓ 3DNR & DWDR & Super Adapt Ensures Clear Details in Strong Backlight Conditions
- ✓ Effortless Signal Selection with DIP Switch
- ✓ Time-saving Installation with Quick-to-install Structure
- ✓ IP67 Ratings for Protection Against Harsh Environments



Aprašymas

- High-Quality Imaging with 5MP 16:9 Resolution
- Smart Dual Light: Built-in IR and LED Lights with 3 Illumination Modes Supported
- WizColor Technology: Exceptional Image Quality in Low-Light Conditions

- Built-In Dual Mic : Enhances Video Assistance with Dual Mic Technology
- Smart Light+ : Clear Details with Advanced LED Processing Technology
- 3DNR & DWDR & Super Adapt Ensures Clear Details in Strong Backlight Conditions
- Effortless Signal Selection with DIP Switch
- Time-saving Installation with Quick-to-install Structure
- IP67 Ratings for Protection Against Harsh Environments

Summary: Dahua Technology HAC-HDW1549X-IL-A-PRO. Type: IP security camera, Placement supported: Outdoor, Connectivity technology: Wired. Mounting type: Ceiling/Wall/Pole, Product colour: White, Form factor: Turret. Minimum illumination: 0.0001 lx, Angle of rotation: 360°, Lens viewing angle, horizontal: 111°. Sensor type: CMOS. Detect distance: 63.8 m, Observe distance: 25.5 m, Recognize distance: 12.8 m | Vendor Homepage: <https://www.dahuasecurity.com/products/hd cvi-products/hd cvi-cameras/lite-series/5mp/wizcolor/hac-hdw1549x-il-a-pro> | Tipas: IP apsaugos kamera | Ryšio technologija: Vielinis | Talpinimas palaikomas: Lauke | Maksimalus veikimo nuotolis: 50 | Išplėstinis dinaminis diapazonas (WDR): Taip | Dienos / nakties režimas: Taip | Sertifikavimas: CE-LVD: EN 62368-1; CE-EMC: EN 55032; EN 55035; | Forma: Bokštelis | Montavimo tipas: Ant lubų / sienos / stulpo | Produkto spalva: Balta | Korpuso medžiaga: Metalas/Plastikas | Tarptautinės apsaugos (IP) kodas: IP67 | Minimalus apšviestumas: 0.0001 | Sukimosi kampas: 360 | Objektyvo vaizdo kampas, horizontalus: 111 | Objektyvo vaizdo kampas, vertikalus: 58.5 | Objektyvo vaizdo kampas, įstrižainė: 136.3 | Posvyrio kampo intervalas: 0 - 90 | Viso diapozonas: 0 - 360 | Baltos spalvos balansas: Automatinis | Kameros užrakto greitis: 1/30 - 1/100000 | Progresyvus nuskaitymas: Taip | Jutiklio tipas: CMOS | Aptikties atstumas: 63.8 | Stebėjimo atstumas: 25.5 | Atpažinimo atstumas: 12.8 | Židinio nuotolis: 2.8 | Fiksuotas fokusavimas: Taip | Identifikavimo atstumas: 6.4 | Maksimalus apertūros skaičius: 1 | Mažiausias fokusavimo atstumas: 1.4 | Naktinis matymas: Taip | Naktinio matymo atstumas: 50 | LED tipas: IR | Maksimali rezoliucija: 2880 x 1620 | Iš viso megapikselių: 5 | Palaikomos grafikos rezoliucijos: 2560 x 1440/2880 x 1620/2960 x 1665/960 x 480/960 x 576 | Kadru sparta: 25 | Analoginio signalo formato sistema: NTSC/PAL | Triukšmo mažinimas: Taip | Triukšmo sumažinimo technologija: 3D triukšmo mažinimas | Valdymo sustiprinimo tipas: Automatinis | „Smart IR“ įtaisas: Taip | Privatumo maskavimas: Taip | Signalų ir triukšmo santykis (SNR): 65 | Įmontuotas mikrofonas: Taip | Mikrofonų kiekis: 2 | Integruotas kietasis diskas: Ne | BNC išvesties prievadai: 1 | Vaizdo judesio detekcija: Taip | Veidrodė: Taip | Maitinimo šaltinio tipas: DC | Galios suvartojimas (maks.): 6.1 | DC išėjimo įtampa: 12 | Darbo temperatūros diapazonas (TT): -40 - 60 | Sandėliavimo temperatūros norma (T-T): -40 - 60 | Darbo santykinės drėgmės diapazonas: 0 - 95 | Sandėliavimo santykinis drėgmės diapazonas: 0 - 95 | Aukštis: 102.2 | Skersmuo: 109.9 | Svoris: 330 | Atitikties sertifikatai: CE | Paketo svoris: 450 | Pakuotės tipas: „Box“ | Fotoaparato skaičius: 1 | Lęšio montavimo sąsaja: M12 | Bruto svoris: 0.46 | Neto svoris: 0.33 | Vienetų skaičius vienoje siuntimo dėžėje: 1 | Vieneto plotis: 13.1 | Vienetų skaičius ant paletės: 0 | Shipping Box Height: 11.5 | Vieneto gylis: 13.1 | Vieneto aukštis: 11.5 | Name: CAMERA HDCVI 5MP EYEBALL/HDW1549X-IL-APRO0280BDIP DAHUA

Techninė specifikacija

Performance	
Type	IP security camera
Placement supported	Outdoor
Connectivity technology	Wired
Maximum operating distance	50 m
Wide Dynamic Range (WDR)	Yes
Day/night mode	Yes
Certification	CE-LVD: EN 62368-1; CE-EMC: EN 55032; EN 55035;
Design	
Mounting type	Ceiling/Wall/Pole
Product colour	White
Form factor	Turret
Housing material	Metal, Plastic
International Protection (IP) code	IP67

Camera

Minimum illumination	0.0001 lx
Angle of rotation	360°
Lens viewing angle, horizontal	111°
Lens viewing angle, vertical	58.5°
Lens viewing angle, diagonal	136.3°
Tilt angle range	0 - 90°
Pan range	0 - 360°
White balance	Auto
Camera shutter speed	1/30 – 1/100000

Image sensor

Sensor type	CMOS
Progressive scan	Yes

Lens system

Detect distance	63.8 m
Observe distance	25.5 m
Recognize distance	12.8 m
Focal length range	2.8 mm
Fixed focus	Yes
Maximum aperture number	1
Identify distance	6.4 m
Closest focusing distance	1.4 m

Night vision

Night vision	Yes
Night vision distance	50 m
LED type	IR

Video

Maximum resolution	2880 x 1620 pixels
Total megapixels	5 MP
Supported graphics resolutions	2880 x 1620, 2560 x 1440, 960 x 576, 960 x 480, 2960 x 1665
Frame rate	25 fps
Analog signal format system	NTSC, PAL
Noise reduction	Yes
Noise reduction technology	3D noise reduction

Gain control type	Auto
Privacy masking	Yes
Smart IR	Yes
Audio	
Signal-to-Noise Ratio (SNR)	65 dB
Built-in microphone	Yes
Number of microphones	2
Storage	
Built-in HDD	No
Ports & interfaces	
BNC output ports	1
Security	
Video motion detection	Yes
Mirror	Yes
Power	
Power source type	DC
Power consumption (max)	6.1 W
DC output voltage	12
Operational conditions	
Operating temperature (T-T)	-40 - 60 °C
Storage temperature (T-T)	-40 - 60 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Weight & dimensions	
Height	102.2 mm
Diameter	11 cm
Weight	330 g
Packaging data	
Package weight	450 g
Package type	Box
Sustainability	
Compliance certificates	CE
Packaging content	
Number of cameras	1

Technical details

Lens mount interface	M12
----------------------	-----

Matmenys ir svoris

Matmenys (I × P × A)	13,00cm × 13,00cm × 12,00cm
----------------------	-----------------------------

Dokumentai ir vaizdo įrašai

- › [Naudojimo instrukcija](#)
- › [Greitos pradžios vadovas](#)
- › [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

Zhejiang Dahua Technology Co., Ltd

Bin'an Road, Binjiang District No.1187 & 1199,
310053 Hangzhou, CN
dahuasecurity.com

ATSAKINGAS ASMUO ES

Dahua Technology GmbH

Niederkasseler Lohweg 185, 40547 Düsseldorf,
DE
dahuasecurity.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt