Axagon PCEU-43RS sąsajos plokštė / adapteris Vidinis USB 3.2 Gen 1 (3.1 Gen 1)

Gamintojas: **AXAGON** · Modelis: **PCEU-43RS** · EAN: **8595247906960** · Prekės kodas: **905344**



20,90 €

Kaina su PVM

Be PVM: **17,27 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Vidinis
- ✓ Priimančioji sąsaja: PCIe
- ✓ Išvesties sąsaja: USB 3.2 Gen 1 (3.1 Gen 1)
- ✓ 5 Gbit/s







Aprašymas

AXAGON PCEU-43RS PCI-Express card adds four external USB 3.2 Gen 1 ports to your desktop computer. The card is designed for fast data transfers at speeds up to 5 Gb/s.

All four SuperSpeed USB ports are taken out to the bracket. The dual power supply of the controller enables standard power supply of the controller and connected USB peripherals via the PCI-Express bus as well as optional power supply from the PC power supply via the SATA power connector.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

The USB controller is equipped with a renowned Renesas company chipset with proven seamless compatibility, high performance and UASP support.

Low profile bracket is included in the package for mounting the adapter into low profile cases.

Input:
• PCI-Express 2.0 interface, compatible with PCI-Express 1.0a / 1.1 / 2.1 / 3.0.
• Number of lines: 1-Lane (x1), compatible with x1 / x4 / x8 / x16 PCIe slots.
• A bandwidth of 1-Lane PCI-Express 2.0 bus is 5 Gb/s.

Output:
• 4x external USB 3.2 Gen 1 port with USB type A-F connectors.
• SuperSpeed USB - USB 3.2 Gen 1 interface (before USB 3.1 Gen 1 / USB 3.0).
• Compatible with USB 3.2 Gen 2, backward compatible with USB 2.0 a USB 1.1.
• Supports transmission rates 5000 / 480 / 12 / 1.5 Mb/s (super / high / full / low speed).
• When connected to a PCI-Express bus version 1.0, theor. transmission rate max. 2500 Mb/s.

Other features:
• Full Plug and Play support.
• Supports concurrent activity of SuperSpeed USB, USB 2.0 and USB 1.1 devices.
• Compliant with the final official xHCI specification revision 1.0 by USB-IF.
• Supports UASP (USB Attached SCSI) for faster data transmission in Windows 8 and later.
• Fully supports Hot Plug connecting and disconnecting of USB devices while running.
• Standard power supply for the controller and connected USB peripherals via the PCI-Express bus.
• In this power supply mode, the PCIe controller can handle up to three magnetic 2.5" external disks simultaneously.
• Optional power supply from PC source via SATA power connector.
• Renesas µPD720201 chipset is used.

Supported operating systems:
• MS Windows XP / Vista / 7 / 8 / 8.1 / 10 / 11 and later, Windows Server 2003 / 2008 / 2012 / 2016 / 2019 / 2022 and later (supported are all 32- and 64-bit Windows OS versions), Linux with kernel 2.6.31 and above.
• Note: Drivers are only installed for Windows XP / Vista / 7. For Linux, Windows 8 / 8.1 / 10 / 11, Server 2012 / 2016 / 2019 / 2022 and later versions, no external drivers are required, they are already part of the operating system.

Package contains:
• PCI-Express controller with a standard bracket,
• low-profile bracket
• multilingual guide CZ / DE / DK / ENG / ESP / FIN / FR / GR / HR / HU / IT / NL / PL / PT / RO / RU / SK / SWE / TR / BG / CN / ARA,
• packed in a cardboard box.

Techninė specifikacija

Ryšys	
Priimančioji sąsaja	PCIe
Išvesties sąsaja	USB 3.2 Gen 1 (3.1 Gen 1)
Pagrindinio įrenginio sąsajos tipas	Kištukinis
Išplėtimo kortelės formos faktorius	Viso aukščio / žemo profilio
Išplėtimo kortelės standartas	PCIe 2.0
USB 3.2 (3.1 1 kart.) A tipo prievadų skaičius	4

Konstrukcija	
Vidinis	Taip
Hot-Plug palaikymas	Taip
Lengvas instaliavimas	Taip
Kilmės šalis	Kinija
Sertifikavimas	CE, RoHS
Savybės	
Duomenų perdavimo sparta (maks.)	5 Gbit/s
„Plug and Play“ funkcija	Taip
Sistemos reikalavimai	
Palaikomos „Windows“ operacinės sistemos	Taip
Palaikoma operacinė sistema „Linux“	Taip
Palaikomos serverio valdymo sistemos	Taip
Techninė informacija	
Garantinis laikotarpis	3 metai
Atitikties sertifikatai	RoHS, CE
Pakuotės duomenys	
Kiekis pakuotėje	1 vnt
Instrukcija	Taip
Pakuotės plotis	145 mm
Pakuotės gylis	110 mm
Pakuotės aukštis	25 mm
Paketo svoris	90 g
Pakuotės tipas	„Box“
Matmenys ir svoris	
Matmenys (I × P × A)	3,00cm × 11,00cm × 15,00cm

Dokumentai ir vaizdo įrašai

› Naudojimo instrukcija

Gamintojo ir saugos informacija

GAMINTOJAS

RealQ, s.r.o.
Železná 663/5, 619 00 Brno-jih, CZ
axagon.eu

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.