

TP-Link Omada ER7206 laidinis maršrutizatorius Gigabitinis eternetas Juoda

Gamintojas: **TP-LINK** · Modelis: **ER7206** · EAN: **1210002611220** · Prekės kodas: **905495**



163,89 €

Kaina su PVM

Be PVM: **135,45 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Eterneto WAN SFP WAN
- ✓ IEEE 802.3, IEEE 802.3ab, IEEE 802.3q, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z
- ✓ Gigabitinis eternetas
- ✓ Web pagrįstas valdymas
- ✓ DHCP klientas DHCP serveris
- ✓ SNMP, SNMPv2, SNMPv3



Aprašymas

A Professional, Secure, and Reliable Gateway with Centralized Management Capability

Omada Gigabit VPN Router

- Centralized Management
- Gigabit Ports
- Up to 5 WAN Ports
- Load Balance
- SSL/Wireguard/IPSec/OpenVPN
- Multi-Net DHCP
- Powerful Firewall
- Omada App

Omada SDN—The Smarter Cloud Solution for Business Networking

As the gateway that seamlessly integrates into the Omada Software Defined Networking (SDN) platform, ER7206 allows for remote and centralized management, anywhere, anytime. Standalone management via the Web UI or app is also available to maximize convenience.

Hassle-Free Centralized Cloud Management:

100% centralized cloud management of whole network from different sites—all controlled from a single interface anywhere, anytime.

Up to Five WAN Gigabit Ports to Optimize Bandwidth Usage

One gigabit SFP WAN/LAN port, one gigabit RJ45 WAN port, and four freely interchangeable WAN/LAN ports allow the router to support up to five WAN ports to satisfy various internet access requirements through one device. The multi-WAN Load Balancing function distributes data streams according to the bandwidth proportion of every WAN port to raise the utilization rate of multi-line broadband.

Highly Secure VPN

ER7206 supports multiple VPN protocols including SSL / Wireguard/ IPSec/ OpenVPN/ GRE VPN\$/PPTP/ L2TP/ L2TP over IPSec, helping users to establish VPN connections more flexibly. One-click auto IPSec VPN* greatly simplifies VPN configuration and facilitates network management and deployment while also securing and encrypting private site-to-site data communications traveling over the internet.

Abundant Security Features

Powerful Firewall

Advanced firewall policies protect your network and data.

Convenient VLAN Support

Create virtual network segments for enhanced security and simplified network management.

DoS Defense

Automatically detects and blocks Denial of Service (DoS) attacks such as TCP/UDP/ICMP Flooding, Ping of Death, and other related threats.

IP/MAC/URL Filtering

Forcefully prevent viruses and attacks from intruders.

IP-MAC Binding

Reserves static IP assignment for clients to defend against ARP attacks and spoofing.

One-Click ALG Activation

One-Click ALG Activation for applications such as FTP, H323, SIP, IPsec and PPTP.

Internet Access Management Strategy

Standardize users' online behavior and easily specify the internet access rights and strategies of employee via IP/MAC/URL Filtering and Access Control List (ACL). Captive Portal authentication facilitates network resource control by capturing, authenticating, and classifying user access. Appropriate network resources can also be allocated for particular users or guests.

Easy Management with the Omada App

Follow configuration instructions on the free Omada app to get set up in minutes. Omada lets you configure settings, monitor the network status and manage clients, all from the convenience of a smart phone or tablet.

Techninė specifikacija

WAN jungtis	
Eterneto WAN	Taip
DSL WAN	Ne
SIM kortelės anga	Ne
3G/4G USB modemo suderinamumas	Ne
SFP WAN	Taip
Tinklas	
Tinklo standartai	IEEE 802.3, IEEE 802.3ab, IEEE 802.3q, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z
Eterneto sąsajos tipas	Gigabitinis eternetas
Kabelių technologija	10/100/1000Base-T(X)
Eterneto LAN duomenų perdavimo norma	10,100,1000 Mbit/ai
Statinis maršrutas	Taip
VLAN palaikymas	Taip
Portų ekspedijavimas	Taip
Valdymo funkcijos	
Web pagrįstas valdymas	Taip
Universali „Plug and Play“ jungtis (UPnP)	Taip
Atstatymo mygtukas	Taip
Ryšys	
Ethernet LAN (RJ-45) portų kiekis	5
SFP modulio angų kiekis	1
USB prievadų skaičius	1
USB versija	3.2 Gen 1 (3.1 Gen 1)
DC įėjimo lizdas	Taip

Protokolai

DHCP klientas	Taip
DHCP serveris	Taip

Saugumas

Apsaugos algoritmų palaikymas	SNMP, SNMPv2, SNMPv3
VPN tunelių kiekis	50

Savybės

Flash atmintis	128 MB
Vidinė atmintis	512 MB
Vidinės atminties tipas	DDR4

Konstrukcija

Produkto spalva	Juoda
LED indikatoriai	Taip

Energijos valdymas

Išėjimo įtampa	12 V
Išėjimo srovė	1 A

Aplinkos sąlygos

Darbo temperatūros diapazonas (TT)	0 - 40 °C
Sandėliavimo temperatūros norma (T-T)	-40 - 70 °C
Darbo santykinės drėgmės diapazonas	10 - 90%
Sandėliavimo santykinis drėgmės diapazonas	5 - 90%

Svoris ir matmenys

Plotis	226 mm
Ilgis	131 mm
Aukštis	35 mm

Matmenys ir svoris

Matmenys (I × P × A)	27,00cm × 25,00cm × 7,00cm
Svoris	1,54kg

Dokumentai ir vaizdo įrašai

- › [Naudojimo instrukcija](#)
- › [Gaminio lankstinukas](#)
- › [Saugos informacija](#)
- › [Vaizdo įrašas](#) youtube.com/watch?v=aexJ6vnPmqc

Gamintojo ir saugos informacija

GAMINTOJAS

TP-Link

ATSAKINGAS ASMUO ES

TP-Link Deutschland GmbHNiederkasseler Lohweg 175, 40547 Düsseldorf,
DEtp-link.com

PLATINTOJAS

MB KOMPIUTERIŲ GURUV. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Saugos dokumentai

[› Saugos informacija](#)