

Epson PLQ-35 dot matrix printer 180 x 360 DPI 540 cps

Gamintojas: **EPSON** · Modelis: **C11CJ11401** · EAN: **8715946674636** · Prekės kodas: **905566**



428,90 €

Kaina su PVM

Be PVM: **354,46 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Quiet operation: Noise levels as low as 55dBA
- ✓ Energy-efficient: 4.5W standby power consumption
- ✓ Low TCO: Long-life ribbon
- ✓ Flexible: Handles passbooks up to 2.6mm thick
- ✓ Easy installation: Parallel, serial and USB interfaces

Aprašymas

Fast, quiet passbook printer

A quiet, fast and power-efficient passbook printer with a low TCO, ideal for financial and government institutions.

Customers and staff alike will appreciate the PLQ-30's unobtrusive noise levels, which are as low as 55dBA. It's efficient, too – the print speed enhancer enables fast printing of bit image data under Windows environments to help cut queues.

Low total cost of ownership

Delivering substantial cost and energy savings, the PLQ-30 has a very low standby power consumption of 4.5W. Further reducing TCO, it can print around 10 million characters in draft mode between ribbon changes.

Flexible

It offers excellent passbook handling and data processing flexibility, thanks to its 128kb memory and capacity for passbooks up to 2.6mm thick.

Easy installation

Simple to install, the PLQ-30 features a choice of emulations plus parallel, serial and USB interfaces as standard for an easy fit into most IT environments.

Ultra-high-speed draft mode

High speed print speeds of 585 cps.

Techninė specifikacija

Printing	
Maximum print speed	540 cps
Maximum resolution	180 x 360 DPI
Maximum printing width (columns)	94
Maximum print speed (draft)	360 cps
Maximum print speed (LQ)	120 cps
Maximum print speed (NLQ)	180 cps
Character pitch	10 cpi
Maximum number of copies	6 copies
Built-in barcodes	CODABAR (NW-7), Code 128 (A/B/C), Code 39, EAN13, EAN8, Industrial 2/5, Interleaved 2/5, Matrix 2/5, POSTNET, UPC-A, UPC-E
Bitmap fonts	Courier, Draft, OCR-B, Orator, Orator-S, Prestige, Roman, Sans Serif, Script, Script C
Scalable fonts	Roman T, Sans Serif H
Character sets	PCAPTEC, PC437, PC708, PC720, PC850, PC858, PC864, PCAR864, ISO 8859-15, Roman 8, Italic
Number of characters	14
Paper handling	
Multi-part paper thickness range	0.12 - 0.53 mm
Single sheet thickness range	0.065 - 0.19 mm
Features	
Product colour	White
Buffer size	128 KB
Sound pressure level (printing)	55 dB
Page description languages	Epson ESC/P2, PPDS
Country of origin	Indonesia
Ports & interfaces	
Standard interfaces	Parallel, RS-232, USB 2.0
Endurance	
Print head	24-pin

Print head life	400 million characters
Mean time between failures (MTBF)	35000 h
Power	
Power consumption (typical)	61 W
Power consumption (standby)	0.7 W
AC input voltage	220-240 V
AC input frequency	50 - 60 Hz
Operational conditions	
Operating temperature (T-T)	5 - 38 °C
Storage temperature (T-T)	-30 - 60 °C
Operating relative humidity (H-H)	10 - 85%
Weight & dimensions	
Width	384 mm
Depth	280 mm
Height	203 mm
Weight	7.8 kg
Packaging data	
Quantity per pack	1 pc(s)
Package width	365 mm
Package depth	455 mm
Package height	255 mm
Package weight	9.27 kg
Other features	
Print technology	Dot matrix
Needles	24 (2 x 12)
Logistics data	
Products per pallet (UK)	48 pc(s)
Pallet weight (UK)	0 g
Harmonized System (HS) code	84433210
Matmenys ir svoris	
Svoris	9,33kg

Dokumentai ir vaizdo įrašai

- > [Naudojimo instrukcija](#)
- > [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

Seiko Epson

Owa, Suwa 3-3-5, Nagano, JP
corporate.epson

ATSAKINGAS ASMUO ES

Epson Deutschland

Schiessstraße 49, D-40549 Düsseldorf, DE
epson.de

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt