

Epson LQ-630 dot matrix printer 360 x 180 DPI 360 cps

Gamintojas: **EPSON** · Modelis: **C11C480141** · EAN: **8715946538068** · Prekės kodas: **905592**



528,90 €

Kaina su PVM

Be PVM: **437,11 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Paprastas ir pasiekiamas: Aiškus valdymas naudojant 3 eilučių šviesos diodų valdymo skydą
- ✓ Planšetinė technologija: Popierius išstumiamas priekyje, todėl prieiga yra paprasta
- ✓ Laikmenos pasirinkimas: Taip pat spausdina ant nedidelių nupjautų popieriaus lapų
- ✓ Kokybė ir sparta: Aukštos kokybės 24 kontaktų spausdinimas iki 360 cps
- ✓ Kelių dalių lankstumas: Spausdina iki 5 dalių formas (1 originalas + 4 kopijos)



Aprašymas

„Epson LQ-630“ yra nebrangus, aukštos kokybės adatinis spausdintuvas, idealiai tinkantis naudoti ant prekystalių

„Epson LQ-630“ yra greitas, paprastas naudoti ir patikimas visur, áskaitant parduotuves, bankus, padtus, gydytojų kabinetus ir bilietų kioskus, taip pat gamybos, prekybos ir paslaugų ámones

Techninė specifikacija

Printing

Colour	No
Maximum print speed	360 cps
Maximum resolution	360 x 180 DPI
Maximum printing width (columns)	80
Maximum print speed (draft)	225 cps
Maximum print speed (LQ)	79 cps
Character pitch	10,12 cpi
Maximum number of copies	5 copies
Built-in barcodes	Code 39, POSTNET, UPC-A, UPC-E

Paper handling

Maximum print size	254 x 559 mm
Paper tray media types	Labels, Roll

Features

Product colour	Grey
Buffer size	32 KB
Sound pressure level (printing)	57 dB
Page description languages	Epson ESC/P2, PPDS
Country of origin	China

Ports & interfaces

Standard interfaces	Parallel, USB 2.0
---------------------	-------------------

Endurance

Print head	24-pin
Print direction	Bidirectional
Print head life	400 million characters
Ribbon life (black, draft)	2 million characters
Mean time between failures (MTBF)	10000 h

Power

Power consumption (typical)	20 W
Power consumption (standby)	4.8 W
AC input voltage	220 - 240 V

Operational conditions

Operating temperature (T-T)	5 - 35 °C
-----------------------------	-----------

Operating relative humidity (H-H)	10 - 80%
System requirements	
Windows operating systems supported	Windows 2000, Windows 7, Windows 8, Windows 98, Windows XP
Bundled software	Epson Status Monitor
Weight & dimensions	
Width	386 mm
Depth	306 mm
Height	185 mm
Weight	3.5 kg
Packaging data	
Quantity per pack	1 pc(s)
Package width	265 mm
Package depth	455 mm
Package height	310 mm
Package weight	5.2 g
Other features	
Print technology	Dot matrix
Standard media sizes	Sheet Paper (single- and multi-layer), Continuous Paper (single- and multi-layer), Labels (single- and multi-layer), Roll Paper
Needles	24
Logistics data	
Products per pallet	35 pc(s)
Pallet gross width	120 cm
Pallet gross height	100 cm
Products per pallet layer	5 pc(s)
Products per pallet layer (UK)	7 pc(s)
Products per pallet (UK)	49 pc(s)
Pallet length (UK)	120 cm
Pallet width (UK)	100 cm
Pallet height (UK)	2 m
Harmonized System (HS) code	84433210
Matmenys ir svoris	
Matmenys (I × P × A)	45,00cm × 31,00cm × 26,00cm
Svoris	4,52kg

Gamintojo ir saugos informacija

GAMINTOJAS

Seiko Epson

Owa, Suwa 3-3-5, Nagano, JP

corporate.epson

ATSAKINGAS ASMUO ES

Epson Deutschland

Schiessstraße 49, D-40549 Düsseldorf, DE

[epson.de](https://www.epson.de)

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt