

D-Link DWM-311 mobiliojo ryšio įrenginys

Gamintojas: **D-LINK** · Modelis: **DWM-311** · EAN: **790069475238** · Prekės kodas: **905627**



139,90 €

Kaina su PVM

Be PVM: **115,62 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Transfer speeds of up to 150 Mbps for fast internet access and data transfer
- ✓ 1 x WAN/LAN 10/100/1000 Ethernet port for high-speed connectivity
- ✓ 1 x SIM slot
- ✓ No set up required, simply plug in and your network is ready to go
- ✓ Zinc-plated steel case is durable, resistant to corrosion and built to ensure a longer product life cycle
- ✓ Able to operate in temperatures between -30 to 60°C
- ✓ Wall mounts allow for optimal placement



Aprašymas

Scalable LTE M2M Routing Solution

The DWM-311 is a robust 4G LTE modem fully prepared to go out in the field. Blazing fast speeds guarantee Machine to Machine (M2M) communications. It offers economical and reliable connectivity suitable for the most demanding Internet of Things (IoT) applications. This cost-effective device is here to offer complete connectivity, straight out the box.

Connectivity Where You Need It Most

Easily connect to your high-speed 3G/4G LTE mobile connection with the DWM-311 4G LTE M2M Router, and enjoy fast downlink speeds of up to 150 Mbps, giving you the speed you need for fast, responsive Internet access. Deploy it in a remote location to access IP cameras and systems remotely.

Robust Build Quality

The industrial-grade casing provides reliable high-speed connectivity in extreme conditions. The corrosion-resistant zinc-plated steel case and wide operating temperature and humidity tolerance mean that the DWM-311 is ready for the most demanding M2M applications in virtually any environment. Wall mounts allow the DWM-311 to be mounted virtually anywhere.

Network Agility for Enterprise IoT Management

D-Link offers the latest advanced EaaS (Edge as a Service) cloud computing platform to enable flexible, secure and low latency networks for mission critical operations.

With fast, flexible deployment and having full control and visibility over your network, the D-ECS D-Link Edge Cloud Solution platform offers extensive functionality enabling device management, traffic analytics, security, cost-management and more.

Techninė specifikacija

Konstrukcija	
Produkto spalva	Juoda
Atstatymo mygtukas	Taip
LED indikatoriai	Taip
Ethernet LAN funkcijos	
Eterneto LAN duomenų perdavimo norma	10,100,1000 Mbit/ai
Tinklo standartai	IEEE 802.3i, IEEE 802.3u
Mobilusis ryšys	
4G standartai	LTE
Ryšys	
Ethernet LAN (RJ-45) portų kiekis	1
Sertifikatai	
Atitikties sertifikatai	CE, RoHS
Veikimo charakteristikos	
Web pagrįstas valdymas	Taip
Aplinkos sąlygos	
Darbo temperatūros diapazonas (TT)	-30 - 60 °C

Sandėliavimo temperatūros norma (T-T)	-40 - 85 °C
---------------------------------------	-------------

Darbo santykinės drėgmės diapazonas	10 - 85%
-------------------------------------	----------

Svoris ir matmenys

Plotis	77,4 mm
--------	---------

Ilgis	68,5 mm
-------	---------

Aukštis	26 mm
---------	-------

Svoris	145 g
--------	-------

Matmenys ir svoris

Matmenys (I × P × A)	7,00cm × 8,00cm × 3,00cm
----------------------	--------------------------

Svoris	0,54kg
--------	--------

Dokumentai ir vaizdo įrašai

- › [Naudojimo instrukcija](#)
- › [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

D-Link

ATSAKINGAS ASMUO ES

D-Link Benelux

Postbus 48, 5480 AA Schijndel, NL
[dlink.com](https://www.dlink.com)

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt