

D-Link DWM-314-GP/B modemai

Gamintojas: **D-LINK** · Modelis: **DWM-314-GP/E** · EAN: **790069475283** · Prekės kodas: **905718**



469,90 €

Kaina su PVM

Be PVM: **388,35 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 5G speeds of up to 3.4 Gbps¹ for ultra-fast Internet access and data transfer
- ✓ 2 x 10/100/1000 Ethernet LAN ports for high-speed connectivity
- ✓ 2 x 10/100/1000 Ethernet PoE LAN ports for PoE-enabled connectivity
- ✓ 2 x SIM slots for plug-and-play connectivity with failover
- ✓ No set up required, simply plug it in and your network is ready to go
- ✓ Durable zinc-plated steel case is corrosion-resistant to ensure device longevity
- ✓ -30 to 70°C operating temperature to resist harsh environments
- ✓ Wall or DIN-rail mounting allow for optimal device placement



Aprašymas

Powering Smart City Innovations with 5G

The DWM-314-GP 5G Multi-Connect PoE modem harnesses the power of 5G to deliver ultra-fast speeds and low latency, ensuring dependable connectivity. Featuring dual SIM slots with failover capabilities, it provides uninterrupted service even if one network is down. Ideal for constructing smart city infrastructures such as smart poles for traffic monitoring, digital signage advertising, and environmental sensing, this plug-and-play modem simplifies installation for quick deployment. With its ability to switch seamlessly between 4G and 5G, the DWM-314-GP maintains stable connectivity in varying network conditions, enhancing local engagement by delivering timely information, advertisements, and services efficiently.

Empower Your M2M Network with PoE+

The DWM PoE Modem Series, featuring a built-in 4-port Gigabit switch and 802.3af/at Power over Ethernet (PoE+) technology, delivers both data and power through Ethernet cables. As a true PSE (Power Sourcing Equipment) solution, it streamlines M2M communication for IoT applications, reducing the need for separate electrical infrastructure and lowering installation costs of extra PoE switch. Ideal for powering surveillance cameras, digital signage, wireless access points, and IoT sensors, it offers flexible device placement without extra wiring. Its PD-Alive feature minimizes downtime, ensuring continuous operation, while PoE scheduling optimizes power use and cuts energy costs.

Robust Build Quality

The industrial-grade casing provides reliable high-speed connectivity in extreme conditions. The corrosion-resistant zinc-plated steel case with wide operating temperature range and humidity tolerance mean that the DWM-314-GP is ready for the most demanding M2M applications in virtually any environment. Convenient wall and DIN-rail mounting options allow the DWM-314-GP to be mounted virtually anywhere to optimize signal quality.

The DWM-314-GP is also engineered to safely accept wide input voltage(VDC 48~57V) fluctuations, providing more flexibility and convenience when selecting a suitable power source, making your M2M installations significantly more reliable and much easier to deploy.

Seamless 5G PoE Power for Reliable Connectivity

The DWM-314-GP 5G Multi-Connect PoE Modem delivers ultra-fast 5G and Ethernet connectivity with instant, driverless access—no pre-configuration required. Its plug-and-play design and intuitive web interface make it ideal for versatile applications, simplifying network setup and management. Equipped with two fast Ethernet LAN ports for reliable wired connectivity and dual Gigabit Ethernet ports and 802.3af/at PoE functionality, the DWM-314-GP powers and connects multiple Ethernet PD devices simultaneously, reducing the need for additional PoE switches. Its auto-reboot feature ensures device stability by restoring unresponsive devices. Perfect for powering IP cameras, access points, vending machines, and NVRs, this modem is the ideal solution for traffic lights, retail stores, surveillance systems, and smart infrastructure like bus stops.

Techninė specifikacija

Modemas	
Sąsaja	2x RJ45, 2x RJ45 PoE
Antenos tipas	Išorinis
Veikimo charakteristikos	
Tinklo standartai	IEEE 802.3at
Savybės	
Produkto spalva	Juoda
LED indikatoriai	Taip
Maitinimo LED	Taip
Ryšys	
Ethernet LAN (RJ-45) portų kiekis	4
Energijos valdymas	
DC įėjimo įtampa	48 - 57 V
Aplinkos sąlygos	
Darbo temperatūros diapazonas (TT)	-30 - 70 °C

Darbo santykinės drėgmės diapazonas	10 - 95%
-------------------------------------	----------

Sandėliavimo temperatūros norma (T-T)	-40 - 85 °C
---------------------------------------	-------------

Svoris ir matmenys

Ilgis	99 mm
-------	-------

Aukštis	40 mm
---------	-------

Plotis	131 mm
--------	--------

Matmenys ir svoris

Svoris	1,60kg
--------	--------

Dokumentai ir vaizdo įrašai

› [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

D-Link

ATSAKINGAS ASMUO ES

D-Link Benelux

Postbus 48, 5480 AA Schijndel, NL
dlink.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt