

ATEN USB & HDMI Extender CAT5e/6, USB2.0 Full Speed (12Mbit/s) 1080P (40m) / 1080i (60m)

Gamintojas: **ATEN** · Modelis: **VE803** · EAN: **4710423779716** · Prekės kodas: **905911**



89,90 €

Kaina su PVM

Be PVM: **74,30 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Uses two Cat 5e cables to connect the local and the remote units
- ✓ Extends 1080p by 40m; extend 1080i by 60m
- ✓ Superior video quality – HDTV resolutions of 480p, 720p, 1080i, 1080p (1920 x 1080), VGA, SVGA, XGA, SXGA, UXGA and WUXGA (1920 x 1200)
- ✓ Supports USB touch panel
- ✓ 8 segment equalization adjustment switch optimizes display quality
- ✓ Support Dolby True HD and DTS HD Master Audio
- ✓ Built-in 8KV/15KV ESD protection
- ✓ Transparent USB Support – supports all USB 2.0 full speed device (up to 12 Mbps)
- ✓ Supports wide screen formats
- ✓ HDMI (3D, Deep Color); HDCP compatible – signaling rates up to 2.25Gbits

Aprašymas

The VE803 HDMI USB Extender extends an HDMI signal up to 60 meters from the HDMI source using two Cat 5e cables. It is capable of sending 1080i signals up to 60 meters and 1080p signals up to 40 meters.

The VE803 is equipped with USB connectors which allow you to extend any USB device between the units. The USB feature also provides support for touch panel control, allowing you to control the local HDMI source device from the remote display, or control the remote display through the local unit.

1x VE803T HDMI USB Extender
1x VE803R HDMI USB Extender
1x OAD6-1705-10EG Power Adapter
1x USB Cable (1.8 m)
1x Mounting Kit
1x User Instructions

Techninė specifikacija

Features	
Type	AV transmitter & receiver
Maximum resolution	1920 x 1200 pixels
Cable types supported	Cat5e
Maximum transfer distance	60 m
Extended display identification data (EDID)	Yes
Electrostatic Discharge (ESD) protection	Yes
Electrostatic Discharge (ESD) protection	15 kV
Supported video modes	1080i, 1080p
Supported graphics resolutions	640 x 480 (VGA), 800 x 600 (SVGA), 1024 x 768 (XGA), 1280 x 1024 (SXGA), 1600 x 1200 (UXGA), 1920 x 1080 (HD 1080), 1920 x 1200 (WUXGA)
Bandwidth	6.75 Gbit/s
Bandwidth	225 MHz
HDCP	Yes
Material	Metal
3D	Yes
Product colour	Black
Ports & interfaces	
Connectivity technology	Wired
HDMI in	1
Number of HDMI outputs	1
USB connector type	USB Type-A, USB Type-B
DC-in jack	Yes
Power	
Operating voltage (transmitter)	5 V
Operating voltage (receiver)	5 V
Power consumption (TX)	1.04 W
Power consumption (RX)	0.75 W
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	0 - 80%
Storage relative humidity (H-H)	0 - 80%

Weight & dimensions

Weight	495 g
Receiver dimensions (WxDxH)	90 x 57.4 x 24 mm
Receiver weight	160 g
Transmitter dimensions (WxDxH)	90 x 57.4 x 24 mm
Transmitter weight	160 g

Packaging data

Package width	59 mm
Package depth	239 mm
Package height	160 mm
Package weight	652 g

Packaging content

AC adapter included	Yes
Cables included	USB
Manual	Yes
Mounting kit	Yes

Logistics data

Master (outer) case width	315 mm
Master (outer) case length	490 mm
Master (outer) case height	338 mm
Master (outer) case gross weight	13.5 kg
Master (outer) case net weight	9.9 kg
Products per master (outer) case	20 pc(s)

Matmenys ir svoris

Svoris	0,65kg
--------	--------

Dokumentai ir vaizdo įrašai[› Gaminio lankstinukas](#)**Gamintojo ir saugos informacija**

GAMINTOJAS

ATEN INTERNATIONAL CO., LTD.

Datung Road No.125, Sec. 2, 221 New Taipei City, TW

[aten.com](https://www.aten.com)

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt