

Lenovo ThinkSystem SR665 V3 server Rack (2U) AMD EPYC 9135 3.65 GHz 32 GB DDR5-SDRAM 750 W

Gamintojas: **LENOVO** · Modelis: **7D9AA03PEA** · Prekės kodas: **905942**



6 995,91 €

Kaina su PVM

Be PVM: **5 781,74 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ No OS
- ✓ AMD EPYC 9135 (64MB Cache, 3.65GHz)
- ✓ 32GB (4800MHz) DDR5-SDRAM (1 x 32)

Aprašymas

The Lenovo ThinkSystem SR665 V3 is a 2-socket 2U server that features the AMD EPYC 9004 "Genoa" family of processors. With up to 128 cores per processor and support for the new PCIe 5.0 standard for I/O, the SR665 V3 offers the ultimate in two-socket server performance in a 2U form factor.

This product guide provides essential pre-sales information to understand the ThinkSystem SR665 V3 server, its key features and specifications, components and options, and configuration guidelines. This guide is intended for technical specialists, sales specialists, sales engineers, IT architects, and other IT professionals who want to learn more about the SR665 V3 and consider its use in IT solutions.

Techninė specifikacija

Processor

Processor family	AMD EPYC
Processor manufacturer	AMD
Processor model	9135
Processor frequency	3.65 GHz
Processor boost frequency	4.3 GHz

Processor cores	16
Processor cache	64 MB
Number of processors installed	1
Thermal Design Power (TDP)	200 W
Memory	
Internal memory	32 GB
Internal memory type	DDR5-SDRAM
Memory ranking	2
Memory clock speed	4800 MHz
Memory layout (slots x size)	1 x 32 GB
Storage	
RAID support	Yes
Optical drive type	No
Supported RAID controllers	940-8i 4GB
Internal drive bays	8
Supported storage drive interfaces	SAS
Graphics	
Maximum graphics card memory	16 MB
Network	
Ethernet LAN	Yes
Cabling technology	10/100/1000Base-T(X)
Ethernet interface type	Gigabit Ethernet
Ports & interfaces	
Ethernet LAN (RJ-45) ports	1
USB 2.0 ports quantity	1
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	4
VGA (D-Sub) ports quantity	1
Design	
Chassis type	Rack (2U)
Product colour	Black
Rack mounting	Yes
Performance	
Performance management	XClarity Controller Platinum
Trusted Platform Module (TPM)	Yes

Trusted Platform Module (TPM) version	2
Software	
Operating system installed	No
Compatible operating systems	Microsoft Windows Server, Red Hat Enterprise Linux, SUSE Linux Enterprise Server, VMware ESXi, Ubuntu Server
Power	
Redundant power supply (RPS) support	Yes
Power supply	750 W
Number of redundant power supplies installed	1
Operational conditions	
Operating temperature (T-T)	5 - 45 °C
Storage temperature (T-T)	-40 - 60 °C
Operating relative humidity (H-H)	8 - 90%
Storage relative humidity (H-H)	8 - 90%
Operating altitude	0 - 3050 m
Certificates	
80 PLUS certification	80 PLUS Titanium
Weight & dimensions	
Width	445 mm
Depth	766 mm
Height	87 mm
Technical details	
Supported storage drives form factor (internal)	2.5"
Matmenys ir svoris	
Svoris	5,10kg

Gamintojo ir saugos informacija

GAMINTOJAS

Lenovo Group Limited

Courtyard Xibeiwang East Road Building 2, No.10,
100094 Beijing, CN

[lenovo.com](https://www.lenovo.com)

ATSAKINGAS ASMUO ES

Lenovo France SAS

Rue des Deux Gares 20, 92500 Rueil-Malmaison,
FR

[lenovo.com](https://www.lenovo.com)

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt