

Vertiv Geist VP4G30AR power distribution unit (PDU) 42 AC outlet(s) 0U Black

Gamintojas: **VERTIV** · Modelis: **VP4G30AR** · EAN: · Prekės kodas: **906417**



1 089,90 €

Kaina su PVM

Be PVM: **900,74 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ The Monitored RPDU provides access to power usage data so you can see trends and maximize uptime
- ✓ VP4G30AR is a vertical rack mount PDU with 36 IEC C13 and 6 IEC C19 outlets and a 1P+N+E (IP44) plug
- ✓ Vertiv Geist Next-Generation IMD has a 128x128 high-contrast LCD for monitoring data
- ✓ Helps ensure that data and operations are protected with the enhanced security features
- ✓ Vertiv Geist rPDUs are individually tested, CE Marked, Complies with IEC 60950-1 (CB Certificate Available), and RoHS certified



Aprašymas

The Vertiv Geist Monitored RPDU VP4G30AR is a 32A, 230V, 0U, vertical rack power distribution unit with input power monitoring. It has (36) IEC C13 and (6) IEC C19 outlets and a 1P+N+E (IP44) providing 7.3kW of power capacity. This device offers quick access to critical power usage information down to the device level to evaluate energy usage trends and maximize uptime. It is integrated with the Vertiv Geist Next-Generation IMD which displays power data via its 128x128 high-visibility LCD. It has an internal sensor that intelligently adjusts the orientation based on horizontal or vertical installation. This includes a redundant power-sharing port that connects two IMDs in the rack and provides backup power in case of power loss. Enhanced security with a secure boot is added to the device to help ensure data and operations are protected. The units are CE Marked, comply with IEC 60950-1 (CB Certificate Available), RoHS certified, and are individually tested for functionality and reliability.

Techninė specifikacija

Design	
PDU types	Monitored
Rack capacity	0U
Type	Single-phase
Mounting	Vertical
Product colour	Black
Display	LCD
On/off switch	No
Ports & interfaces	
AC outlets quantity	42 AC outlet(s)
AC outlet types	C13 coupler, C19 coupler
Power plug	IEC 60309
Serial ports quantity	1
Ethernet LAN (RJ-45) ports	1
USB ports quantity	1
Features	
Reset button	Yes
Cable length	3.05 m
Management features	
Monitoring	Current, Power, Voltage
Supported network protocols	DHCP, HTTP, HTTPS, IPv4, IPv6, LDAP, NTP, RADIUS, RSTP, SSH, SMTP, SNMP (v1/v2c/v3), Syslog, TACACS+, Modbus TCP
Power	
Nominal input voltage	200-240 V
Maximum current	32 A
AC input frequency	50/60 Hz
Nominal output voltage	32 V
Load capacity	230 VA
Power protection features	Over current
Maximum power	7300 W
Certificates	
Certification	CE Marked UKCA Marked Complies with IEC 62368-1 (DOC Available) Complies with EN 55032 and EN 55035 RoHS Compliant C ₀ Mark

Operational conditions

Operating temperature (T-T)	10 - 45 °C
-----------------------------	------------

Weight & dimensions

Width	51 mm
Depth	51 mm
Height	1778 mm
Weight	7.26 kg

Matmenys ir svoris

Matmenys (l × P × A)	222,00cm × 22,00cm × 16,00cm
Svoris	9,02kg

Dokumentai ir vaizdo įrašai[› Gaminio lankstinukas](#)**Gamintojo ir saugos informacija**

GAMINTOJAS

Vertiv

ATSAKINGAS ASMUO ES

Vertiv GmbHAugust-Everding-Str 25, 81671 München, DE
[vertiv.com](https://www.vertiv.com)

PLATINTOJAS

MB KOMPIUTERIŲ GURUV. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt