Axagon ADS-1PSN USB-A 2.0 - serial RS-232 DB9-M Prolific adapter cable 1.5m - Adapter - Digital/Daten serijinis kabelis Juoda 1,5 m USB A tipo

Gamintojas: **AXAGON** · Modelis: **ADS-1PSN** · EAN: **8595247907646** · Prekės kodas: **906979**



13,90 €

Kaina su PVM

Be PVM: **11,49 €**

Sandėlyje

Prekė internetu

Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 1,5 m
- ✓ USB A tipo Kištukinis
- ✓ RS-232 Kištukinis
- ✓ Prolific PL2303GT
- ✓ Juoda
- ✓ 1 vnt













Aprašymas

The AXAGON ADS-1PSN active USB converter easily extends your computer with a RS 232 standard serial port. The seamless compatibility of the USB - serial RS232 adapter is due to the use of an original chip from the Taiwanese company Prolific.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

The fixed 1.5 m long USB-A cable is suitable for use with both a desktop computer and a laptop. The cable is equipped with gold-plated connectors and contacts, the very durable body of the adapter is also suitable for industrial applications. Double shielding protects transmitted signals from adverse interference.

An ideal accessory for your computer to connect barcode readers, cash register printers, scanners, microcontroller programmers, CNC machines, modems, and to upgrade or configure set-top boxes, security devices, switches, transmitters and other devices.

Input:
• USB 480Mbps interface (USB 2.0), backward compatible with USB 1.1.
• Connecting USB type A male connector located on a fixed 1.5 m cable.

Output:
• 1x serial RS-232 port with a DB9 male connector integrated in the adapter’s body.
• Transmission rate adjustable in range 75 bit/s - 1000 kbit/s.
• Compatible with 16C950 UART, backward compatible with 16C550, 16C650, 16C750 and 16C850.

Other features:
• Plug and Play support.
• FIFO buffer sending 768B and receiving 256B.
• Adjustable flow control Xon/Xoff, hardware or none.
• Adjustable word length 4, 5, 6, 7 or 8 bits.
• Adjustable parity (even, odd, none, mark, space), 1, 1.5 or 2 stop bits.
• Adjustable usage of the FIFO buffer: receiving (1 - 14b) and sending (1 - 16b).
• Adjustable number of the port COM1 to COM256.
• Power Management support.
• Adapter power supply via USB (bus power) - no auxiliary power supply required.
• Gold-plated connectors and contacts ensure a reliable connection and, by preventing oxidation, ensure a long life of the converter.
• Outer cable diameter 5 mm, double shielding.
• Original Prolific PL2303GT chipset with integrated serial line driver is used.
• Adapter body dimensions 35 x 56 x 17 mm, cable length 1.5 m.
• Adapter weight 83 g (including cable).

Supported OS:
• MS Windows XP / Vista / 7 / 8 / 8.1 / 10 / 11 and later, Windows Server 2003 / 2008 / 2012 / 2016 / 2019 / 2022 and later (supported are all 32 and 64-bit versions of Windows OSs), MacOS X 10.4.x and later, Linux with kernel 2.6.x and later, Android most versions.
• Note: Drivers are included with supported operating systems and are installed completely automatically.

Package contains:
• USB - serial adapter with a 1.5 m long permanently attached USB cable,
• multilingual manual CZ / DE / DK / ENG / ESP / FIN / FR / GR / HR / HU / IT / NL / PL / PT / RO / RU / SK / SWE / TR / BG / CN / ARA,
• packed in a cardboard box with a hanging hole.

Techninė specifikacija

Savybės	
Produkto spalva	Juoda
Kabelio ilgis	1,5 m
Jungtis 1	USB A tipo
Jungtis 2	RS-232

1 jungtis – vidinė ar išorinė	Kištukinis
2 jungtis – vidinė ar išorinė	Kištukinis
Dažnių juostos plotis	1000 Kbit/ai
Kilmės šalis	Kinija
Lustų rinkinys	Prolific PL2303GT
Palaikomos „Windows“ operacinės sistemos	Taip
Palaikomos MAC operacinės sistemos	Taip
Palaikoma operacinė sistema „Linux“	Taip
Palaikomos serverio valdymo sistemos	Taip
Suderinami produktai	barcode readers, cash register printers, scanners, microcontroller programmers, CNC machines, modems, and to upgrade or configure set-top boxes, security devices, switches, transmitters and other devices

Pakuotės duomenys

Kiekis pakuotėje	1 vnt
Pakuotės tipas	„Box“
Pakuotės plotis	150 mm
Pakuotės gylis	92 mm
Pakuotės aukštis	28 mm
Paketo svoris	112 g

Sertifikatai

Atitikties sertifikatai	RoHS, CE
Sertifikavimas	CE, RoHS

Svoris ir matmenys

Kabelio skersmuo	5 mm
Plotis	35 mm
Ilgis	56 mm
Aukštis	17 mm
Svoris	83 g

Pakuotės turinys

Instrukcija	Taip

Logistikos duomenys

Garantinis laikotarpis	3 metai

Matmenys ir svoris

Matmenys (I × P × A)	9,00cm × 15,00cm × 3,00cm
Svoris	0,11kg

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Dokumentai ir vaizdo įrašai

› Naudojimo instrukcija

Gamintojo ir saugos informacija

GAMINTOJAS

RealQ, s.r.o.
Železná 663/5, 619 00 Brno-jih, CZ
axagon.eu

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt