InLine 35795I USB cable USB 3.2 Gen 2 (3.1 Gen 2) 5 m USB C Black

Gamintojas: **INLINE** · Modelis: **35795I** · EAN: **4043718343478** · Prekės kodas: **907636**



142,90 €

Kaina su PVM

Be PVM: **118,10 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 5 m
- ✓ USB C Straight Male
- ✓ USB C Straight Male
- ✓ USB 3.2 Gen 2 (3.1 Gen 2) 10000 Mbit/s USB Power Delivery (USB PD) 60 W
- ✓ Black
- ✓ 1 pc(s)





Aprašymas

Maximum transmission quality up to 8K@60Hz: Supports modern video formats such as 8K@60Hz or 4K@120Hz – perfect for professional AV applications with the highest demands.
Adaptive 5-fibre structure: One of the OM3 fibres is adaptively usable (DP or USB) – for flexible switching between pure video transmission or video with USB data channel.
Active optical hybrid technology (AOC): Combination of copper and fibre optic cables for loss-free transmission over long distances without an external power supply or repeater.
DisplayPort Alt Mode via USB-C with HDR support: Compatible with DP Alt Mode (4-lane/2-lane) – including HDR10, HDCP 2.2, EDID and 3D support.
Robust construction for professional applications: Metal housing, flexible cable sheath, OM3 fibres and copper conductors for durability in AV, industrial or test environments.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

The InLine® USB 3.2 Gen.2 AOC cable from the 3579xI series is the high-end solution for demanding AV, data and docking applications with variable use. The unique adaptive fibre architecture allows either the use of all four lanes for DisplayPort 2.1 or a combination of 2x DP + 2x USB 3.2 (10 Gbps), depending on requirements. This enables resolutions of up to 8K@60Hz or 4K@120Hz, or alternatively 4K@60Hz with simultaneous high-speed data transfer. Active optical transmission (AOC) also allows longer cable lengths to be used without any loss of quality or external power supply.
Support for HDR10, HDCP 2.2, EDID, 3D and USB Power Delivery (up to 60W) round off the profile – ideal for modern AV systems, high-resolution displays, docking solutions and technical test environments.

USB-C plug to USB-C plug
Supports DP Alt Mode (4-lane or 2-lane)
Supports HDR10, HDCP 2.2, EDID, 3D
Data transfer: up to 10 Gb/s (USB 3.2 in 2-lane mode), 480 Mb/s (USB 2.0 at full video utilisation)
Video resolution: up to 8K@ 60Hz or 4K@120Hz
Power delivery: up to 20 V / 3 A (60W)
Plug-and-play without external power supply
Cable type: 5x OM3 fibre (1 adaptive), 8x copper conductors
Bending radius: 30 mm
Operating temperature: 0–50 °C
Storage temperature: -20–70 °C
Metal housing

Techninė specifikacija

Features	
USB version	USB 3.2 Gen 2 (3.1 Gen 2)
Connector 1	USB C
Connector 2	USB C
Connector 1 gender	Male
Connector 2 gender	Male
Product colour	Black
Connector 1 form factor	Straight
Connector 2 form factor	Straight
Connector housing material	Metal
Maximum data transfer rate	10000 Mbit/s
Maximum data transfer rate	10 Gbit/s
Cable type	Round cable
Plug and Play	Yes
USB Power Delivery (USB PD)	Yes
USB Power Delivery up to	60 W
USB Type-C DisplayPort Alternate Mode	Yes
DisplayPort version	1.4
Maximum resolution	7680 x 4320 pixels

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Maximum refresh rate	144 Hz
High Dynamic Range (HDR) supported	Yes
High Dynamic Range (HDR) technology	High Dynamic Range 10 (HDR10)
HDCP	Yes
HDCP version	2.2
3D	Yes
Power	
Output voltage	20 V
Output current (max)	3 A
Weight & dimensions	
Cable length	5 m
Cable diameter	5 mm
Width	14 mm
Depth	5000 mm
Height	9 mm
Weight	334 g
Bend radius (min)	3 cm
Dimensions (WxDxH)	14 x 5000 x 9 mm
Packaging data	
Package type	Box
Package width	155 mm
Package depth	170 mm
Package height	55 mm
Package weight	407 g
Packaging content	
Quantity per pack	1 pc(s)
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-20 - 70 °C
Certificates	
Compliance certificates	CE, TÜV mark
Logistics data	
Package volume	0 cm³
Country of origin	Taiwan

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Gamintojo ir saugos informacija

GAMINTOJAS

InLine

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt